



ProFlow Pumping Solution
 ProFlow Pumping Solutions
 2850 W. 139th Street
 Blue Island IL 60406
 United States

Quote

#QTE2752

10/31/2018

Bill To

City of Aurora Illinois (Aurora-IL)
 44 E Downer Place
 AURORA IL 60507
 United States

Expiration Date: 1/6/2019

Expiration Date	Job Reference Number	Sales Rep	Shipping Method
1/6/2019	19-20180566	ProFlow	

Quantity	Item	Rate	Amount
----------	------	------	--------

2	Pump Skid Placeholder	\$8,531.00	\$17,062.00
---	------------------------------	------------	-------------

ProMinent model DFCU0500351010AR001 hose pump assembly:

The DULCOflex DFCu is a versatile peristaltic pump, which incorporates both hose and tubing technology. The unique roller design offers a lubricant-free housing unlike typical shoe pumps. With pressures up to 116 psi and flow rates to 130 GPM, the DFCu is a great choice for pumping abrasive chemicals, such as inks, slurries, along with sheer sensitive polymers. On customer request, DFCu pumps can be equipped with a controller for precise batch metering. The pumps can be equipped with a Halar-coated pump housing for use in industrial chemical applications.

Capacity Data:

- Flow Rate: 14.1 GPM
- Pressure: 30 PSI

Selected options:

- speed: 35 rpm
- motor type: TEFC 230-460/3/60 20:1 var spd
- hose material: Natural Rubber
- hydraulic connection: ANSI Flange SS
- base plate: base plate, painted steel
- leakage detector: 5-48 VDC, N.O. (use w/ drive)
- orientation: right facing (standard)
- VFD Control: Without VFD
- special version: standard
- discharge pressure: 30 PSI
- approval: CE





ProFlow Pumping Solution
 ProFlow Pumping Solutions
 2850 W. 139th Street
 Blue Island IL 60406
 United States

Quote
 #QTE2752
 10/31/2018

Quantity	Item	Rate	Amount
3	<p>Pump Skid Placeholder ProMinent model DFCU0500351010AL001 hose pump assembly:</p> <p>The DULCOflex DFCu is a versatile peristaltic pump, which incorporates both hose and tubing technology. The unique roller design offers a lubricant-free housing unlike typical shoe pumps. With pressures up to 116 psi and flow rates to 130 GPM, the DFCu is a great choice for pumping abrasive chemicals, such as inks, slurries, along with sheer sensitive polymers. On customer request, DFCu pumps can be equipped with a controller for precise batch metering. The pumps can be equipped with a Halar-coated pump housing for use in industrial chemical applications.</p> <p>Capacity Data: - Flow Rate: 14.1 GPM - Pressure: 30 PSI</p> <p>Selected options: - speed: 35 rpm - motor type: TEFC 230-460/3/60 20:1 var spd - hose material: Natural Rubber - hydraulic connection: ANSI Flange SS - base plate: base plate, painted steel - leakage detector: 5-48 VDC, N.O. (use w/ drive) - orientation: left facing - VFD Control: Without VFD - special version: standard - discharge pressure: 30 PSI - approval: CE</p> <p>**Lead Time for complete shipment: Approximately 8 Weeks ARO; pricing valid for qty (5) or more units to be purchased at a time**</p>	\$8,531.00	\$25,593.00
1	<p>PRO/1037199 *1 Hose to be supplied at no charge with purchase of (5) pumps* 1037199 - DFCA 050 HOSE - NATURAL RUBBER</p> <p>**Subject to ProFlow Pumping Solutions Conditions of Sale with MNS Redline submitted 10/26**</p>	\$0.00	\$0.00





ProFlow Pumping Solution
ProFlow Pumping Solutions
2850 W. 139th Street
Blue Island IL 60406
United States

Quote

#QTE2752

10/31/2018

Total	\$42,655.00
--------------	-------------

This proposal is subject to Pumping Solutions conditions of sale. A copy of Pumping Solutions conditions of sale are attached. Conditions of sale can also be downloaded from: https://proflow.co/wp-content/uploads/2017/09/psi_cos.pdf or a copy can be submitted upon request.

