



Fire Apparatus Quotation for: AURORA FIRE DEPARTMENT



Quotation Number: 126016 Rev: 32

Unit Description: AERM-CYCN-092P

Quote Description: Aerial, Rear Mount, Aluminum, Cyclone, 95-Platform

Salesperson: GREGHANSEN

Salescode	Extended Description	Qty	
TESTING COMPLIANCE STANDARD			
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3340-1137-12C	Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
BUMPERS			
1160-0000	Bumper 10" stainless steel.	1	
1160-0008	3/16" Front Bumper Gravel Shield.	1	
1160-0015	24" Front Bumper Gravel Shield Extension.	1	
BUMPER TRAYS			
1150-0095	Hinged diamond plate lid for center bumper tray. Includes: seal, D-Ring latch and gas shock hold open device.	1	
1150-0120	Bumper tray center of bumper with slats 12 inches deep (approx 11 inches to slats).	1	
FRAME ASSEMBLY			
1250-0005	Frame - Torque box for tandem axle RM aerial.	1	
1250-0072	Torque box modifications to allow for Hendrickson FIREMAAX tandem air ride suspension (for use with CR100/137, 95-Platform and HP100 Platform).	1	
1250-0078	Zinc flame spray coating for integral torque box chassis.	1	
1250-0092	GEOMET coated frame assembly fasteners.	1	
AXLE OPTIONS			

Salescode	Extended Description	Qty	
AXLE OPTIONS			
1025-0022	Meritor RT-50-160 rear tandem axle 52,000 lb. capacity.	1	
1025-0028	Koni shock absorbers for front axle - adjustable.	1	
1025-0030	Stemco sight glass for front axle hubs. Inboard wheel seals will be Chicago Rawhide (or equivalent).	1	
1025-0210	Meritor FL-943 front axle 21,000 lb. Includes maintenance free bushings.	1	
SUSPENSIONS			
1070-0021	Rear suspension FIREMAAX EX air ride (50-54K) rated equal to the capacity of the axles. Requires TB modification on 4-jack aerals. (Raises OAH .5" over springs)	1	
WHEEL OPTIONS			
1050-0001	Alcoa aluminum wheels for front axle (2).	1	
1050-0005	Alcoa aluminum wheels for rear axles (8).	1	
1050-0007	Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals.	1	
1050-0009	Rear axle (tandem) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center caps with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers.	1	
1050-0018	Each inside wheel of the tandem rear axles shall have valve stem extensions.	1	
TIRE OPTIONS			
1060-0043	Two Michelin 425 tires model XZY3 for front axle.	1	
1060-0085	Eight Michelin 12R rear tires with Mud and Snow XDS tread	1	
1060-0119	RWC AirGuard LED tire pressure monitoring valve stem caps (10) for tandem rear axle applications.	1	
BRAKE SYSTEMS			
1100-0001	Meritor EX225H 17" disc brakes for front axle.	1	
1100-0004	Meritor EX225H 17" disc brakes for rear axles, maximum capacity 54,000 lbs.	1	
1100-0006	Parking brake release mounted on the driver's side lower dash.	1	
1100-0008	Brake system air 6X4/6X6.	1	
1100-0020	Compression fittings for all air brake system lines. Includes cab interior air lines as applicable and accessories (if equipped).	1	
1100-0026	G4 Electronic Stability Control (6x4), Includes RSC and ATC. Not available on 6x6 or commercial chassis.	1	

Salescode	Extended Description	Qty	
AIR SYSTEM OPTIONS			
1110-0000-001	Inlet for air system. Location: driver door jamb.	1	
1110-0002	Air dryer Bendix AD-9.	1	
1110-0006	Air lines nylon.	1	
1110-0026	Air horns Hadley e-tone recessed in bumper (PR).	1	
1110-0027	Isolated air tank. Includes pressure protection valve.	1	
1110-0034	Auxiliary air tank to be plumbed to the chassis air horns only.	1	
1110-0050	Air brake lines to have 4 to 6" slack for future service work.	1	
1110-0096	Stainless steel mounting straps for air tank.	4	
ENGINES & TRANSMISSIONS			
1200-0017	Push-button transmission shift selector.	1	
1200-0021	TranSynd, Shell Spirax S6ATF A295, or equivalent synthetic transmission fluid for EVS4000 series.	1	
1200-0096	Electronic speed limiting set at 60 MPH. Note: Axle gear ratio will be as low as possible while allowing for 60 MPH top speed to improve acceleration.	1	
1200-0457	Eng/Trans Cummins X12 525HP with EVS4500 transmission. 2021 EPA Compliant.	1	
SECONDARY BRAKING			
1125-0003	Allison transmission retarder. Pre-select feature will be switched off with this option.	1	
1125-0010	Allison transmission retarder to be programmed at 1/3 off throttle, 1/3 at 4 psi brake pressure, 1/3 at full (10 psi) brake pressure.	1	
EXHAUST OPTIONS			
1225-0060	Exhaust end with fresh air vent for Plymovent exhaust extraction system.	1	
COOLING PACKAGE			
1800-0013	Cooling system for use with Typhoon, Cyclone and Quest chassis. For use with 2010 - 2021 EPA engines. Includes coolant recovery system.	1	
FUEL SYSTEMS			
1350-0011	Fuel pump electric w/re-prime.	1	
1350-0012-669	Fuel shut-off valve. Location: one (1) at fuel tank.	1	
1350-0012-670	Fuel shut-off valve. Location: one (1) inlet side of OEM fuel filter.	1	
1350-0022	Fuel line hose rubber.	1	
1350-0060	Fuel system 60 gallon stainless steel saddle tanks.	1	

Salescode	Extended Description	Qty	
ALTERNATOR			
1700-0008	Alternator Leece Neville dual 320 amp. 560 amp NFPA/540 amp SAE rating. Available only on ISX12 and Detroit EGR Series 60 engines.	1	
BATTERIES			
1400-0031	Stainless steel battery trays with stainless steel covers.	1	
1400-0032	Battery five group 31 1000 CCA (two left / three right). For use with below cab DEF tank only.	1	
CHASSIS OPTIONS			
1680-0005	Thermatic fan clutch.	1	
1680-0007	Drivelines 1810. Required on 1550 lb/ft torque or greater engines. N/A with EVS3000 transmission.	1	
1680-0008	Tow eyes front painted below bumper/cab (PR).	1	
1680-0012	Tow eyes rear frame painted black.	1	
1680-0017	Hot shift PTO.	1	
1680-0076	Receiver. Under front bumper 9K winch receiver. Includes electrical connection for portable winch application. Custom chassis only. NOTE: When facing the receiver, mount electrical connection to the left side.	1	
1680-0096	Receivers. Side underbody 9K winch receivers. Includes (2) side facing- (1) each below body compartment ahead of the rear wheels or as shown on approval drawings for portable winch with electrical connection for winch. NOTE: When facing the receiver, mount electrical connection to the left side. Final location to be approved by engineering.	1	
1680-0188	Aerial hydraulics installed on bottom port of EVS4000/4500 transmission (to allow for flat rear cab floor).	1	
1680-0247	Trailer hitch Class III mounted rear, optimized mounting to be in a raised mounting position.	1	
1680-0250-M58	Diesel Exhaust Fluid (DEF) 5 gallon tank. Location: left side below rear of cab.	1	
1680-0284	Radiator mounted power steering cooler.	1	
CAB MODEL			
1520-0244	Cyclone long cab - 100" wide (67.5" CA).	1	
CAB ROOF TYPE			
1615-0022	Cab roof to have 12" high split raised rear section with full length center waterway trough. For use with rear mount aerial.	1	
CAB BADGE PACKAGE			

Salescode	Extended Description	Qty	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
CAB DOOR OPTIONS			
1550-0003	Rear crew cab doors in the medium position.	1	
1550-0084	All cab exterior entry doors to have 1250 keyed locks.	1	
1550-0159	Interior cab door locks - manual. Will be individually actuated from each respective door. Includes key lock on each exterior cab door handle.	1	
1550-0179-000-J7	Red/Fluorescent Yellow Green Reflexite V98 chevron "A" stripe on lower cab door panel approx 18" high. Stainless steel/painted door panels only. E-ONE cabs only.	1	
1550-0185	Cab door panels aluminum painted multi-tone to match cab interior paint. Includes upper and lower panels with seam below handrail.	1	
1550-0247-657	Door mounted Weldon 8401 series 16" x .75" amber LED flashing arrow strip lights (4) w/clear lenses. Locate lights on each cab door in the outboard position. Lights to be switched with door ajar.	1	
1550-0283	Driver and officer cab door windows with manual regulators. For use with new Typhoon and Cyclone cabs.	1	
1550-0284	Rear crew cab door window(s) with manual regulator(s). For use with new Typhoon and 100" wide Cyclone cabs.	1	
1550-0288	Cab doors to extend down to cover lower step well. For use with new Typhoon cab and 100" wide Cyclone only.	1	
1550-0378	All cab doors shall have exterior pull style handles with chrome metal base and integral key lock.	1	
CAB STEP OPTIONS			
1640-0045-158	Step below cab door. Open back style with angled corners. Located driver's front door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0045-159	Step below cab door. Open back style with angled corners. Located officer's front door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0045-160	Step below cab door. Open back style with angled corners. Located driver side rear door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0045-161	Step below cab door. Open back style with angled corners. Located officer side rear door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0047	Lower steps to extend 3.5" past cab. For use with legacy Typhoon / Cyclone with barrier style doors and new Typhoon / Cyclone with barrier style or extended doors.	1	
MIRRORS			
1670-0001-274	Ramco 6001FFR mirrors. Remote controlled with top CAS750 manual convex. Location: mounted on front corners of cab.	1	

Salescode	Extended Description	Qty	
MIRRORS			
1670-0031	2" extension for Ramco mirrors.	1	
1670-0088	Driver and officer Ramco cab mirrors to be heated. Includes all surfaces (flat and convex, as applicable).	1	
MISC EXTERIOR CAB OPTIONS			
1550-0035	No window on the driver side of the cab	1	
1550-0036	No window on the officer side of the cab.	1	
1675-0030	Mud flaps, front, black with E-ONE logo.	1	
1675-0046	Rear cab wall to be smooth 3/16" aluminum plate. Cab wall to be finish painted to match the cab paint scheme.	1	
1675-0201	Large radius cab wheel well. Includes bolt-on adjustable wheel well trim.	1	
1675-0202	Mounting plate for battery charger receptacle, indicator, air inlet, etc (if applicable). Plate to be removable brushed stainless steel.	1	
1675-0229	Pair of one piece knurled stainless steel 18" handrails located just behind driver and officer front door one each side.	1	
1675-0230	Pair of one piece knurled stainless steel 36" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side.	1	
1675-0254	Rear cab and vista glass (if so equipped) to have dark tint IPOS. Glass to be smoked glass with 20% light transmittance (+/- 10%). Includes all glass rearward of front cab doors.	1	
1685-0705	Coat hook(s), stainless steel Brey-Krause VS-1030-BS, shall be provided on the cab. Location: mounted with the upper mount of the cab handrail. (EA) For one piece hand rails only.	4	
HVAC			
1515-0053	Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and Cyclone with severe duty dash)	1	
1515-0077	Additional fan control for rear facing air conditioner. Locate adjacent to rear AC vents/filter on driver side.	1	
1515-0099	Air conditioning with radiator mounted condenser for use with Cummins L9 and X12 engine. Includes reduced profile evaporator w/powder coated cover and electronic controls.	1	
1685-0056	Heater rear cab w/o cover (PR) and front cab heater with heat to the feet for the driver and officer.	1	
SEATS			
1510-0116-132	Fold-down seat located officer's side outboard.	1	
1510-0279-146	ReadyReach seat belt extender. Location: driver's seat.	1	

Salescode	Extended Description	Qty	
SEATS			
1510-0279-147	ReadyReach seat belt extender. Location: officer's seat.	1	
1510-0279-151	ReadyReach seat belt extender. Location: inboard driver's side rear wall.	1	
1510-0279-152	ReadyReach seat belt extender. Location: inboard officer's side rear wall.	1	
1510-0301	Seats, Valor brand.	1	
1510-0302	Seat cover material Valor Tech XD (previously identified as Cordura).	1	
1510-0303	Seat color black with red stitching.	1	
1510-0329	Officer seat USSC Valor fixed SCBA.	1	
1510-0332	Two man bench centered on rear wall with Valor SCBA backs. Includes angled corners.	1	
1510-0466	Driver seat USSC Valor electric attendant non-ABTS.	1	
1685-0032	Seating capacity tag of five occupants.	1	
MEDICAL CABINETS			
1535-0129	Reverse hinge driver and officer side ALS compartment door. Includes vertically mounted drip rail along forward area of compartment opening (as applicable)(in addition to the horizontal drip rail above the door opening; Cyclone and Typhoon cabs only). Doors to open approx. 110 degrees.	1	
1535-0177	Compartment rear side of cab "under riser" type. Approx 9W x 30H opening. Includes double pan hinged door. Long cab with medium door location only. Note: striker pin extends into opening - may block extinguisher placement. Location: driver and officer side.	1	
1535-0202	Cab medical/storage cabinet(s) finish to be multi-tone gray. Includes interior/exterior of cabinet and shelves/trays if equipped.	1	
1535-0310	The compartments to the rear sides of the cab are to be designed with a pass through that extends fully from the driver side compartment to the officer side compartment. To be used when equipped with a bench seat riser, common riser used with individual seat(s) or center rear wall cabinet.	1	
1535-0583-160	The cab compartment located behind driver side rear door to have floor 7.75 inch outside dimension square recessed 4" for storage of one (1) standard size SCBA bottle, 20lbs ABC Extinguisher or 2.5 gal Water Extinguisher. Storage shall be rectangular with cutout for extinguisher hose towards the inside wall. Requires minimum 30" tall compartment and 67.5" CA or longer cab.	1	
1535-0583-161	The cab compartment located behind officer side rear door to have floor 7.75 inch outside dimension square recessed 4" for storage of one (1) standard size SCBA bottle, 20lbs ABC Extinguisher or 2.5 gal Water Extinguisher. Storage shall be rectangular with cutout for extinguisher hose towards the inside wall.	1	

Salescode	Extended Description	Qty	
MEDICAL CABINETS			
	Requires minimum 30" tall compartment and 67.5" CA or longer cab.		
1535-0705	(2) broom handle tubes vertically stacked on forward wall of cab transverse compartment.	1	
1535-0926	Special cargo net cover with twist lock fasteners on cab medical cabinets IPOS. (EA)	1	
1535-1185	Officer side cab wheel well medical cabinet divided into (2) areas. Includes full height external locking pan door painted job color and 20" from top down upper interior access that includes cargo net with twist locks. Cabinet to be full exterior access and interior access only for upper. Cabinet is approximately FH x 22W x 28D on Typhoon and Cyclone and FH x 25W x 28D on 100" wide Cyclone and Quest One adjustable shelf will divide upper and lower.	1	
1535-1186	Driver side cab wheel well medical cabinet divided into (2) areas. Includes full height external locking pan door painted job color and 20" from top down upper interior access that includes cargo net with twist locks. Cabinet to be full exterior access and interior access only for upper. Cabinet is approximately FH x 22W x 28D on Typhoon and Cyclone and FH x 25W x 28D on 100" wide Cyclone and Quest One adjustable shelf will divide upper and lower.	1	
MAP BOXES			
1540-0029	Offset suspended map box to rear of vertical 3x3 extrusions and as low as possible. Front of map box flush with front of 3x3 uprights.	1	
1540-0103	Map box suspended with drop down doors. 34"W x 6"H x 12.5"D. Includes full width upper shelf and lower vertical divider.	1	
MISC INTERIOR CAB OPTIONS			
1685-0005	Lexan sun visors, driver and officer's side overhead.	1	
1685-0068	Rear engine cover diamond plate trim.	1	
1685-0187	Severe duty engine cover, molded polyurethane.	1	
1685-0275-966	Cup holder (PR). Polyurethane construction for use in Typhoon and CII with severe duty engine cover only. Location: to be mounted at final inspection.	1	
1685-0285	Cup holder / tray for engine cover painted to match cab interior. Approx 14" wide x 10" long with tapered front corners and cup holders at each rear corner. For use in Typhoon and CII with severe duty engine cover.	1	
1685-0438	Cover(s) below rear bench seat or in the transverse/ pass-thru area (if equipped) to protect back of heaters.	1	
1685-0446	Severe duty overhead console. Includes driver, center and officer overhead ahead of air conditioning plenum. Center overhead includes siren mounting locations. Overhead to match cab interior.	1	

Salescode	Extended Description	Qty	
MISC INTERIOR CAB OPTIONS			
1685-0464	Control lanyard Y type with "Heavy-Duty" (keyring) attachment for air horns.	1	
1685-0531	Reduced profile rear engine cover for increased legroom.	1	
1685-0670	Severe duty dash package with raised profile center section. Cast alum construction. Includes smooth plate alum lower kick panels; all painted to match cab interior.	1	
1685-0692	Cab insulation package. Includes insulation for ceiling, front wall, rear wall, side walls, below seat risers and in doors.	1	
1685-0775	Aluminum tray mounted to rear of engine cover. Approximately 49"W x 22"D with 2" lip on all sides. To be used between wheel well cabinets (as applicable). Located approx. 21" from floor to bottom of tray. Finish to match interior. Equipment stored on shelf must use brackets to meet NFPA.	1	
1685-0809-S66	Active Air Purification System for cab crew area. Location: rear engine cover centered between 3x3	1	
1685-0891	Cab interior padding to be gray.	1	
CAB ELECTRICAL OPTIONS			
1750-0015-175	Windshield fans 8" pair. Location: centered below overhead console.	1	
1750-0015-G71	Windshield fans 8" pair. Location: rear facing mounted up high on vertical 3 x 3 posts.	1	
1750-0024-179-02	Auto-Eject receptacle inlet 20 amp located outside driver's door next to handrail with a Red cover.	1	
1750-0046-195	Cab Headlights. Position: lower.	1	
1750-0072-545	12 VDC electrical outlet wired battery hot. Location: In cab driver side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0072-546	12 VDC electrical outlet wired battery hot. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0072-592	12 VDC electrical outlet wired battery hot. Location: driver side dash.	1	
1750-0072-593	12 VDC electrical outlet wired battery hot. Location: officer side dash.	1	
1750-0075	English dominant main cab gauge cluster.	1	
1750-0080	Conduit flexible 1.5" for radio installation center of dash to compartment under officer's seat. To include pull string/wire.	1	
1750-0166	ATC override switch.	1	
1750-0198-A31	Battery charger to be located behind driver's seat.	1	
1750-0265	Speedometer for officer side multiplex display.	1	
1750-0449	Momentary DPF regeneration override switch.	1	

Salescode	Extended Description	Qty	
CAB ELECTRICAL OPTIONS			
1750-0580	Light EON LED (EA) mounted in riser height compartment.	4	
1750-0663	JW Speaker LED cab headlights. Model 8800 Evolution 2, heated.	1	
1750-0768	TecNiq D07 LED cab door step area lighting. Includes (2) lights at each door area. Lights to be switched with door ajar.	1	
1750-0796	Turn signal TecNiq LED strip (PR) with clear lens and polished alum housing located between quad headlight bezels (New Typhoon and Cyclone only).	1	
1750-0902-545	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: In cab driver side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0902-546	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0902-592	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: driver side dash.	1	
1750-0902-593	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: officer side dash.	1	
1750-0912	Radio speakers pair. Locate speakers in cab as specified by sales, with wiring terminating in location as specified by sales.	1	
1750-1004	Battery charger Kussmaul Chief Series. 120/240 volt inlet, 40 amp output. Includes remote and built-in touch screen displays.	1	
5400-0057	Dome lts red/white 4" LED (4). Lights to be located two front and two rear. White light wired through door and light assembly mounted rocker switch. Red light through light assembly mounted rocker switch.	1	
AERIAL BODY			
3060-0019	Body aerial CR100/137/95-Platform without pump (187" C/A) (245" WB medium cab). Includes driver and officer side full height compartments, extended height front side compartments, individual rear side compartments, dual 18" wide rear side staircases with pocket style drop down step and 34" wide ladder tunnel. 61" high body for 11'-10 +/-1" OAH.	1	
AERIAL BODY MODIFIERS			
3065-0009	Body modification - Raise the rear perimeter aft of rear jack legs 4" for improved angle of departure. Reduces height of rear side compartments and may eliminate the small lower storage area with combined rear side compartment option.	1	

Salescode	Extended Description	Qty	
AERIAL BODY MODIFIERS			
3065-0031	Body modification - Remove upper inner body angled side walls to rear of extended high compartments.	1	
3065-0047	Body modification - Reduce width of the L1/R1 transverse compartment 5" for long cab (67.5" C/A) IPO medium cab (58" C/A) with a 250 WB or to shorten WB from 245" to 240" with a medium cab. (For use with NPNT CR100/137/95-P only).	1	
BODY COMPT REAR			
3110-0360	Rear of body to have un-painted smooth plate overlay style body panels to facilitate rear body striping.	1	
AERIAL BODY OPTIONS			
3310-0032	Recessed tubes for (6) pike poles. Not available on HP75 SideStacker.	1	
3310-0096	Doors for rear master and jack control controls. Doors will match rear body finish.	1	
3310-0107	Transverse compartment floor to be extended out to door opening in L1/R1.	1	
3310-0162	Jack leg opening covers diamond plate (4) sets. Includes diamond plate outrigger covers and fixed diamond plate filler panels. HM100/HR100/110 requires surface mount warning lights.	1	
3310-0309	Auxiliary jack pad 26X26 (4) with 20 degree formed handle. Includes (4) mounting brackets.	1	
3310-0568	Fuel fill hinged door and fixed panel below door each side to rear of rear axle to be smooth plate painted job color.	1	
3310-0766	Storage tubes in transverse compartment above transverse shelf on rearward wall for (6) pike poles. Tubes to be sized for 6' pike poles. Tubes to have locking slots to hold poles in compt. Three poles shall be accessible from L1 and three poles accessible from R1.	1	
3310-0987	Rear ladder tunnel door with D-ring slam latch. Lift-up door to open 20 degrees past horizontal (degrees may be reduced due to other options). Door will match rear body finish.	1	
3310-1001	Jack leg opening covers diamond plate painted LINE-X (4) sets. Includes painted plate outrigger covers and fixed painted plate filler panels.	1	
3310-1143	Open storage area beneath the aerial device on top of body to have dual compartment lids for storage (no center channel) with gas shocks and recessed handles and appropriate NFPA LED lights to illuminate the interior when lids are opened.	1	
DOORS			
3300-0021-006	Door roll up short (up to 45") with painted finish ROM. Location(s): L4.	1	

Salescode	Extended Description	Qty	
DOORS			
3300-0021-008	Door roll up short (up to 45") with painted finish ROM. Location(s): L6.	1	
3300-0021-018	Door roll up short (up to 45") with painted finish ROM. Location(s): R4.	1	
3300-0021-020	Door roll up short (up to 45") with painted finish ROM. Location(s): R6.	1	
3300-0022-003	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L1.	1	
3300-0022-004	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L2.	1	
3300-0022-005	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L3.	1	
3300-0022-009	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L7.	1	
3300-0022-015	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R1.	1	
3300-0022-016	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R2.	1	
3300-0022-017	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R3.	1	
3300-0022-021	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R7.	1	
3300-0066-003	Drip pan for a ROM roll-up door (EA). Location(s): L1.	1	
3300-0066-004	Drip pan for a ROM roll-up door (EA). Location(s): L2.	1	
3300-0066-005	Drip pan for a ROM roll-up door (EA). Location(s): L3.	1	
3300-0066-006	Drip pan for a ROM roll-up door (EA). Location(s): L4.	1	
3300-0066-008	Drip pan for a ROM roll-up door (EA). Location(s): L6.	1	
3300-0066-009	Drip pan for a ROM roll-up door (EA). Location(s): L7.	1	
3300-0066-015	Drip pan for a ROM roll-up door (EA). Location(s): R1.	1	
3300-0066-016	Drip pan for a ROM roll-up door (EA). Location(s): R2.	1	
3300-0066-017	Drip pan for a ROM roll-up door (EA). Location(s): R3.	1	
3300-0066-018	Drip pan for a ROM roll-up door (EA). Location(s): R4.	1	
3300-0066-020	Drip pan for a ROM roll-up door (EA). Location(s): R6.	1	
3300-0066-021	Drip pan for a ROM roll-up door (EA). Location(s): R7.	1	
3300-0289-007	Door double vertical hinged w/rotary latches - painted . Location(s): L5 Includes latch handle extension installed on secondary door's interior latch with "PULL" tags using .125 plate.	1	
3300-0289-019	Door double vertical hinged w/rotary latches - painted . Location(s): R5 Includes latch handle extension installed on secondary door's interior latch with "PULL" tags using .125 plate.	1	
3300-0368	Pull-down bungee type straps for full height and high side roll-up door(s) on body / pump module. For use with ROM and AMDOR doors only.	1	
SHELVES			

Salescode	Extended Description	Qty	
SHELVES			
3370-0245	Permanent fixed shelf. Aluminum or stainless steel body applications. Location:	1	L3 offset 42'` above compartment floor to bottom of shelf. 3370-0025-1YQ
3370-0246	Adjustable shelf for non-transverse compartments. Location:	15	L3 lower qty 2; R3 lower qty 3; L4 lower qty 1; L6 upper qty 1; L7 upper qty 1; R4 lower qty 2; R7 upper qty 1; L2 middle qty 2; R2 middle qty 2
COMPARTMENT DIVIDERS			
3390-0557	Partition, bolt-in vertical partition wall. Location:	2	R2 18'` off forward wall; L3 16'` off forward wall.
TRAYS / TOOLBOARDS			
3380-0508	Adjustable heavy duty tool board with 500 lbs. capacity. Includes return style reinforcing bends on vertical front and rear edges of tool board, upper and lower adjustable track and gas shock actuated. Tool board sized to compartment height and depth as applicable. Location:	3	L3 qty 1; R2 qty 2 located forward of partition
3380-0701	Floor mounted steel bi-directional SlideMaster model SM2-D powder coated silver with aluminum tray. For use in tranverse compartments w/ extended floors. Location(s):	1	
LADDER STORAGE / RACKS			
3365-0013-5TV	Center mounted ladder tunnel. Ladder rack to hold: PEL-35, PEL-28, DRL-20, DRL-18, FL-10 and fabricated aluminum sleeve for customer supplied CMC 726100 stokes basket.	1	
HANDRAILS / STEPS			
3330-0340	Handrail upgrade for pump enclosure (as applicable) and rear body handrails (excludes chrome grab handles if equipped) replaced with Brey-Krause Mfg. Co. one piece knurled SS IPOS.	1	
MISC BODY OPTIONS			
3340-0090-000-13	Turtle Tile Brand Black Floor Matting covering all applicable Compartment Floors, Shelves, and Rollout Trays. Does not include roof top compartments (Added separately)	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0282-X73	Cab tilt switch and manual jack to be located: right side forward jack leg compartment low behind door in access panel (tilt sw behind door).	1	
3340-0478	Insulation shall be installed behind and / or below the body to protect the compartment(s) from excessive exhaust system heat.	1	
3340-0689	Insulation to protect compartment from exhaust system heat. Locate behind R1	1	

Salescode	Extended Description	Qty	
MISC BODY OPTIONS			
	wall.		
3340-0895	Seamless & Flush Smooth plate tandem axle wheel well painted job color. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes. Wheel well plates to be flush mounted.	1	
3340-1632	Diamond plate corner guard for the rear compartment face forward of staircase(s). Guard to wrap around the corner. SideStacker or NPNT w/ side staircase aerial bodies only.	1	
3340-1648	Anodized aluminum trim on bottom edge of all body compartment openings including pump enclosure if applicable with painted edges.	1	
SCBA BOTTLE STORAGE			
3320-0009	SCBA Bottle Storage. (8) Cast Product SCBA bottle storage with gasketed doors. (4) each side in rear wheel well area.	1	
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
ELECTRICAL SYSTEMS			
5010-0039	V-MUX Electrical system for aerials.	1	
5010-0049	Vehicle data recorder - 2009 / 2016 NFPA compliant. Includes occupant detection shown in multiplex display. E-ONE chassis only.	1	
5010-0055-168	Vista IV display for V-MUX electrical system. Location: officer's side engine cover.	1	
5010-0055-649	Vista IV display for V-MUX electrical system. Location: driver's side engine cover.	1	
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
LIGHT BARS			
5300-0391-034	Light bar Federal Signal Split Vision VSLR8. Two (2) 26.5" 4-pod light bars. Driver w/ (2) red and (2) multi-color pods with clear lenses; officer w/ (3) red and (1) multi-color pods with clear lenses. Location: front cab corners.	1	
5300-0392-0VE	Front Federal Signal VSLR multi-color pod programming: to be clear in response and change to red with park brake. (If applicable, includes side facing when colors are the same.)	1	
5300-0462-5YI	Light bar Federal Signal Split Vision VSLR6S-CHI3. Two (2) 21" 3-pod light bars w/ (1) red pod, (1) multi-color pod and (1) blue pod on each bar with clear lenses. Location: on cab/bumper as specified.	1	
5300-0738	Diamond plate cover over body mounted light bar. (EA)	2	
5300-0742-0VE	Side Federal Signal VSLR multi-color pod programming: to be clear in response and change to red with park brake.	1	

Salescode	Extended Description	Qty	
LIGHT BARS			
5300-0858-5YK	Light bar Federal Signal Split Vision VSLR6. Two (2) 21" 3-pod light bars w/ (3) red pods on each bar with clear lenses. Location: On body as specified.	1	
WARNING LIGHTS			
5550-0069	Flash rate for Federal QuadraFlare and/or FireRay LED lower level warning lights to be set at DoubleFlash 150 - Simultaneous.	1	
5600-0085-F21	Tomar strobe preemption emitter with chrome housing. Includes pedestal mount and switch accessible to driver. Wire through parking brake. Location: front of cab behind grille.	1	
5600-0377-479	Federal Signal Vision LED rotating beacons with clear lenses model VSLR1-R2A02 with rear facing IPX6 amber LED warning light. Location: rear upper body on aerial style brackets.	1	
5600-0680-3RE-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone front facing.	1	
5600-0680-3RF-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone forward side facing.	1	
5600-0680-3RG-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone midship side facing.	1	
5600-0680-3RI-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone rear facing.	1	
5600-0680-457-9Y	Warning light Federal Signal FireRay model FR6 LED (PR) AMBER with AMBER lenses. Surface mounted with bezel. Location: (1) each side of body rear facing up high.	1	
5600-0680-463-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side in front quad inboard of NFPA warning light.	1	
5600-0680-464-5D	Warning light Federal Signal FireRay model FR6 LED (PR) BLUE with BLUE lenses. Surface mounted with bezel. Location: (1) each side of cab down low just ahead of rear doors.	1	
5600-0680-5YK-5D	Warning light Federal Signal FireRay model FR6 LED (PR) BLUE with BLUE lenses. Surface mounted with bezel. Location: On body as specified.	1	
5600-0773-3RH-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone rear side facing. Note: MicroPulse Series lights are only available with clear	1	

Salescode	Extended Description	Qty	
WARNING LIGHTS			
	lenses.		
5600-0773-469-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side centered below forward compartments in rubrail if equipped. Note: MicroPulse Series lights are only available with clear lenses.	1	
5600-0773-470-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side rear facing (angled portions of Boston style tailboard as applicable) corners of tailboard in rubrail if equipped. Note: MicroPulse Series lights are only available with clear lenses.	1	
5600-0773-471-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side just behind rear wheels in rubrail if equipped. Note: MicroPulse Series lights are only available with clear lenses.	1	
5600-0850-170	Hazard (door ajar) light TecNiq S38 LED red. Location: center overhead.	1	
DIRECTIONAL LIGHT BARS			
5310-0012	Diamond plate shield over rear directional light.	1	
5310-0020-846	Directional light bar control is to be located center overhead console offset to driver side.	1	
5310-0025	Directional light circuit wiring through upper level warning.	1	
5310-0123	Light bar Federal Signal Signal Master split amber LED - (2) 15.7" long, with clear lenses.	1	
SIRENS			
5500-0009	Federal PA300 electronic siren recessed mounted.	1	
5500-0011-209	Federal Q2B siren - Pedestal mounted on bumper. Location: driver side front bumper. Requires activation switch.	1	
5500-0024-170	The primary electronic siren control is to be located center overhead.	1	
SPEAKERS			
5510-0029-211	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: officer side front bumper.	1	
DOT LIGHTING			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	
5150-0068	Marker lights Britax LED amber/red rubber housed mounted on the rear body corners angled down.	1	
5150-0205	Federal Signal FireRay LED vertical mount tail lights. Includes LED stop/tail,	1	

Salescode	Extended Description	Qty	
DOT LIGHTING			
	arrow turn and back-up lights with vertical 4 housing and weatherproof connectors.		
5150-0233	Marker light package cab / body LED. Body lights to be .75" Dia TecNiq for custom cab with rear mount aerial platform bodies only. Includes (3) TecNiq marker lights on front of platform.	1	
5150-0242-1WS	Light Whelen model PSR01FCR LED (EA) red 3rd brake light. Location: rear of body rear facing up high below traffic advisor.	1	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0068	Ground light package Federal Signal LED - large.	1	
5380-0070	Step light package body Federal Signal LED - large.	1	
5380-0312	Compartment light package Hansen white LED for large bodies. Includes two lights per compartment (four if transverse).	1	
5380-0323	The auxiliary steps below the cab doors and/or below pump module/body (if applicable) to have EON LED lights to illuminate the stepping surface and ground below (IPO lights indicated in the main ground light package).	1	
5380-0325	EON LED ladder tunnel light (EA).	2	
LIGHTS - DECK AND SCENE			
5390-0007	Deck/scene light circuit wiring through chassis reverse. Requires rear deck or scene light.	1	
5390-0169-457	Deck light FireTech, model FT-WL3500-FT LED (PR) with black housing. Switched with work light switch in cab. Location: (1) each side of body rear facing up high.	1	
LIGHTS - NON-WARNING			
5400-0224	Engine compartment light Optronics LED Series ILL22 (EA).	1	
CONTROLS / SWITCHES			
1750-0034-A24	Switch, additional 12 volt/15 amp. Location and function: driver rear of body for rear work lights.	1	
5100-0000-198	Foot switch to control air horns located driver's side.	1	
5100-0000-968	Foot switch to control air horns located officer's side for left foot.	1	
5100-0006-198	Foot switch to control Q2B located driver's side.	1	
5100-0006-199	Foot switch to control Q2B located officer's side.	1	
5100-0036-0A3	Additional programming instructions: side facing platform warning lights wired through aerial master and/or upper level warning.	1	

Salescode	Extended Description	Qty	
CONTROLS / SWITCHES			
5100-0036-1P9	Additional programming instructions: outrigger/jack leg warning lights to activate with lower warning IATS.	1	
5100-0036-1YI	Additional programming instructions: all side facing scene/flood lights wired together ("Left Scene" and "Right Scene")..	1	
5100-0036-2IY	Additional programming instructions: the scene light portion of all side facing M6V lights to activate when park brake is set.	1	
5100-0036-Z04	Additional programming instructions: provide node programming for dealer supplied Vogel Lubrication System in pump module (or near aerial crade on aerals with no pump module).	1	
5100-0046	Cut-off switch for Q2B main power. Switch to be accessible from driver's seat.	1	
5100-0165	Audible door ajar alarm wired through door ajar light. For use with multiplex display(s) only.	1	
CAMERAS / INTERCOM			
5350-0070	Voyager back-up camera. Video displays automatically when transmission is in reverse. Camera only - does not include monitor.	1	
5350-0156	FRC ACT 2-way aerial intercom.	1	
5350-0193	Voyager rear facing camera positioned on officer's side front cab corner (approx 31" bottom of camera to bottom of cab) interlocked with right turn signal. Camera only - does not include monitor.	1	
MISC ELECTRICAL			
5110-0004	Alternating flasher for headlights. Not available on Ford chassis.	1	
5110-0005	Pre-wire for trailer hitch. Includes stop, left turn, right turn, marker and ground wires. Does not include connector.	1	
5110-0017	Back-up alarm 97 dB.	1	
5110-0041	7 pin trailer wiring connector. Requires trailer wiring pre-wire option.	1	
5110-0219-170	Blue Sea 12V power distribution module model 5032. Location: center overhead.	1	
5110-0219-762	Blue Sea 12V power distribution module model 5032. Location: behind officer's seat.	1	
LIGHTS - AREA			
5450-0341-3UL	FireTech 72" 12V scene light with black housing. Includes switch accessible to driver. Side facing lights switched seperately. Location: above L4/R4 compartments.	2	
5450-0395-493	FireTech 35" 12V mini brow light (EA) with black housing and flood optics. Includes switch in cab (driver and officer side facing lights switched separately). Location: driver and officer side over rear cab door	2	

Salescode	Extended Description	Qty	
LIGHTS - AREA			
5450-0759-3UL	Diamond plate light shield for Firetech scene light (EA). Sized as applicable for optioned light fixture. Location: above L4/R4 compartments.	2	
RECEPTACLES			
5470-0004-G93	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: driver side interior of map box.	1	
5470-0074-25K	8 outlet household 15A/110V power strip wired to shoreline. Location: R3 back wall up high centered.	1	
AERIAL MODEL			
6100-0112	Turntable extension on right side of aerial. Includes additional handrail. For use on aerials with fabricated turntable only.	1	
6100-0144	Aerial jack leg beams and feet to be zinc flame spray coated before paint (4 sets).	1	
6100-0157	Platform 95 Rear-Mount. Includes fabricated SideStacker style turntable deck, platform with angled corners, left side turntable console, turntable mansaver bars and jack leg flood lights.	1	
AERIAL HYDRAULIC SYSTEM OPTIONS			
6150-0001	Aerial hydraulic filter isolation kit.	1	
6150-0003-218	Gauge aerial hydraulic oil level. Electronic display to be located next to aerial master panel.	1	
6150-0008	Integral outrigger pad extensions (4). 15" x 20" x .5" steel plate welded to std jack foot plates. N/A on HP75/78, 4-jack HP95 MM or HP100 Platform with short jack.	1	
6150-0014	Aerial hydraulic pump to be upgraded to a variable displacement style pump	1	
AERIAL CONTROLS			
6850-0037	Advanced Aerial Control System - Platform. Includes body protection, cradle alignment It and 3.2" displays with flowmeter at each control console.	1	
6850-0043	Diamond plate turntable console mounted to tube style pedestal mount. Includes side hinged diamond plate cover with hinge on outboard side. Includes modified left side turntable handrail. (95-platform and HP/HPS100 Platform only)	1	
6850-0083	Moon spring for aerial console cover. To hold cover open at 90 degrees to the side.	1	
MONITORS			
6300-0017	Monitor painted silver from OEM.	1	

Salescode	Extended Description	Qty	
MONITORS			
6300-0108	Monitor Akron StreamMaster II electric with 5177 nozzle 1250GPM for platform. Includes tip controls, base controls and a butterfly valve. Monitor to have multiple flow ratings based on aerial model and monitor position.	1	
WATERWAY OPTIONS			
6350-0005	Rear 4" NST waterway inlet for rear mounted aerals. Includes chrome cap.	1	
6350-0012-219	Akron 2.5" valve for platform. Valve to be located at the left rear of platform.	1	
6350-0014	2.5" chrome elbow with 2.5" x 1.5" reducer and 1.5" cap for platform / ladder discharge valve.	1	
6350-0123	Waterway inlet shut-off valve - 4" electric controlled Akron with 9333 controller. Mounted below ladder tunnel between torque box and rear of body. Includes relief valve and bleeder outboard of 4" valve. Note: Std aerial relief valve to be located ahead of 4" valve.	1	
6350-0162	Innovative Controls TC Series 2.5" (63MM) waterway inlet pressure gauge (0-400) with chrome bezel.	1	
AERIAL WARNING LIGHTS			
6550-0096	Outrigger warning lights (4) LED. Whelen M6V2R Super LED.	1	
6550-0103-000-4U	Federal FireRay model FR6 LED warning lights (4). Color: RED with RED lenses. Located down low across front of platform wired to upper level lights.	1	
6550-0104-224-5D	Federal FireRay model FR6 LED warning lights on platform (PR). Color: BLUE with BLUE lenses. The lights shall be switched with aerial master and located one each side on the side of the ground pad brackets.	1	
AERIAL LIGHTING			
6560-0085-000-06	Ladder climbing lights Luma Bar Pathfinder LED strip for 95-Platform and HP100 Platform (both sides). Color: Red.	1	
6560-0184	FireTech model FT-WL3500-FT-B LED flood/spot light with black housing. Includes hardwired switch on turntable console. Location: left and right side of base section.	1	
6560-0203-235	FireTech model FT-WL-X-9-FT-B-SH2 LED flood/spot light with black housing. Includes switch on lighthouse and turntable console. Location: left side front of platform.	1	
6560-0203-236	FireTech model FT-WL-X-9-FT-B-SH2 LED flood/spot light with black housing. Includes switch on lighthouse and turntable console. Location: right side front of platform.	1	
6560-0307-23M	FireTech 15" 12V mini double stacked black trunnion mount light. Includes switch on platform or turntable console. Location: left side of platform offset rearward.	1	

Salescode	Extended Description	Qty	
AERIAL LIGHTING			
6560-0307-598	FireTech 15" 12V mini double stacked black trunnion mount light. Includes switch on platform or turntable console. Location:right side of platform offset rearward.	1	
AERIAL EQUIPMENT			
6500-0014-139	Pike pole tube for 12' pole on ladder. Location: right side fly section.	1	
6500-0019-266	Axe bracket mounted on aerial. Includes pick cover. For use with a 6 lb axe only. Location: right side inside of platform.	1	
6500-0064	Diamond plate storage box with hinged lid for chain or power cut saw. Box to be approx 32L x 16W x 20H located on right side of aerial turntable. Includes notch(es) as required for turntable handrail clearance. CR100/92Pltfrm/110/100 with full T/T only.	1	
6500-0150	Stokes basket receiver for 95-Platform & HP95 Mid-Mount platforms. Stokes and storage brackets on side of base not included.	1	
AERIAL LADDER BRACKETS			
6600-0000	Folding ladder bracket. Locate inside the right side fly section for a FL-10.	1	
6600-0035-1S1	Lift out slim profile style roof ladder bracket. Locate outside base section for a DRL-16 on left side of base section. Available on 95RM, 110, CR100, HR100 and HM100.	1	
SIGN PLATES			
6750-0002-000-18	Aerial sign plates 22 x 144 (PR). Does not include lettering. Color: FLNA 4006 E-ONE WHITE.	1	
AERIAL TESTING			
6900-0000	Aerial flow test - 3rd party.	1	
6900-0007	Aerial 2016 NFPA Certification.	1	
GROUND LADDERS			
7800-0021	Alco-Lite PEL-28' extension ladder.	1	
7800-0024	Alco-Lite PEL-35' extension ladder.	1	
7800-0032	Alco-Lite FL-10, 10' folding ladder w/safety shoes.	2	
7800-0102	Alco-Lite DRL-16' roof ladder.	1	
7800-0112	Alco-Lite DRL-20' roof ladder.	1	
7800-0118	Alco-Lite DRL-18' roof ladder.	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors	1	

Salescode	Extended Description	Qty	
MISC LOOSE EQUIPMENT			
	with carrying case. This kit is for the end user and is to remain with the truck.		
7900-0388	CMC model 726100 stokes basket. Ship loose.	1	
EXTERIOR PAINT			
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0176-000-26	Paint E-ONE chassis cab - Sikkens paint (non-metallic color). Color: FLNA 3047 E-ONE RED.	1	
8100-0183-000-26	Paint Body - Large - For Aerials, T/A Tankers/Wetsides, Rear Mounts and Rescues. Sikkens paint (non-metallic color). Color: FLNA 3047 E-ONE RED.	1	
8100-0222	Paint roll up door header plate(s) job color for all painted roll-up doors.	1	
8100-0354	Paint lift cylinders, extension cylinders and upper turntable steelwork primary job color (does not apply to TT deck).	1	
8100-0396	Undercoating E-ONE. To be applied after customer final inspection.	1	
8100-0501	Paint each body compartment lower door opening edge with Scorpion polyurethane coating. Color: Job Color.	1	
8100-0589	Paint each cab door opening at the rear vertical edges that is rolled back and over 1" on both sides with Scorpion polyurethane coating. Including behind each exterior handrail the same size as a scuff plate between the cab and handrail. Color: Job Color.	1	
8100-0614	Paint each exterior cab compartment lower door opening edge with Scorpion polyurethane coating. Color: Job Color.	1	
8100-0799	Paint wheel well SCBA compartment door opening edge with Scorpion polyurethane coating.(EACH) Color: Job Color.	1	
INTERIOR PAINT			
8150-0011	The interior of the cab to be painted multi-tone gray finish.	1	
8150-0024	The lower area of the painted cab interior door panels to be masked off and left un-painted for reflective material.	1	
PROTECTIVE COATINGS			
1160-0149	LINE-X bumper package: Includes all visible diamond plate/smooth aluminum surfaces including gravel shield, exterior surface of trays and lids(flat or raised). If equipped, exterior of the fabricated booster reel housing, fabricated box for booster reel rollers and winch access door shall be included in this package.	1	
1640-0036	LINE-X package for custom cab steps: Includes cab step wells (everything below the cab floor) and all welded and bolt on steps including stirrup and swing out steps as applicable. Steps hanging below the cab shall have LINE-X coating inside	1	

Salescode	Extended Description	Qty	
PROTECTIVE COATINGS			
	and outside. DEF tank door or any other access doors are also included in this package if located in the step well area below the cab floor.		
3110-0359	LINE-X package for welded (exterior surface only), bolt on (exterior surface only) or flip down style (exterior and interior surfaces) tailboards. Includes rear bumper overlay or E-ONE fabricated boxes mounted on the tailboard as applicable.	1	
3340-1019	LINE-X package for Aerial body miscellaneous parts: Includes wheel well plates, outrigger covers, diamond plate filler panels, diamond plate fuel fill doors and aerial control doors as applicable.	1	
3340-1150	Rear Aerial staircase steps and platework, beavertail platework and tailboard as applicable shall be coated with black Line-X.	1	
6100-0063	LINE-X package for Aerial Turntable: Includes turntable console, turntable deck platework and access steps and any other storage boxes or brackets fabricated out of diamond plate installed on the turntable.	1	
8100-0495	LINE-X: One or more components installed on this unit shall have LINE-X coating. Color shall be Black unless otherwise specified.	1	
STRIPING			
8300-0001	NFPA required reflective striping to be dealer/customer applied.	1	
8300-0101	Black rubrail scotchlite insert.	1	
8300-0274-000-J7	Chevron "A" style 6" Reflexite V98 striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0281-000-J7	Chevron "A" style 6" Reflexite V98 striping on outriggers. Striping to alternate in an "A" pattern when viewed from the front or rear of the truck. Colors to be: Red/Fluorescent Yellow Green.	1	
8300-0381	Yellow perimeter marking to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901 consisting of individual Reflexite diamonds approximately 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.	1	
GRAPHICS			
8400-0033	Logo E-ONE (PR) on aerial lift cylinder. Logo to be sign gold material approx 14" long located midway along outward surface of cylinder.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0101	Meritor 5 year / unlimited miles parts and labor warranty for front non-drive axle. Exceptions: MFS rated at 22,800 includes a 2 year / 200K miles parts and labor warranty and a front drive axle includes a 2 year / unlimited miles parts and	1	

Salescode	Extended Description	Qty	
WARRANTY / STANDARD & EXTENDED			
	labor warranty.		
9100-0102	Meritor 5 year unlimited miles, parts and labor rear drive single or rear drive tandem axle warranty.	1	
9100-0117	General One (1) year or 24,000 Miles Limited Warranty (RFW0001)	1	
9100-0126	Custom chassis One (1) Year or 18,000 Miles Limited Warranty (RFW0101).	1	
9100-0131	Regulated Emissions Systems Five (5) Years or 100,000 Miles Limited Warranty (RFW0140). N/A for California. For units going to California use 9100-0162 with L9 and 9100-0163 with X12/15.	1	
9100-0132	Electrical One (1) Year or 18,000 Miles Limited Warranty (RFW0201).	1	
9100-0135	Aerial Ladder Structure Twenty (20) years or 100,000 Miles Limited Warranty (RFW0403).	1	
9100-0136	Body Structure Aluminum Ten (10) years or 100,000 Miles Limited Warranty (RFW0502).	1	
9100-0138	Cab Structural Ten (10) Years or 100,000 Miles Limited Warranty (RFW0602).	1	
9100-0140	Paint and Finish (Exterior Clear coated) Ten (10) Years Limited Warranty (RFW0710).	1	
9100-0165	Frame Rail Lifetime (50) Years or 250,000 Miles Limited Warranty (RFW0305).	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0000	Vehicle familiarization aerial (Domestic). 3 consecutive days. Use 9300-0315 for additional days.	1	
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0016	Approval Drawings-Standard.	1	
9300-0031	Dash/Console panel layout approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
Dealer Supplied Equipment			