

## KEYNOTES

KEYNOTES ARE TYPICALLY NOT DUPLICATED WITHIN A GIVEN DETAIL. AN UN-KEYNOTED ITEM IN A DETAIL IS THE SAME AS A KEYNOTED ITEM HAVING THE SAME APPEARANCE WITHIN THE SAME DETAIL.

- 1.410 30" X 48" CLEAR FLOOR SPACE FOR WHEELCHAIR.  
1.411 60" DIA. CLEAR TURNING SPACE FOR WHEELCHAIR.  
2.030 EXISTING CAST-IN-PLACE CONCRETE; EARTH RETAINING WALL.  
7.464 FIBER CEMENT SIDING PANELS: USED FOR CEILING/SOFFIT SURFACE; REFER TO SPECIFICATIONS.  
7.929 JOINT SEALANT ASSEMBLY: PROVIDE 1/8" GAP BETWEEN FIBER CEMENT SIDING/TRIM/SOFFIT AND ADJACENT SURFACE AND FILL GAP WITH BACKER ROD AND POLYURETHANE JOINT SEALANT; COLOR TO MATCH ADJACENT FIBER CEMENT COMPONENT, TYPICAL.  
8.311 ACCESS DOOR: 14"x14", HINGED, WITH FLANGED FRAME FOR CEILING MOUNTING; PRIME STEEL; PROVIDE SUPPLEMENTAL ROUGH CARPENTRY WOOD FRAMING BETWEEN JOISTS TO CREATE ROUGH OPENING FOR MOUNTING DOOR; SCREWDRIVER-OPERATED CAM LATCH; ACUDOR MODEL #ED-2002.  
8.360 ECTIONAL OVERHEAD DOOR: 15'-0" WIDE X 7'-0" TALL.  
8.362 SECTIONAL OVERHEAD DOOR COMPONENT: CONTROL STATION; KEY SWITCHED; TYPICAL.  
10.211 PLASTIC TOILET COMPARTMENT: CONFIGURATION AS INDICATED.  
10.212 PLASTIC TOILET COMPARTMENT: URINAL SCREEN, WITH FLOOR-MOUNTED, OVERHEAD-BRACED PILASTER.  
22.113 PLUMBING PIPING SPECIALTY: FLOOR DRAIN; REFER TO PLUMBING DRAWINGS; SLOPE FLOOR TO DRAIN AS INDICATED.  
22.400 PLUMBING FIXTURE: REFER TO PLUMBING DRAWINGS.  
26.001 LIGHT FIXTURE: REFER TO ELECTRICAL DRAWINGS.

## CEILING SYMBOL LEGEND

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	FIBER CEMENT SIDING CEILING PANELS		SURFACE MOUNTED LED LIGHT FIXTURE (12" X 48")
	ACCESS PANEL: 14" X 14" U.N.O.		WALL MOUNTED LED LIGHT FIXTURE
			DOWN LIGHT FIXTURES A: SPOT, B: DOWN, C: WALL WASHER, D: SCONCE

## WALL TYPES

- 2X4 STUDS @ 16" O.C. WITH 5 1/2" THERMAL INSULATION (R-21) BETWEEN STUDS; PROVIDE SILL SEALER INSULATION BETWEEN SOLE PLATE AND CONCRETE SLAB; SHEATHING ON EXPOSED SIDES AS FOLLOWS:  
-IN RESTROOMS: 1 LAYER OF 1/2" CEMENT BOARD  
-IN UTILITY ROOMS: 1 LAYER OF 5/8" PLYWOOD  
-IN OTHER SPACES: 1 LAYER OF 5/8" EXTERIOR GYPSUM SHEATHING  
2X6 STUDS @ 16" O.C.; 1 LAYER OF 5/8" EXTERIOR GYPSUM SHEATHING ON EACH SIDE; PROVIDE SILL SEALER INSULATION BETWEEN SOLE PLATE AND CONCRETE SLAB.  
2X4 STUDS @ 16" O.C. WITH 3" SOUND ATTENUATION BATTS BETWEEN STUDS; PROVIDE SILL SEALER INSULATION BETWEEN SOLE PLATE AND CONCRETE SLAB; SHEATHING ON EACH SIDE AS FOLLOWS:  
-IN RESTROOMS: 1 LAYER OF 1/2" CEMENT BOARD  
-IN UTILITY ROOMS: 1 LAYER OF 5/8" PLYWOOD  
-IN CONCESSIONS: 1 LAYER OF 5/8" EXTERIOR GYPSUM SHEATHING

## ROOM SCHEDULE

RM. NO.	ROOM NAME	RM. NO.	ROOM NAME
100	GATHERING SPACE		
101	CONCESSIONS		
102	WOMEN'S RESTROOM		
103	FAMILY RESTROOM		
104	UTILITY		
105	MEN'S RESTROOM		

## GENERAL NOTES

- REFER TO DRAWING G100 FOR PROJECT GENERAL NOTES.
- IN WOOD STUD-FRAMED PARTITIONS AND WALLS, PROVIDE 2X WOOD BLOCKING FOR WALL-MOUNTED ITEMS REQUIRING MECHANICAL ANCHORAGE.
- SPOT ELEVATIONS ARE DESIGNATED NOMINAL HEIGHTS ABOVE FINISHED FLOOR UNLESS NOTED OTHERWISE. COORDINATE FINAL HEIGHTS OF CEILING ELEMENTS WITH INFORMATION CONTAINED ON STRUCTURAL, MECHANICAL, PLUMBING, AND ELECTRICAL DRAWINGS.
- COORDINATE EXACT LOCATIONS OF TOILET ACCESSORY ITEMS WITH ACCESSIBILITY AND MOUNTING INFORMATION CONTAINED ON DRAWING A201 AND WITH OWNER'S REPRESENTATIVE.
- REFER TO SHEET A900 FOR TOILET ACCESSORIES.

ISSUED	DATE	BY	FOR
10/12/2021	10/12/2021	10/12/2021	10/12/2021

JOB NO.	19-130-1277
DRAWN	HMA
CHECKED	CDH
APPROVED	CDH

SHEET TITLE

FLOOR PLAN AND REFLECTED CEILING PLAN

SHEET NUMBER

A310

KLUBER  
Architects + Engineers  
Baltimore, Illinois 60510  
Tel. 630.406.2413  
Chicago, Illinois 60606  
Tel. 312.667.6970  
www.kluberinc.com

## REFLECTED CEILING PLAN

SCALE: 1/4" = 1'-0"

1

## FLOOR PLAN

SCALE: 1/4" = 1'-0"

1