MEMORANDUM

TO:

Bill Wiet

Stephane Pfifer Alex Minnella

FROM:

Bruce L. Goldsmith

RE:

Narrative of Changes to Old Dominion Plan and Additional Information to

Address Neighbors' Concerns

DATE:

June 9, 2016

As you requested, we are submitting this "narrative" on behalf of our client Old Dominion Freight Line, Inc. to address a variety of issues raised by the neighbors, City staff, or members of the P&D Committee. These include the following:

1. <u>Site operations</u>. The truck terminal will have tractor trailers entering the site and exiting the site on Meridian Road on a 24 hour basis from Monday to Friday. In general, from approximately 3:00 a.m. on Saturday until after 6:00 p.m. on Sunday, there is no activity on the site

For the most part, drivers entering the site will back their trailers into the docks. The tractors/cabs used by drivers who make pick-ups and deliveries do not have any back-up horns or alarms. However, there are occasions where trailers are moved on the site by "spotters" which are smaller cabs that are equipped with "white noise" back-up alarms. No more than two (2) spotters will be operating at any one time.

- 2. <u>Back-up Horns</u>. As noted above, spotters are equipped with back-up horns using the white noise technology. Dr. Thunder testified before the P&D Committee about the effectiveness of such horns. Old Dominion has since recorded the sounds emitted from a prior model of a backup horn still in use at the Chicago facility and also one using the white noise device, measured at 25 feet behind the spotters. Dr. Thunder then graphed the two sounds. The louder horn peaks in the range in which the human ear is most sensitive. Dr. Thunder's graph of the two horns along with the recorded sounds are attached hereto as Exhibit 1. He can explain this further at the next P&D Committee meeting. We will also reproduce these sounds for the P&D Committee as part of our PowerPoint at the next meeting on June 16th.
- 3. **Berming**. By eliminating one aisle from the fueling center, the berm along Meridian Road has been expanded in width. As a result, the berm is now 6-10 feet high along Meridian Road using a 3:1 slope. On the Sunrise Road side, the berm is 4-6 feet in height, using a 2:1 slope. The six foot portion of the berm is directly across from all three houses on Sunrise Road. The emergency fire access has been moved to the farther end of Sunrise Road to eliminate any break in the berm in front of the houses on the south side of Sunrise Road. The berm and fire

Bill Wiet Stephane Pfifer Alex Minnella

access changes were incorporated in the revised preliminary plan submitted to the City on June 3, 2016. A reduced version is attached as Exhibit 2.


- 4. Landscaping. The new landscape plan incorporates 12 foot high evergreens on both the Meridian Road and Sunrise Road sides from the entrance south to Sunrise Road and down Sunrise Road until the fence ends at a point at the tree line west of the third house on the south side of Sunrise Road. See Exhibit 3. Although not required under the City's landscaping standards, tall evergreens are also being placed on the south side of the Sunrise Road right of way to replace material that may be removed when the roadway and utilities are installed. A buffer is being provided on Meridian Road in front of the only house on the east side of Meridian Road to enhance visual screening. In addition, street trees are being installed on the east side of Meridian Road along its entire length from Ferry Road to Sunrise Road. All street trees will be at 4 inch caliper, rather than the City's standard 2 1/2 inch caliper requirement, for the streetscape on Meridian Road and the north side of Sunrise Road. Due to the slope of the berm on Sunrise Road, it is to be planted in low mow fescue to eliminate the need to provide lawn maintenance. These changes to the landscape plan were delivered to the City on June 3, 2016. We are resubmitting pages 3 and 4 of the plan with this narrative in order to call out the 200 feet of 12 foot Simtek fence along the east end of Sunrise Road, as recommended by Dr. Thunder. It also shows the location of the 8 foot sections of Simtek fence, as well as the higher berm heights on both the Meridian Road (south of the entrance) and Sunrise Road sides.
- 5. **Sound attenuation by fencing.** Consistent with Dr. Thunder's testimony, a special fence has been specified from the maker Simtek. We have previously provided staff with the specifications for this fence, a copy of which is attached as Exhibit 4a. In addition, we have had the landscape architect prepare a line of sight exhibit to show that the fence on top of the berm extends well above the height of the exhaust pipe on the trucks to create an effective sound buffer. As Dr. Thunder indicated, sound follows line of sight. Our depiction shows the line of sight from the only two story house adjacent to the site, which is located on the south side of Sunrise Road just west of Meridian Road. The six foot berm and the twelve foot fence along this portion of the berm provide an extra level of screening for the two story residence. For the rest of the site south of the entrance on Meridian Road to a point past the third house on Sunrise Road an eight foot fence together with a minimum 6 foot berm will be constructed to provide a screen of fourteen (14) feet. This will completely address the line of sight issues on the four houses along these two roadways. We are also enclosing a line of sight depiction of the area in front of a one story house. Exhibit 4b.
- 6. **Lighting**. The site lighting meets the City's standard for no spillage as noted in the attached lighting plan as Exhibit 5. Although this is really a final plan detail, we felt it was best to provide this now. In addition, we provided an aerial of the OD Memphis facility, which is twice as large and adjacent to a residential subdivision. The aerial shows there is no spillage and the residential neighbors are thus protected. See aerial, Exhibit 6. In addition, with the use of the berms (at a minimum of six feet across from any of the adjacent homes) and an 8 foot fence (plus the run of 12 foot fence along the frontage of the 2 story house), as well as 12 foot evergreens placed at the top of the berms, there is a visual buffer to the on-site lighting.


- 7. <u>Traffic</u>. The traffic study established that the volume of traffic generated by the OD facility has an impact of less than 1% to the area roadways. Moreover, Ferry Road is only at 40% of capacity in spite of all the buildings operating within the Duke development.
- 8. <u>Ambient Noise</u>. Old Dominion asked Dr. Thunder to conduct a noise study to measure ambient noise at the site to compare with noise that will be generated from the site when it is in operation. This study was conducted from the afternoon of June 2nd through the morning of June 3rd. Due to the absence of bad weather, the conditions allowed the collection of good data. The study compares the level of ambient noise at the corner of the Old Dominion site at Meridian Road and Sunrise Road. It shows that while evening rush hour readings are below the state standard, early morning rush hour readings (between 4:00 am and 6;30 am) exceed the state standard. Moreover, the nighttime levels sometimes exceed the daytime levels, which Dr. Thunder indicates is unusual. Dr. Thunder indicates further that the operation of the terminal will not increase these levels. See attached ambient noise graph, Exhibit 7.
- 9. <u>Adjacent Lot on Ferry Road</u>. We are enclosing a copy of the listing sheet to answer a question posed by Alderman Donnell. Exhibit 8.
- 10. <u>Annexation Agreement.</u> We are also enclosing a revised annexation agreement that is consistent with your last version, but adds the commitments as additional conditions at the end of the document. Exhibit 9.
- 11. <u>Miscellaneous Documents</u>. Although other documents have been provided previously, we are also enclosing the following. An electronic version of this memo with exhibits will also be transmitted.
 - a. Huff and Huff study in Crest Hill. Exhibit 10.
 - b. Simtek fence cut sheet and sound study. Exhibit 11.
 - c. Revised Fire Access Plan submitted last week. Exhibit 12.
 - d. Detail of plant materials used in revised Landscape Plan. Exhibit 13.
 - e. Revised sheets 3-4 of Landscape Plan to show higher berms and fence details. Exhibit 14.

Comparison of Two Back-up Alarms

Top panel: conventional tone beeper. Bottom panel: white noise alarm.

EXHIBIT







Time-course analysis: shows the conventional on-off cycling with a duty cycle of 50%.



Spectral analysis: shows a frequency of 1,400 Hz that is more than 50 dB above the background noise.







Time-course analysis: shows an on-off cycling with a duty cycle of 50% - same as the conventional beeper.




Spectral analysis: shows a broad range of high frequencies from 1000-5000 Hz that is 20 dB above the background noise.





















desail Bank Propiet (ed.), you are all everying with the temporal for party and seminate statistical by the official fact the place of two Arminia. Provide and of the great spring reportion and restrict parameter of send and, to specified Provide alterphy related and, one fame then the (2) purps als and from all commiss and communication orders grown. Provide may and annotate of growth and descriptment when the private (challes, or descripts) and in delays not come the commission of the growth provide and arrowment of a Drivery beam of Contrally Chapter and no makes of the commission of the commission of the commission of the commission of the communication of the commission of the commiss Temperary Land Basel Picture - 0 has/1,000 eg/s.

201 Germany Margens W/III

202 Arrand Respons e man amain, the ormani of and behavior is to quadriculary shall many the total ormany of per-open (1935) are now. But top and PLS leading Mormation about to provide to the Landauge when PTP to State (1935). or cross state to braidful is all planning arms ambidning dry repeat, mestic, and set remain solls to, Alto sells, and servine used pressure sharing the perminentary and substitutional of the resists asseting Description for the born
Description for the born
Titley Online Force
Transfer force
Transfer force
Transfer force
Transfer force
Transfer force dictamental trans, niprimi, generalistari esi pereprista ler a primi di ser pere dise data di completta Reject defenta esilekti data esi esimilatari penalit, manja fer defenta matera (term replant ir Delary, desa esi demogri de situa er manda piranamani er inidatia utaka era layard Lendaga. Exemples tobal grafiles designated to place graph are extendened sub-an-risks fill, educate desirage confidence or observation, rodily tardinaps broklasts before planting ministima shifi hisian. Jameriy, herbibry, sprajim, maleby ard proby for jark material and brimming gravitame, translated for Jameriy, herbibry and massing prom own shell in previous or (10) days prior to request for hymentics for find quadrience. Lordsmaps deprivate shell results again of all retrictions when massed also full Groundy Basser, All owes with the countries of entergens group shall solving to the appealment, All the State of the special countries of the state of merrys and anticide grades, mais and clear bands. Observe the graditions other which such is to performed and order technique hardware of consideration technique. Do not present such the arts with translationary conditions have been corrected in an ecosphilate review. there has (2) benying at the state in two tests between the control between, and all other requests of mills the specified as prime to Londonge Josephan for resource to efficie superiors. He was presented that before the specime and apartition of majorial beginning that the profess is the Joseph and CDP specimens. لشجال لمن (2) سيئت با ساز لحد با منطاني ليسبق بدان بمسيرسطينيس آب بينا مشاكره سيئسسيد له المشمه الاخالمال آب جواب جال من سائلت جهوميط. the freely, clearly, now year of the question and programmers are quantitude in their section and and the force year with the device the programmer of the programmer of the programmer of the project data the content of the Principal Policy within the series OPA London III Exemples on the project data of the Device of the produced account from potable this generation made to approve the time the programmer of the produced account from potable this generation made to approve the time. the Berlin orderprod tillly leader crops on form only lead tillly leader sorten sorten or automore of tilly leaders, or a courty acceptance of leading for the process of till adopt more of uses, Coverno stell to reproduct to on decays to the pro-line and more of uses, Coverno stell to reproduct to on decays. de est erain admitistare. If spindent besteups erateral à est attacation, admit le bestimp Arablant print et en-mailablité and proposal for une et apprehent erateral. (Grandy Shame). The of more comp and he agradated. Three deals he in her a semi symbol. In (2) Japan hard, he make some At heat (2) of supposite someting and his relative this summin, At heat (2) of the prompts, sometin, it formed to play that he time and t. (a) Adjust of Symathten instruction recommending precedents to be exclusived by the for the maintenance of invisions until for the Pull year. Believe print to expection of a maintenance product. The property of the property o photogram on the Course of the ampliful opin beings The second in th * 0.0 § 88 8222 2 Addiginals (vertal)
Addigi right of extrapol to an in primaryly fundamental public instruments and its plane shall be reading as a second A the extrapolity fund in the primary shall also a second be self to all fund and will be funded by the second A material of 1000 terms. Behaviously of plan fund the operated by the Landscope Appropriate prior to Violation. frenché palaire all misser arminen et ésan vammanad basel (ambajós a site) for all piechty pits, permiss, armine and openium arms. Topadi stell to antislavad hans en sty restrictions realized from the sail task in 100 Preview pierce committent and understand in restorate continues or integral and pole and with red limit. Uses the minimum number and languh of numers respired by ANSI 2001 for the got size around or taken At land thirty (80) days prior to the Impirity of lasts in such own, spread by the Londonson Artificat. Provide relain coronains of streated implement. impanitor. All plants and in tadjus to impantion and making at the plant of graphs or open about your enforcement of the plants, right of impanits and impanits a Devisions from Propile symbol of the Propile down or fided and with risk limit from the revisions revision of more supervision of Albel for the type and related of strain registed. Therein being and bringing (Bm) decisions drain. lain o'd law'i'tu Panis Aran Piter's Entrike pe manimiza's rammanidae. Deliciosa (Tross). Propide tress of relays and office (black or shown and sitts terrolive) saniforation reserved and by 1862 by type and section respiral. Foreign sixtle date form tress section, stem special forms are shown on listed. Propide topical and bringaped (1885) debitions types. Dadlyn. Profess from, errole and other plants carrylying with the recommendating and equiversity of ANM 2661 Televised for Nature, Disable and as further specified hiere and Variety. Preside narmay group plant, replanted true to regree and variety Till to a septh of not less than \$1; apply sail emergeneits; remove high areas and Fill in decembers; till sail to a hymogenia missen of fire lattice, remove brings, class, saves over I Review which gam, regulation and test. Discuss of each messard legally off-case. Do not term over this self-lessy property for laters. Total Co The state of the s STATISTICS OF PERSONS ASSESSED. Total Hildfauer/Ordelanes Training States Communication of the Communication 24.00 25 3 8888 MINO, or opposed upod. To be created Court of approved equal. To be brainline The Dearth Infrarrantal Residint shall be seen to dearth, as least team per your defect to browner form of the Establishment and Théodormen, to Administ completions with the infrarran-rand professions about (fee 100 Commiss). A methodoly name will be profess to the Court by Joseph Steff (feeling and Francisco). terment extend and relation and controls in more to because the restant part (tree, "Solice and IS"), to extend they the collection of relations of the relation of relations of the relation Law Pau Fame and Nation Family areas are to be remark only one per spring during the least transport small different period. Polytick plantal and model areas by ustaring relity/regrading, restarting and implementing areas control on regards to excellent regulation from all product on two extensions. A The Contractor shall be shally requested by married that all terms are planted to a recibal and planted or property of the planted of th Read land with a series of series of the ser This year had, a security or making mentation, the real and other and stateling means from (8) from year had, the forestens and mental enter write and by making made quantity in the distriction of Africance in the security of the securi Prom mby Pyland or dan branden From Fluendag trees, if way. Protect entrol beater of tree deving aligned and protect generalize. From styles is replay retard despects. It asserts to sub-devial brands from protects. The black and refreshing (Find) and derive and is useful at \$0 or (mail 10) for \$0 or \$1 o dereiden ergenfeld ermiderte stell ist endeltad mit tim mad eine die einde af dijbet ann. Federich ein ist bedar oder mad, under Hen mad er delta ben gege techn. Helen eren desti est reuten bestäte y promet, conjuncted mile spell to delete at need print to medic of Servedad removem for the Servedad Company of the Servedad of the Servedad Committee, involve Apple Servedad removement of the Servedad At the cold foreign factor to delete, The parties for printing province most should be from April 1 to John 10 or Beginnings 15 to John Marrier 15 or John Marrier 15 or John Marrier 15 or John Princip play, together and plantad arms. Preprint has been 27 bitmores of redain and such that the of best 27 and frach hand with adjacent friend grades. Patricks assume that filter is all lives. Die Lip of halefil to elles for moleking. Provide additional haseful horm drawal salge of emerations to form draftes water to callists water. Straight filips shall not be plateded into Steen the openified rade and shall be protected with open estimates surproteing all record opinyships of physics. then from the set symmetry to some dealt has been and as some as followed to symmetric (the people). In filmeding with happylessen, sometrake die landen deep stemm of departement personnent system bespect within the planting some will remove live plane in like of some Amaling and will tradeing/Princing shall not be dane during parisals of neit, somere draught, high What, exclusive measure, frame graves, or other conditions that precises satisfactory rassits. There is altered unit, all making superiors, that he calculated and all paints to man units, but a proper service and the calculated and the calcu tybr is amalog, plating area stad ham at land Ludio Falom of their projected damals Carron, other, store per 2' devictor, reals and other activeness mitter stad in revised on Assault of April of Malos relations, personalist, and dynamic shall be planted in continuous bank of planting sail ministers ream of 8° days. Install per speaking indicates on plant. Company plays while to play to it is retard graphing within designal order containing saturates the or designal order. There is no thing and the play to the containing the order is the play to the containing the cont efter the employ operation is completed, heldel around control blocket per ma professions The General Contention and Matrix Condessions Controller shall be responsible for performing and are resonancy to approximate and residually on manageable sensible place to manife, a fill ories result to regardy proposed select material begins. Engineering broken four still premium grand mental shall a platform Labor to general people.

**Condession broken for the control of the SIMTEK FENCE LAYOUT DETAIL The Long -Term Counties and Politicaness Ries shall be written to belief goldelme and estimate for borning manufact application of implicits, deposition removed and frametics schools for storm deviction and information remove. A fird empfehen repart and Leng-Toron Operation and Hobertooks Then shall be earthful by the Dembyer/Course's Ordermand Specialists as has been able to easily sexual for the enaby sexua Figure prior to the expectation of any landscape Case Bene or Leaster of Course penual for the enaby sexual Figure prior to the expectation of the landscape Case Bene of Course (Case Case). (The Limbsons Arabbasi community for right to requisioning plants, from and strain mixture at plant of speaks are as the latest plants for surpliness with regularization for speak, speaks and a speak, revisit, sin, and presents. Dong indume unit, they retireds not expense, when details. East previous unit over the addition from it is entirely another. How the feelings soft is garphied, beliefly neitheres, the tertains frethest all, year request, rote a feel feelings to describe statebackey. After feel econtenes, the Same self-many-self-many-self-per feelings are to be self-many-self-per feelings. Product fertilisates until gest protection from deriving dat to fertilisate approximation, approximation by other british and transport for the process of the contraction of the contraction process of the contraction and the contraction of t fieldly the Landscape Architect within the (5) days effect completing while end/or a serving in such arms. Supply written efficient, emilywy aprymotopi of med minures and edegrity of pieck meterosis with respect to species, reminy and mores. SUNRUSE HUAD 锁







BUTTERFIELD CENTER FOR BUSINESS & INDUSTRY

UNIT 4 - LOT 402

AURORA, ILLINOIS







MERJDIAN RUAD

OLD DOMINION
FREIGHT LINE, INC
50 0.0 DOMINION
FREIGHT LINE, INC
50 0.0 DOMINION
FREIGHT LINE, INC
50 0.0 DOMINION
FREIGHT LINE
FREIGHT
FREIGH








SIMTEK FENCE LOCATION SCALE: 1"=50"





BUTTERFIELD CENTER FOR BUSINESS & INDUSTRY

UNIT 4, LOT 402 AURORA, ILLINOIS


6/9/16

EXHIBIT LA



BUTTERFIELD CENTER FOR BUSINESS & INDUSTRY

EXHIBIT




THIS LIGHTING DESIGN IS BASED ON LIMITED INFORMATION SUPPLIED BY OTHERS TO HUBBELL LIGHTING. SITE DETAILS PROVIDED HEREON ARE REF CRITICAL SITE INFORMATION (POLE LOCATIONS, ORIENTATION, MOUNTING HEIGHT, ETC.) SHOULD BE COORDINATED WITH THE CONTRACTOR AND/OR

- 2. LUMINAIRE DATA IS TESTED TO INDUSTRY STANDARDS UNDER LABORATORY CONDITIONS. OPERATING VOLTAGE AND NORMAL MANUFACTURING TO
- 3. CONFORMANCE TO FACILITY CODE AND OTHER LOCAL REQUIREMENTS IS THE RESPONSIBILITY OF THE OWNER AND/OR THE OWNER'S REPRESENTA

TITLE:

OLD DOMINION FREIGHT LINES
AUROA, IL
SITE LIGHTING PLAN





REMAX Northern Illinois

CORPORATE CITIZENSHIP

REAL ESTATE NEWS

ccount click here





\$899,000

30W575 Ferry R... NAPERVILLE, IL ... 6.47 ACRE Active













FAVORITE


SHARE

INFO

VISIT

MARKET REPORT VIRTUA TOUR

My Property Finder members always view full listing details. Login or Register











\$899,000

Mortgage Calulator ✓

Active

For Sale

MLS#: 09118106

Location, Location, Location! Prime Development Opportunity!!! 6.46 prime acres of land in a newly developing area. Endless possibility's. Great location easy on and off of I-88. Unincorporated Naperville! Potential for Horse property. Currently used for crops with income potential. Bring your development ideas! Two - 3.23 acres parcels with 2 pin numbers. Sold together

Broker Listing provided courtesy of: RE/MAX Action

General Features



\$899,000

SOMETS Ferry Road NAPERMUE IL 60263

6.47







VIRTUAL

TOUR

SHARE

FAVORITE

VISIT

MARKET REPORT

ACCOURT

NE

出書を

estation, Location, Lecanoni Frime Development Opportunity!!! 6.46 prime acres of land in a newly developing area. Endless possibility's. Great location easy on ind off of 1-88. Unincorporated Neperville, Potencial for Horse property. Currently used for crops with income postencial. Bring your development ideas, Two - 3,23 NLS#: 09:18:06 Active iches parceis wich 2 pin numbans, Sold together Wortgage Calulator V \$899,000

A Brokenty Lissing provided courtesy of SE(1883, Action

Seneral Features

· County: Do Sage

Property Features

3uilding Features

· Current Use: AgriculturaPland

- Acreage: 6 47

· Utilities: Blectric Meanby, Gas

Road Surface: Asphalt

Nearby, Sanisary Sewen Nearby

Schools

High School District; 20±

• Middle School District: 294 Elementary School District: 204

Burgermeister REMAX Action 680-842-5145 Peggy

Ask a Question

· Area: Naperville

THE PARTY IN Section 2 HI CH

I would like more information about the home located at 30W575 Ferty Road NAPERVILLE, IN

EXHIBIT "A"

ANNEXATION AGREEMENT FOR APPROXIMATELY 4.958 ACRES LOCATED ALONG SUNRISE ROAD AND WEST OF MERIDIAN ROAD

This ANNEXATION AGREEME	NT, hereinafter referred to as "AGREEMENT", is made and
entered into this day of	, 2016 by and between the CITY OF AURORA,
ILLINOIS, a municipal corporation	on, "CITY"; and OLD DOMINION FREIGHT LINE, INC.,
"OWNER" and "DEVELOPER".	The City, Owner, and Developer are referred to as "Party" or
"Parties".	

WITNESSETH:

- 1. The Owner is record title holder of the Subject Property consisting of approximately 4.958 acres, legally described in Attachment "A" attached hereto (the "Subject Property").
- 2. The Owner has attached hereto as Attachment "B" a disclosure of the beneficial owners of any land trust holding title to all or a portion of the Subject Property, if any or a statement indicating that there are none.
- 3. The Parties to this Agreement desire that the Subject Property be annexed to the City of Aurora with the benefits of the Subject Property being as follows:
 - a. Full development potential of the Subject Property;
 - b. Establishment of high quality development standards that will elevate, support and stabilize property values for the proposed land uses;
 - c. Provision of a water supply system that has been engineered to supply water services to the Subject Property;
 - d. Provision of a sanitary sewer system that has been engineered to supply services to the Subject Property through the Fox Metro Water Reclamation District's facilities, or the City's facilities;
 - e. Provision of police protection by the City's fully trained, staffed and equipped Police Department;
 - f. Provision of fire protection by the City's fully trained, staffed and equipped Fire Department; and,
 - g. Favorable insurance rates due to the City's Fire Department having a Class 2 rating.



- 4. The Subject Property is contiguous to the city limits of the City of Aurora, Illinois, and is not within the corporate limits of any other municipality.
- 5. This Agreement is made pursuant to 65 ILCS 5/11-15.1-1 and 65 ILCS 5/7-1-1 of the Illinois Compiled Statutes.

All notices, publications, public hearings, and all other matters attendant to said Agreement as required by State statute and the ordinances, regulations, and procedures of the City have been met prior to the execution by the Parties to this Agreement.

NOW, THEREFORE, it is agreed by and between the Parties hereto as follows:

SECTION A Duration, Applicability and Owner/Developer Responsibility

- 1. This Agreement shall be binding upon and inure to the benefit of the Parties hereto, successor owners of record and/or Developers of the Subject Property, or any part thereof, which is the subject of this Agreement, and their heirs, executors, administrators, successors, assignees, lessees, devises and upon any successor municipalities for a period of fifteen (15) years from the date of execution hereof, unless changed in accordance with the law.
- 2. It is understood and agreed by the Parties hereto that, in the event all or any portion of the Subject Property is sold or conveyed at any time during the term of this Agreement, all the obligations and responsibilities of the Owner, as herein set forth shall devolve upon and be assumed by such purchaser or grantee, and the Owner shall be released from all obligations which relate to that portion of the Subject Property as may have been sold or conveyed.
- 3. Owner agrees to record a copy of the City ordinance providing for the execution of this agreement and an executed copy of this Agreement with the appropriate county recorder within sixty (60) days of the approval of said ordinance.
- 4. Owner agrees to file with the City Clerk a properly executed Annexation Petition pursuant to this Agreement covering the properties described in Attachment "A" not later than ninety (90) days after the execution of this Agreement.
- 5. Owner agrees to petition and diligently pursue the Fox Valley Park District for annexation of the entire Subject Property within ninety (90) days of annexation to the City.
- 6. Owner agrees to petition and diligently pursue the Fox Metro Water Reclamation District for annexation of the entire Subject Property within ninety (90) days of annexation to the City.
- 7. Owner agrees to petition and diligently pursue the appropriate U.S. Post Office for an "Aurora" mailing address on the Subject Property of this Agreement, within ninety (90) days of annexation to the City.

- 8. Owner agrees to dedicate right of way for proposed roadways on, through, adjacent, to the Subject Property, at the time of the approval of the final plat and plan of the Subject Property as specified herein. To the extent there are existing roadways that have come under the jurisdiction of the City as part of the annexation of the Subject Property but are not formally owned by the City, the Owner shall make the necessary dedication of such right of ways at the time it submits for final plan and plat approval.
- 9. Developer agrees that all existing structures on the Subject Property shall be razed and removed within one (1) year after the first final plan and/or plat approval for any portion of the Subject Property
- 10. Developer agrees to connect to the public sanitary sewer system at the time the Subject Property is developed and shall pay charges for sewer service as are prescribed by City ordinances and by the Fox Metro Water Reclamation District.
- 11. Developer agrees to establish cross-access easements with regard to private drives on the Subject Property that are mutually agreeable with Owner/Developer and the adjacent property owner.
- 12. Developer agrees that one-hundred percent (100%) of the public improvements costs required to serve development to be constructed on the Subject Property shall be the Developer's responsibility.
- 13. Developer agrees that the cost of roadway improvements described in Section E as the "Developer's Responsibility" shall be constructed at one-hundred percent (100%) the Developer's cost.
- 14. Owner agrees to cooperate with the City in establishing any special service areas required by the City concerning storm water control and common areas maintenance for Subject Property and shall establish any required specific Special Service Area ("SSA") within 60 days after Final Plan, Plat, and Final Engineering approval, and prior to any conveyance of any parcels to any non-Developer/Owner controlled person or entity. Owner waives any objection to the establishment of an SSA for the Subject Property, and agree that failure to comply and have a required SSA established may result in the City withholding Occupancy Permits in the Development. Owners of land in the Butterfield Center for Commerce and Industry have set up a not for profit corporation to act as the Property Owner's Association called the Butterfield Owner's Association and Developer shall bind the Subject Property to the covenants and conditions of this association.

SECTION B. Annexation, Zoning and City Responsibility

- 1. Subsequent to the approval of this Annexation Agreement, the City agrees to adopt an ordinance annexing the Subject Property to the City pursuant to an Annexation Petition, subject to the terms and conditions herein.
- 2. In the event that an Annexation Petition for the Subject Property is not filed within ninety (90) days, the City may void this Agreement by ordinance.

- 3. Subsequent to Annexation the City agrees to adopt an ordinance zoning the Subject Property as part of the Area B "Manufacturing (Office/Research/Industrial)" of the Butterfield Planned Development District (P.D.D.) except for variations which are specifically set forth as part of Area B "Manufacturing (Office/Research/Industrial)" of the Butterfield Planned Development District (P.D.D.) and accompanying Plan Description.
- 4. The City agrees to adopt the Preliminary Plan and Plat documents incorporated herein as Attachment "C" by separate Resolution, upon and concurrently with annexation of the Subject Property.
- 5. City agrees to adopt a recapture ordinance(s) to reimburse Developer, as specifically requested subsequent to this agreement, for the cost of installing Meridian Road and Sunrise Road, including engineering, construction, and other costs from owners of property which may be reasonably expect to benefit from such facilities. The recapture ordinance shall be for fifty percent (50%) of the cost of any full cross section improvement of the roadway installations across the frontage of the parcels that are not included in this annexation to the extent such properties are annexed to the City either along the east side of Meridian or the south side of Sunrise. The City shall adopt the recapture ordinance within a reasonable time following notice from Developer that facilities are complete, and provided that the Developer supplies all information required by the City to process said ordinance(s). The recapture ordinance shall provide for Developer to be paid by said owners a reasonable amount of interest of no more than five percent (5%) on the amount expended in completing the improvements, which interest shall be calculated from and after the date of completion and acceptance of the improvement, said interest shall accrue for a maximum of ten (10) years, and for the payment of all recapture sums due at the time of connection, or use by any benefited property owner.
- 6. The City agrees that the dedication of land or cash in lieu of land is not required as the Subject Property is being zoned ORI.

SECTION C Development Review

- 1. No portion of the Subject Property shall be developed until and unless the City in accordance with the conditions has approved such development hereinafter set forth.
- 2. The Subject Property described in Attachment "A" shall be governed by all of the requirements contained in the Aurora Zoning Ordinance No. 3100, to be treated as part of the Area B "Manufacturing (Office/Research/Industrial)" of the Butterfield Planned Development District (P.D.D.) except for variations which are specifically set forth in the accompanying Plan Description.
- 3. Except as provided herein, the provisions of the Aurora Subdivision Control Ordinance shall govern all development of the Subject Property regardless of the size of a parcel being developed at any one time. If no subdivision plats for the Subject Property are required, then Owner agrees that the public improvements and other subdivision control

requirements of the Aurora Subdivision Control Ordinance shall be applicable to the Subject Property, except for variations which are specifically set forth as part of Area B "Manufacturing (Office/Research/Industrial)" of the Butterfield Planned Development District (P.D.D.) and accompanying Plan Description.

- 4. Preliminary plans and plats and final plans and plats may be submitted and approved simultaneously.
- 5. Final plats may be presented to the City for approval individually.
- 6. Building elevations shall be presented for approval with the Final Plat and/or Plan and will be evaluated based on quality and variety of building materials, orientation and presentation from the public street, and the use of architectural elements.
- 7. The construction of buildings on the Subject Property shall be in accordance with the Aurora Building Code requirements in force at the time of issuance of building permits.
- 9. All codes and ordinances of the City of Aurora not amended by the Butterfield Plan Description and all codes and ordinances applicable Citywide adopted by the City after the execution and entering into of this Agreement by the Parties hereto shall apply to the Subject Property.
- 10. Engineering plans and specifications for the improvements to be installed in each phase of the development shall be submitted to the City together with the final subdivision plat for such phase.

SECTION D Variations and Special Uses

The variations and conditions as set forth in the Area B "Manufacturing (Office/Research/Industrial)" of the Butterfield Planned Development District (P.D.D.) and accompanying Plan Description.

SECTION E Roads, Public Utilities and Storm Water Management

1. Meridian Road – The public right of way has been dedicated for Meridian Road and is located along the eastern property line of the Subject Property. Said right of way shall be established at 66 feet, with a cross section of 39 feet of roadway width from back of curb to back of curb with B6-12 curb and gutter. DEVELOPER RESPONSIBILITY: The Developer shall be responsible for dedicating any necessary right-of-way to meet the 66 foot width along the entire frontage of the Subject Property and intersection right-of-way triangles as requested by the Engineering Division. The Developer shall be responsible for construction of a full cross section improvement from Ferry Road to Sunrise Road. The cost of said improvements adjacent shall include, but not be limited to, engineering, construction, utilities, interest and other costs. The principal access point(s) from the existing public right-of-way and/or proposed roadway extension for the Subject Property shall be from Meridian Road. Developer shall construct a sidewalk along the east side of Lot 402.

- 2. Sunrise Road The public right of way has been dedicated for Sunrise Road and is located along the southern property line of the Subject Property. Said right of way shall be established at 80 feet with a cross section of 39 feet of pavement width back to back with B6-12 curb and gutter. DEVELOPER RESPONSIBILITY: The Developer shall be responsible for dedicating any necessary right-of-way to meet the 80 foot width along the entire frontage of the Subject Property and intersection right-of-way triangles as requested by the Engineering Division. The Developer shall be responsible for construction of a full cross section improvement from Meridian Road to Frieder Lane. If Frieder Lane has not been extended to Sunrise Road prior to occupancy of Lot 402, a turnaround for Sunrise Road shall be required prior to an occupancy permit being issued for Lot 402. The cost of said improvements shall include, but not be limited to, engineering, construction, utilities, interest and other costs. Developer shall construct a sidewalk along the north side of Sunrise Road. The City recognizes that Sunrise Road will not connect to future Frieder Lane until Lot 401 is developed.
- 3. Frieder Lane A portion of the public right of way has been dedicated for Frieder Lane and is located along the western property line of the Subject Property. Said right of way shall be established at 66 feet with a cross section of 39 feet of pavement width back to back with B6-12 curb and gutter. DEVELOPER RESPONSIBILITY: The responsibility for dedicating any necessary right-of-way to meet the 66 foot width along the entire frontage of the Subject Property shall be with the development of as part of Lot 401. The Developer shall be responsible for dedicating intersection right-of-way triangles at the northwest and southwest corners of Lot 402 as requested by the Engineering Division. The responsibility for construction of a full cross section improvement from Ferry Lane to Sunrise Road shall be with the development of Lot 401. Due to the need to determine the profile and location of public utilities (in particular storm sewer) once Lot 401 is developed, no sidewalk will be required on the west side of Lot 402.
 - 4. A double-fed public water main system is required to provide adequate fire protection and water service for the Subject Property and each lot.

Sanitary Sewer Language

- 5. Development of the Subject Property requires that adequate storm and sanitary discharge plans, and other related plans, have been approved by the appropriate City of Aurora Department, or agency with responsible jurisdiction.
- 6. Owner has already supplied evidence to the City that the Subject Property is not subject to any jurisdictional review by the Army Corps of Engineers relating to wetland mitigation and wetland/floodplain mitigation shall be subject to review and approval in accordance with the applicable Kane County ordinances.
- 7. A subsurface drainage investigation report shall be submitted to the City's Engineering Division for review, as per the requirements of the Stormwater Ordinance. Any and all field tiles on the Subject Property must be protected during construction and shall be rerouted so as to not run under any building. Any filling operations must be done in such a manner so as not to raise the emergency overland flow elevations on adjacent properties. When, as and if said field tile is re-routed or damaged Owner and Developer shall repair

all damaged field tile, but shall not be required to use any tile of a type, kind or character other than is the same or equal to that presently used in the field tile in question. If the tile is run under any paved area, or within public right of way, then concrete tile must be used.

- 8. Retaining walls utilized within the development shall not exceed three (3) feet in height. The stepping of retaining walls is allowed up to six (6) feet in overall height with a minimum run of three (3) feet between steps.
- 9. All improvements, buildings and structures shall be required to follow the Kane County Stormwater Ordinance requirements as adopted by the City.

SECTION F General Provisions

- 1. In the event that any section, subsection or paragraph of this Agreement is held to be invalid, the invalidity of such section, subsection or paragraph shall not affect any of the other provisions of this Agreement. None of the parties to this Agreement shall challenge the validity or enforceability of this Agreement nor any provision of this Agreement, nor assert the invalidity or unenforceability of this Agreement or any provision thereof as defense to any claim by any other party seeking to enforce this Agreement.
- 2. Any notice or demand hereunder from any Party hereto to another Party hereto shall be in writing and shall be deemed served if mailed by prepaid registered or certified mail addressed as follows:

If to the CITY:

Mayor of Aurora

City of Aurora 44 East Downer

Aurora, Illinois 60507

With copy to:

Aurora Corporation Counsel

City of Aurora

5 East Downer Place, Suite F

Aurora, Illinois 60507

If to the OWNER/DEVELOPER:

Old Dominion Freight Lines, Inc.

500 Old Dominion Way Thomasville, NC 27360 Attention: Phil Danner

With a copy to:

Dykema Gossett PLLC

4200 Commerce Court, Suite 300

Lisle, Illinois 60532 Attn: Bruce Goldsmith

- 3. Should correspondence to Owner be a notification of violation of any provision of this Annexation Agreement, Owner shall have thirty (30) days in which to correct such violation. The thirty-day period shall begin at the time of the mailing of said notice.
- 4. The Parties hereto agree to cooperate in applying the provisions of this Agreement and to fulfill the intent of the provisions set forth herein.
- 5. The Parties agree that the Parties or their successors in title may enforce this Agreement in any court of competent jurisdiction, in an appropriate action at law or in equity, as provided in 65 ILCS 5/11.1-4, as amended, including the right of any of the Parties to seek specific performance of the terms of this Agreement.
- 6. Owner and Developer understand and agree that the Subject Property shall be subject to any lawful fees enacted by the City with regard to development so long as said fees are uniformly applied in the City except for fees that the City elects to rebate to developers pursuant to an annexation or development agreement.

(SIGNATURE PAGES TO FOLLOW)

Executed in Aurora, Illinois.		
SIGNED BY OWNER and DEVELOPER on the	day of	, 2016.
Name: Old Dominion Freight Lines, Inc.		
By: Name:	1	

SIGNED BY CITY OF AURORA on this day of	, 2016.
CITY OF AURORA, an Illinois Municipal Corporation	
By; Thomas Weisner, Mayor	
Attest: Wendy McCambridge, City Clerk	

ATTACHMENT "A"

LEGAL DESCRIPTION OF SUBJECT PROPERTY

LOT 15; TOGETHER WITH THAT PART OF PRAIRIE LANE (NOW KNOWN AS MERIDIAN ROAD) LYING EAST OF AND ADJOINING SAID LOT 15; TOGETHER WITH THAT PART OF SUNRISE ROAD LYING SOUTH OF AND ADJOINING SAID LOT 15; TOGETHER WITH THAT PART OF SAID SUNRISE ROAD LYING SOUTH OF AND ADJOINING SAID PRAIRIE LANE; ALL IN ARTHUR T. MCINTOSH AND COMPANY'S FERRY ROAD FARMS, BEING A SUBDIVISION OF PART OF THE WEST 1/2 OF SECTION 4, TOWNSHIP 38 NORTH, RANGE 9 EAST OF THE THIRD PRINCIPAL MERIDIAN, ACCORDING TO THE PLAT THEREOF RECORDED NOVEMBER 12, 1943 AS DOCUMENT NO. 455751, IN DUPAGE COUNTY, ILLINOIS.

PARCEL NUMBERS: 07-04-102-007 and 07-04-102-008

ATTACHMENT "B" NOT APPLICABLE

ATTACHMENT "C"

PRELIMINARY PLAN AND PLAT PREPARED BY MANHARD CONSULTING

PRELIMINARY PLAN CONDITIONS

- 1. The proposed fences that are not Simtek screening fences shall be decorative metal fences.
- 2. The truck parking stalls shall be modified to be a minimum of ten (10) feet in width and forty-five (45) feet in length.
- 3. The roadway improvements for Sunrise Road, including a sidewalk on the north frontage, shall be shown from Meridian Road to Frieder Lane extended. This extension can be shown as a construction obligation to be completed by the developer of Lot 401 pursuant to the Annexation Agreement.
- 4. The fencing used for screening and sound attenuation from the entrance on Meridian to a point on Sunrise noted in the Landscape Plan shall be eight (8) feet in height, using the Simtek type fencing. On the Sunrise Road side, the fence shall be twelve (12) feet in height for the first two hundred (200) feet and then at eight (8) feet to the far end of the third house on the road, all as shown on the Landscape Plan.
- 5. The evergreens to be planted south of the entrance on Meridian Road and along the north and Sunrise Road shall be twelve (12) feet in height. There will also be twelve (12) feet evergreens along the south side of Sunrise in front of the first house (two story). Evergreens are also shown at six (6) feet in height along the south side of Sunrise where it is expected construction will remove existing plantings. These commitments are shown on the Landscape Plan.
- 6. All street trees shall be four (4) inch caliper in lieu of the City's standard s 2 1/2 inch caliper requirement along both sides of Meridian from Ferry Road to Sunrise Road. Street trees shall be four (4) inch caliber on the north side of Sunrise Road from Meridian to the secondary fire access lane. These commitments are noted in the Landscape Plan.
- 7. Backup horns on the spotters shall use the white noise equipment.
- 8. Berms on the Meridian Road south of the entrance shall be from six (6) to ten (10) feet in height as shown on the Landscape Plan. Berms on the Sunrise Road side in front of the three houses on the south side of Sunrise Road shall be six (6) feet in height with the remainder at four (4) feet as shown on the Landscape Plan.

NOISE MONITORING STUDY REPORT FOR THE CITY OF CREST HILL, ILLINOIS

January 2015





SUMMARY

The following report presents the methodology used, associated testing details, and resultant findings from three evenings of noise level monitoring conducted for the City of Crest Hill in addressing the community concerns associated with the trucking facilities located south of Division Street and west of Weber Road in Crest Hill, Illinois. We hereby certify that to the best of our knowledge the information and data contained herein this report are true and accurate.

Tiny Mel

Tim Kelly, P.E., Huff & Huff, Inc.

Gerry Trzupek, Huff & Huff, Inc.

1. INTRODUCTION

A noise monitoring study was conducted by the Huff & Huff, Inc. (H&H) personnel listed above to evaluate the effect two trucking facilities have upon noise levels at the nearest residential area. The trucking terminals are located southeast of the intersection of Division Street and Enterprise Boulevard, and the nearest residential area is north of the facilities, across Division Street and known as Carillon Lakes. The project area and monitoring location is shown in Figure 1.

Figure 1 – Project Area and Monitoring Location

MONITORING LOCATION

Frucking Facility

H&H conducted noise following the regulations maintained by the Illinois Pollution Control Board and found at Title 35 of the Illinois Administrative Code (35 IAC), specifically those limits and methodologies found is Subtitle H, "Noise Pollution", Chapter I, Parts 900 through 910. Regulations regarding the measurement of highly impulsive noise sources and the regulatory standards for Class C (in this case transportation facilities) noise effects upon Class A (residential) land uses were utilized. Noise measurements were taken for five-hour periods (10 p.m. to 3 a.m.). This time period falls within the state definition of "nighttime hours" found at 35 IAC 900.101, which is 10 p.m. to 7 a.m.

One monitoring session was conducted on a Saturday night when the facility was not in operation to determine background noise levels for the area. The two other monitoring sessions were conducted on week nights with the facility operating.

The facility noise levels, once isolated from background noise and roadway noise, was compared to both applicable octave band-based noise level limits and to impulse noise level limits. These limits are found in 35 IAC 901. The facilities did not exceed either of these noise level limits during the ten hours noise monitoring was conducted.

2. NOISE BACKGROUND

Sound is caused by the vibration of air molecules, and is measured on a logarithmic scale using units of decibels (dB). Sound is composed of a wide range of frequencies; however, the human ear is not uniformly sensitive to all frequencies. Therefore, the "A" weighted scale was devised to correspond with the ear's sensitivity. Noise levels reported using the A-weighted scale are identified using "dB(A)".

The equivalent sound level is the steady-state, A-weighted sound level, which contains the same amount of acoustic energy as the actual time-varying, A-weighted sound level over a specified period of time. The A-weighted unit is used because:

- 1) it is easily measured,
- 2) it approximates the human ear's sensitivity to sounds of different frequencies,
- 3) it matches attitudinal surveys of noise annoyance better than other noise measurements, and
- 4) it has been adopted as the basic unit of environmental noise by many agencies around the world, including OSHA.

3. NOISE LEVEL MONITORING


3.1 Obtaining Background Noise Levels

To distinguish trucking terminal noise from other ambient noise sources, noise levels must be monitored during a time at which the terminals are NOT in operation. H&H was informed that the only overnight period without terminal operations is Saturday night to Sunday morning. H&H

therefore monitored noise levels from 10 p.m. to 3 a.m. on the evening of September 13, 2014 in order to establish a baseline background noise level for the neighborhood. The monitoring location, immediately south of the fence line at Carillon Lakes, just east of the Enterprise and Division intersection, was necessarily the same for both background measurements and facility operations measurements. This location met the requirements of 35 IAC 910.105(a).

The time of night monitored were also the same for both background measurements and facility operations measurements. This was done in order to determine the trucking facilities' contribution to overall noise levels. This was done by logarithmically subtracting the background noise levels from the noise reading taken during facility operating hours. The justification for this correction is found in 35 IAC 910.106(a)(4).

Without the truck terminals operating, and therefore without the related truck traffic on the roadway, the major contributor to overnight background noise levels at the monitoring location was roadway car and single unit truck traffic. Traffic from the background monitoring periods and from the terminal noise monitoring periods was compared to ensure the volumes were comparable. The car volumes for all three monitoring periods are graphically presented as running one-hour totals below:



3.2 Obtaining Terminal Operations Noise Levels

Noise monitoring is required to be conducted only within certain ambient parameters. Monitoring is not considered valid in conditions of high (greater than 12 mph) winds, temperature extremes (below 14 °F or above 112 °F), or excessive humidity (greater than 90%). Pavement must also be dry. These conditions were met for each of the three monitoring sessions.

H&H attempted to conduct this noise study on an evening in which terminal noise would be at or near its loudest levels. Residents had volunteered to rate the night-time noise levels and send this data to The City. H&H sorted through the available data and determined the consensus "loudest" nights of the week. These became the target night for the study, as The City authorized no more than two nights of operational study, and this information provided the best opportunity for picking a "loud" night. Monitoring was conducted on the evenings of September 11 and October 22.

4. **NOISE MONITORING RESULTS**

The truck terminal noise levels were checked against two sets of regulatory limits determined by the Illinois Pollution Control Board. These two limits are octave band limits and highly-impulsive noise limits. Once isolated from background traffic levels and short-term transient sounds, trucking facility noise levels at specified frequencies was compared with nighttime limits found at 35 IAC 901.102(b) for sound emitting from the trucking facilities' land classification (C) to residential land (classified as A):

Octave Band Center Frequency (Hertz)	Allowable Octave Band Sound Pressure Levels (dB)
31.5	69
63	67
125	62
250	54
500	47
1000	41
2000	36
4000	32
8000	32

Additionally, highly impulsive sound, as defined in 35 IAC 900.101 and found below, was also studied:

Highly Impulsive Sound: either a single pressure peak or a single burst (multiple pressure peaks) for a duration usually less than one second. Examples of highly impulsive sound sources are drop forge hammer and explosive blasting.

The limit for highly impulsive sound levels generated from Class C land and received upon Class A land during nighttime hours, as found in 35 IAC 901.104, is 43 dB(A).

These limits apply to noise levels coming from the facility not including background noise and other

noise sources from outside the facility. In order to properly define terminal noise, non-terminal-generated noise must be extracted from the 18,000 individual seconds that make up each evening's worth of noise monitoring data. The major components of the non-terminal noise was semi-trailer truck noise and automobile noise from Enterprise Drive and Division Street. Traffic noise will not be counted against regulatory noise limits found in 35 IAC 901 based on the exception found in 35 IAC 901.107(f):

Sections 901.102 through 901.106 inclusive do not apply to the operation of any vehicle registered for highway use while such vehicle is being operated within any land used as specified by Section 901.101 in the course of ingress to or egress from a highway.

The truck-related noise levels and over-all, uncorrected noise levels are presented below for informational purposes:

Test Start Date	Total Truck Count for 5-hour Monitoring Period	Noise Level when Trucks are Present L_{eq} , $dB(A)^1$	Over-all, Uncorrected Noise Levels, dB(A) ²
September 11, 2014	78	55.8	50.8
October 22, 2014	82	57.3	54.3

This represents the noise level for the periods when trucks are audible. This includes the approach, idle, pass-by, and departure noise.

This represents the overall noise level measured each night. This includes all background, facility, impulse, transient, and truck noise.

The Federal Highway Administration (FHWA) defines traffic noise-related impacts for residential land uses as a noise level (in terms of hourly Leq) of 67 dB(A). This impact criterion is applied only at exterior residential areas. The FHWA Impact criterion is only used to determine impacts for new roadway projects, which generally include the addition of a travel lane to an existing roadway or the construction of a new roadway. When determining potential impacts stemming from the new roadway projects, the Illinois Department of Transportation (IDOT) analyzes abatement measures to reduce traffic noise at residential receivers when the traffic noise levels from the new roadway project are expected to approach, meet or exceed the FHWA criterion. IDOT defines "approach" as an expected noise level of 66 dB(A) or greater.

Short-term transient background sounds not generated by the trucking facilities (for example a truck gathering contents of a dumpster at the near-by strip mall) must not be included as part of the data set based on 35 IAC 910.107(b)(2)(B):

Data collection must be inhibited whenever a short-term background transient sound occurs,

Data from the terminal for each of the five hours of the study nights was averaged for each of the nine octave bands for which night-time noise limits exist in the Illinois Administrative Code, based on appropriate land use. The background noise levels were then used, as per the methodology found in the regulation, to correct for the terminal noise levels measured. When accounting for background levels, all but 13 data points out of ninety (nine octave band averages for each of five hours on two study nights) fall at or below the background noise level, thereby meeting the regulatory requirements. The remaining 13 data points are less than the regulatory limit. Therefore, the facility does not exceed octave bands noise limits. These results are tabulated below:

Table 1 - Octave Band Results - September 11, 2014

	A. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.			ð	orrected Hourty Facili	ity Leq			
Hour	LZeq_O 31.5Hz	12eq_0 63Hz	LZeq_ O 125Hz	12eq 0.250Hz	1Zeq 0 500Hz	tZeq O 1kHz	LZeg OZKHE	LZeg O 4kHz	LZed O 8kHz
	1 59.0	52.1	61.2	\$25	43.9	45.2			29.5
	2 57.2	0'09	57.0	50.8	45.4	44.2	44.3	25.1	1 2
	3 56.8	59,3	56.4	47.2	41.2	40.3	47.5	31.7	26.2
	4 58.2	60.5	54.6	48.7	39.3	28.5	35.7	776	3 5
	5 58.0	59.4	005	46.9	40.2	30.0	12.0	30.0	15
Allowabi	le 69.0	67.0	0.69	540	40.2	22.5	30.9	30.1	7.57
		-	2000	24.0	0.74	47.0	38.0	32.0	32.0

				Con	rected Hourly Backgr	band Leg			
tout	12eq 0 31.5Hz	1Zeg 0 63Hz	LZeq_O125Hz	LZeq_0 250Hz	LZeq O 500Hz	LZeq O INH2	LZeq O 2kHz	LZeg O 4kHz	12eg Oski
	1 56.2	62.4	609	54.0	46.2	49.0	45.5	36.9	
	2 58,3	62.1	57.0	270	46.5	20.8	47.7	37.4	80
	3 60.1	63,3	56.6	46.7	42.6	45.7	42.4	33.2	24.5
	4 57.4	59.4	52.4	47.7	44.3	45.1	42.5	33.1	24
1	5 54.3	58.1	53.2	45.1	43.6	44.1	40.1	31.4	25.4

				Corrected Hourly F.	acility Leg with Back	ground Noise Remov	ved		
Hour	LZeq_ 0 31_5Hz	LZeq 0 63Hz	LZeq_0 125Hz	LZeq O 250Hz	LZeq O 500Hz	LZeq_O1kHz	LZeq_O 2kH2	LZeq O 4kHz	Zeq O 8kHz
	1 Background 2 Background 3 Background 4 Background 5 55.6	Background Background Background Background	Background Background Background Background S7.7	Background Background Background Background Background	Background Background Background Background	Background Background Background Background Background	Background Background Background Background	Background Background Background Background Background	Background Background Background Background Background
Allowab	0.69 69.0	67.0	62.0	54.0	47.0	41.0	36.0	32.0	32.0

Table 2 - Octave Band Results - October 22, 2014

				10-22-14 - Co	rrected Hourly	Facility Leg			
our	LZeq_0 31.5Hz	LZeq_O 63Hz	LZeq_0 125Hz	LZeq 0 250Hz	LZeq_O 500Hz	LZeq O 1KHz	LZeq O 2KHz	LZeg O 4kHz	LZeg O SKHZ
	1 60.7	62.1	57.8	51.4	47.1	50.8	47.2	37.0	26.9
	2 59.4	63.0	613	51.8	46.8	48.5	44.9	36.3	28.1
	3 60.9	63.8	55.6	46.3	45.8	46.7	43.4	34.2	25.9
	4 61.9	65.2	57.2	46.9	48.3	47.2	43.0	34.3	25.0
	5 60.8	61.8	55,0	48.8	44.0	46.4	43.0	34.5	27.2
Allowat	0.69 ale	67.0	62.0	0,1%	47.0	41.0	36.0	32.0	37.0

				Correcte	d Hourly Backgroun	nd Leg			
OUL	LZeq_031.5Hz	LZeq_O 63Hz	LZeq_0 125Hz	LZeq_0 250Hz	LZeq_0 500Hz	LZeq O 1kHz	LZeq_O 2KHz	LZeq O 4KHz	LZeg O SKHz
	1 56.2	62.4	603	54.0		49.0		36.9	29.0
	2 58.3	62.1	57.0	51.0	46.5	50.8	47.7	37.4	28,3
	3 60.1	63.3	56.6	46.7	42.6	45.7	424	33.2	24.5
	4 57.4	59.4	52.4	47.7	44.3	45.1	42.5	33.1	24.3
	5 54.3	58.1	53.2	45.1	43.6	44.1	40.1	31.4	25.4

			Correcte	cted Hourly Facilit	ed Hourly Facility Leq with Background Noise Removed	ound Noise Remo			
Hour	(Zeq_0 31.5Hz	LZeq_0 63Hz	LZeq_0 125Hz	LZeq_O 250Hz	Zeq_0 500Hz	LZeq_O 1kHz	eq_O 2kHz	LZeq O 4kHz	LZeq O 8KHz
	1 58.9	Background	Background	Background	Background	Background	Background	Background	Background
	2 Background	Background	59.4		Background	Background	Background		Backeround
	3 Background	Background	Background	Background	43.1	Background	Background		Backeround
	4 60.0	63.9	55.5	Background	46.1	Background	Backeround		
	5 59.7	59.3	Background	46,4	Background			31.5	
Allowabi	0'69 3	67.0	62.0	\$3.0	47.0	1		32.0	32.0
Exceedances	0	0	0	0	0	C	0	-	C

Terminal noise also includes "highly impulsive noise," short-duration 'jarring' sounds. The monitored data from the evenings of September 11th and October 22nd, in conjunction with H&H field notes, was analyzed for highly impulsive noise events. The noise limit for the land uses in question is 43 dB(A), as a Leq value for a 60 minute period. The facility did not exceed this noise level during any continuous one-hour period.

During the facility monitoring session, four main types of highly-impulsive noise emanated from the facility. The majority of these noise events were from loading operations, as forklifts bumped across loading gates, and also metal 'clanging' and 'crashing' noises. The metallic noises were exclusive to the October 22^{nd} monitoring period. To a lesser extent beeping and spotter truck noises added to highly-impulsive noise events. A running 60-minute average of highly-impulsive noise levels indicated that the Leq from these events never exceeded 29 dB(A) on the evening of September 11^{th} and never exceeded 40 dB(A) on the evening of October 22^{nd} .

The loudest highly-impulse noise event from the September 11th monitoring session – loudest by far, about four times louder than the next loudest highly-impulsive noise event during the entire five-hour study – would have to be repeated 27 times in one hour before the facility was in violation of the highly-impulsive noise regulatory level.


The loudest highly-impulse noise event from the October 22nd monitoring session would have to be repeated 30 times in one hour before the facility was in violation of the highly-impulsive noise regulatory level.

Based on the worse of the two monitoring nights, the average loading bump noise could be repeated 178 times in an hour before the facility exceeded regulatory levels. There were 163 distinguishable loading bump noises during the ten hours studied, and the most in any consecutive 60-minute period was 60.

The loudest spotter truck impulse noise observed during the September 11th monitoring session could be repeated 646 times in an hour before exceeding regulatory standards. The average spotter truck impulse noise observed during the monitoring period could be repeated 2,429 times in an hour before exceeding regulatory standards. There were 18 distinguishable spotter truck noises during the ten hours studied. Spotter truck-based impulse noise was less discernible on the evening of October 22nd.

Based on the worse of the two monitoring nights, the loudest beeping impulse noise could be repeated 85 times in an hour before exceeding regulatory standards. The average beeping impulse noise observed during the monitoring period could be repeated 286 times in an hour before exceeding regulatory standards. There were 48 distinguishable beeping noises during the ten hours studied.

The October 22nd monitoring session produced more impulse noise events, and contained numerous metal-on-metal "clangs" not heard in the September 11th session. It is likely this increase in impulse noises was a major component leading to the increase in overall facility noise compared to September 11th, as seen in the octave band results from October 22nd. The loudest metallic noise could occur 30 times in an hour before exceeding regulatory standards. The average metallic impulse noise observed during the monitoring period could be repeated 201 times in an hour before exceeding regulatory standards. There were 117 distinguishable metallic impulse noises during the October 22nd monitoring period, and the most metallic noise events in any one-hour period was 79.





ASTM E 90 SOUND TRANSMISSION LOSS TEST REPORT

Rendered to:

SIMTEKTM FENCE

SERIES/MODEL: Simtek 8-Foot Wall

TYPE: Privacy Fence

	Summary of Test Results		
Data File No.	Description (Nominal Dimensions)	STC	OITC
89608.01	Simtek 8-foot wall, simulated rock wall, 8' by 8' privacy fence section	26	20

Reference should be made to Architectural Testing, Inc. Report No. 89608.01-113-11 for complete test specimen description. The complete test results are listed in Appendix B.

130 Derry Court York, PA 17406-8405 phone: 717-764-7700 fax: 717-764-4129

www.archtest.com



ACOUSTICAL PERFORMANCE TEST REPORT

Rendered to:

SIMTEKTM FENCE 1330 West 400 North Orem, Utah 84057

Report No: 89608.01-113-11

Test Date:

03/03/09

Report Date: Expiration Date:

03/10/09 03/03/13

Test Sample Identification:

Series/Model: Simtek 8-Foot Wall

Type: Privacy Fence

Overall Size: 96" by 96"

Material: Polyethylene

Pattern: Simulated Rock Wall

Project Scope: Architectural Testing, Inc. was contracted by SimTekTM Fence to conduct a sound transmission loss test on a Series/Model Simtek 8-foot wall, privacy fence. A summary of the results is listed in the Test Results section and the complete test data is included as Appendix B of this report. The sample was provided by the client.

Test Methods: The acoustical tests were conducted in accordance with the following:

ASTM E 90-04, Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions.

ASTM E 413-04, Classification for Rating Sound Insulation.

ASTM E 1332-90 (Re-approved 2003), Standard Classification for Determination of Outdoor-Indoor Transmission Class.

ASTM E 2235-04, Standard Test Method for Determination of Decay Rates for Use in Sound Insulation Test Methods.

www.archtest.com



Test Equipment: The equipment used to conduct these tests meets the requirements of ASTM E 90. The microphones were calibrated before conducting sound transmission loss tests. The test equipment and test chamber descriptions are listed in Appendix A.

Sample Installation: Sound transmission loss tests were initially performed on a filler wall that was designed to test 96" by 96" specimens. The filler wall achieved an STC rating of 68.

The 96" by 96" plug was removed from the filler wall assembly. The privacy fence was placed on a foam isolation pad in the test opening. Duct seal was used to seal the perimeter of the privacy fence to the test opening on both sides. The interior side of the privacy fence, when installed, was approximately 1/4" from being flush with the receiving room side of the filler wall. A stethoscope was used to check for any abnormal air leaks around the test specimen prior to testing.

Test Procedure: The sound transmission loss test consisted of the following measurements: One background noise sound pressure level and five sound absorption measurements were conducted at each of the five microphone positions. Two sound pressure level measurements were made simultaneously in both rooms, at each of the five microphone positions. The air temperature and relative humidity conditions were monitored and recorded during the background, absorption, source, and receive room measurements.

Sample Descriptions: A polyethylene fence section measuring 96" by 96" was tested. SimTekTM Fence provided all test materials, and the test specimen did not arrive assembled. Two horizontal sections were installed between two end posts.

Each horizontal section was 89-7/8" wide by 48" high and approximately 2" thick. Both horizontal sections were hollow-molded polyethylene with an 18 gauge thick, 1-1/2" by 1-1/2" hollow steel stiffener in the top and bottom rails.

The two polyethylene end posts were a nominal 5" by 5" by 96", C-channel shape. Each post was filled with recycled polyethylene and had a 14 gauge, 2" by 3" hollow steel reinforcement channel. The vertical sections were stacked and inserted into both C-channel shaped end posts.

Comments: The weight of the sample was 188 lbs. The client did not supply drawings on the Series/Model Simtek 8-foot wall, privacy fence. The test specimen was returned per the client's request. Photographs of the test specimen are included in Appendix C.



Test Results: The STC (Sound Transmission Class) rating was calculated in accordance with ASTM E 413. The OITC (Outdoor-Indoor Transmission Class) was calculated in accordance with ASTM E 1332. A summary of the sound transmission loss test results on the Series/Model Simtek 8-foot wall, privacy fence is listed below.

	Summary of Test Results		
Data File No.	Description (Nominal Dimensions)	STC	OITC
89608.01	Simtek 8-foot wall, simulated rock wall, 8' by 8' privacy fence section	26	20

The complete test results are listed in Appendix B. Flanking limit tests and reference specimen tests are available upon request.

Detailed drawings, data sheets, representative samples of test specimens, a copy of this report, or other pertinent project documentation will be retained by Architectural Testing for a period of four years from the original test date. At the end of this retention period, such materials shall be discarded without notice and the service life of this report will expire. Results obtained are tested values and were secured by using the designated test methods. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimen tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing.

For ARCHITECTURAL TESTING, INC:

Kurt A. Golden

Senior Technician - Acoustical Testing

Told D. Kistn
Digitally Signed by: Todd D. Klater

Todd D. Kister

Laboratory Supervisor - Acoustical Testing

KAG:jmcs


Attachments (pages): This report is complete only when all attachments listed are included.

Appendix-A: Equipment description (1) Appendix-B: Complete test results (2)

Appendix-C: Photographs (1)



Architectural Testing, Inc., is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.





Revision Log

<u>Rev. #</u>	<u>Date</u>	Page(s)	Revision(s)
0	03/10/09	N/A	Original Report Issue



Appendix A

Instrumentation:

Instrument	Manufacturer	Model	Description	ATI Number
Analyzer	Agilent Technologies	35670A	Dynamic signal analyzer	Y002929
Receive Room Microphone	G.R.A.S.	40AR	1/2", pressure type, condenser microphone	Y003246
Source Room Microphone	G.R.A.S.	40AR	1/2", pressure type, condenser microphone	Y003245
Receive Room Preamp	G.R.A.S.	26AK	1/2" preamplifier	Y003249
Source Room Preamp	G.R.A.S.	26AK	1/2" preamplifier	Y003248
Microphone Calibrator	Bruel & Kjaer	4228	Pistonphone calibrator	Y002816
Noise Source	Delta Electronics	SNG-1	Two, uncorrelated "Pink" noise signals	Y002181
Equalizer	Rane	RPE228	Programmable EQ	Y002180
Power Amplifiers	Renkus-Heinz	P2000	Two Amplifiers	Y002179 Y001779
Receive Room Loudspeakers	Renkus-Heinz	Trap Jr/9"	Two Loudspeakers	Y001784 Y001785
Source Room Loudspeakers	Renkus-Heinz	Trap Jr/9"	Two Loudspeakers	Y002649 Y002650

Test Chamber:

	Volume	Description
	2 2	Rotating vane and stationary diffusers.
Receiving Room	8291.3 ft ³ (234 m ³)	Temperature and humidity controlled.
		Isolation pads under the floor.
Carrage Dance	7296.3 ft ³ (206.6 m ³)	Stationary diffusers only.
Source Room	/290.3 It (200.6 m)	Temperature and humidity controlled.

	Maximum Size	Description
TI Tost Opening	14 ft wide by 10 ft high	Vibration break between source and receive
The Test Opening	14 it wide by 10 it high	rooms.



Appendix B

Complete Test Results



SOUND TRANSMISSION LOSS

ASTM E 90

Architectural Testing

ATI No. 89608.01 Date 03/03/09

Client SimTek™ Fence

Specimen Series/Model: Simtek 8-foot wall, simulated rock wall, 8' by 8' privacy fence section

Specimen Area64.00 Sq FtFiller Area76.00 Sq FtOperatorKurt Golden

	Bkgrd	Absorp	Source	Receive	Filler	Specimen	
Temp F	71.2	70.9	71.7	71.1	71.8	71.2	
RH %	44.1	44.6	45.1	44.3	42.9	44.5	

	Bkgrd	Absorp	Source	Receive	Filler	Specimen	95%	No. of	Trans
Freq	SPL	(Sabines	SPL	SPL	TL	TL	Conf	Defici-	Coef
(Hz)	(dB)	/Sq Ft)	(dB)	(dB)	(dB)	(dB)	Limit	encies	Diff
80	40.3	55.5	83.9	70.8	47.1	14	2.04	0	32.6
100	39.3	50.6	87.9	74.3	47.9	15	2.27	0	32.5
125	41.5	51.7	91.8	77.4	55.1	15	2.01	0	39.0
160	39.3	56.3	94.5	80.8	55.3	14	1.22	0	40.4
200	38.3	57.5	98.6	84.5	54.5	15	0.60	1 1	39.1
250	36.8	63.6	99.1	85.0	57.0	14	0.96	5	42.1
315	36.1	69.1	98.0	81.1	57.5	17	0.78	5	40.1
400	34.4	74.6	97.6	78.7	62.5	18	0.81	7	43.6
500	34.0	69.5	99.1	77.2	66.0	22	0.36	4	43.7
630	32.2	65.0	101.8	76.3	67.0	25	0.45	2	40.8
800	35.2	63.5	101.2	72.0	70.6	29	0.38	0	40.6
1000	32.7	65.5	100.9	69.2	74.0	32	0.26	0	41.7
1250	32.4	72.7	104.0	71.3	75.3	32	0.53	0	42.4
1600	30.1	77.1	110.0	78.3	74.1	31	0.47	0	42.5
2000	21.2	83.3	105.3	74.0	72.3	30	0.22	0	41.3
2500	10.9	98.8	103.7	72.6	74.6	29	0.22	1	44.7
3150	11.6	114.4	104.3	73.2	80.2	29	0.44	1	50.9
4000	9.5	137.9	103.2	69.8	83.2	30	0.33	0	52.4
5000	7.8	176.6	101.4	64.8	86.2	32	0.46	0	53.3

STC Rating = 26 (Sound Transmission Class)

Deficiencies = 26 (Number of deficiencies versus contour curve)

OITC Rating = 20 (Outdoor/Indoor Transmission Class)

Notes:

- 1) The acoustical chambers are qualified for measurements down to 80 hertz. Data reported below 80 hertz is for reference only.
- 2) Transmission loss coefficient differences less than 6 indicate the lower limit of the transmission loss for this specimen. These cells are highlighted red.
- 3) Transmission loss coefficient differences between 6 and 15 indicate there has been a filler wall correction applied. These cells are highlighted green.
- 4) Receive Room levels less than 5dB above the Background levels are highlighted in yellow-



Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.




Architectural Testing

ATI No. 89608.01 **Date** 03/03/09

Client SimTek™ Fence

Specimen Series/Model: Simtek 8-foot wall, simulated rock wall, 8' by 8' privacy fence section

Specimen Area64.00 Sq FtFiller Area76.00 Sq FtOperatorKurt Golden





Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods lis under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.



Appendix C


Photographs



Receive Room View of Installed Specimen



Source Room View of Installed Specimen



Landscape Material Worksheet

Project Number: 2015.226

Petitioner: Old Dominion Freight Lines, Inc

Proposed Canopy Trees

Family	Family Genus Species Cor		Common Name	Size
Aceraceae	Aceraceae Acer x freemanii 'Autumn Fantasy' Au		Autumn Fantasy Maple	2 1/2", 4" along Meridian & Sunrise Rd.
Aceraceae	Acer	myabei 'Morton'	State Street Miyabe Maple	2 1/2", 4" along Meridian & Sunrise Rd.
Aceraceae	Acer	saccharum	Sugar Maple	2 1/2" Cal.
Rosaceae	Amelanchier	grandiflora	Apple Serviceberry	2 1/2" Cal.
Ulmaceae	Celtis	occidentalis	Common Hackberry	2 1/2" Cal.
Fabaceae	Gymnocladus	dioicus	Kentucky Coffee Tree	2 1/2" Cal.
Fabaceae	Gymnocladus	dioicus 'Espresso'	Espresso Kentucky Coffee Tree	2 1/2", 4" along Meridian & Sunrise Rd.
Hamameldaceae	Liquidambar	styraciflua 'Moraine'	Moraine Sweetgum	2 1/2", 4" along Meridian & Sunrise Rd.
Fagaceae	Quercus	bicolor	5wamp White Oak	2 1/2", 4" along Meridian & Sunrise Rd.
Fagaceae	Quercus	macrocarpa	Bur Oak	2 1/2", 4" along Meridian & Sunrise Rd.
Fagaceae	Quercus	muehlenbergii	Chinquapin Oak	2 1/2" Cal.
Taxodiaceae	Taxodium	distichum	Bald Cypress	2 1/2" Cal.
Tiliaceae	Tilia	americana 'McKSentry'	Sentry American Linden	2 1/2" Cal.
Tiliaceae	Tilia	tomentosa 'Sterling'	Sterling Silver Linden	2 1/2", 4" along Meridian & Sunrise Rd.
Oleaceae	Syringa	reticulata 'Ivory Silk'	Ivory Silk Japanese Tree Lilac	2 1/2" Cal.
Ulmaceae	Ulmus	'Morton Glossy'	Triumph Elm	2 1/2", 4" along Meridian & Sunrise Rd.
Ulmaceae	Ulmus	carpinifolia 'Regal'	Regal Smoothleaf Elm	2 1/2", 4" along Meridian & Sunrise Rd.

Proposed Evergreen Trees

Family	Genus	Species	Common Name	Size
Pinaceae	Abies	concolor	White Fir	6' Ht, 12' Ht. along Meridian & Sunrise Rd.
Pinaceae	Picea	abies	Norway Spruce	6' Ht, 12' Ht. along Meridian & Sunrise Rd.
Pinaceae	Picea	glauca 'Densata'	Black Hills Spruce	6' Ht, 12' Ht. along Meridian & Sunrise Rd.
Pinaceae	Picea	pungens	Green Colorado Spruce	6' Ht, 12' Ht. along Meridian & Sunrise Rd.
Pinaceae	Picea	pungens 'Glauca'	Colorado Blue Spruce	6' Ht, 12' Ht. along Meridian & Sunrise Rd.
Pinaceae	Pinus	nigra	Austrian Pine	6' Ht

Proposed Understory Trees

Family	Genus	Species	Common Name	Size
Cornaceae	Cornus	mas	Corneliancherry Dogwood	8' Ht
Rosaceae	Crataegus	virdis 'Winter King'	Winter King Hawthorne	8' Ht
Rosaceae	Malus	'Purple Prince'	Purple Prince Crabapple	8' Ht
Rosaceae	Malus	'Snowdrift'	Snowdrift Crabapple	8' Ht
Tiliaceae	Tilia	americana 'McKSentry'	Sentry American Linden	10' Ht

Proposed Deciduous Shrubs

Family	Genus	Species	Common Name	Size
Oleaceae	Syringa	patula 'Miss Kim'	Miss Kim Lilac	24" Tall
Caprifoliaceae	Viburnum	dentatum 'Morton'	Northern Burgundy Arrowwood Viburnum	36" Tall
Caprifoliaceae	Viburnum	lantana 'Mohican'	Mohican Viburnum	36" Tall
Caprifoliaceae	Viburnum	trilobum 'Hah's'	Hah's Cranberrybush Viburnum	36" Tall

Proposed Evergreen Shrubs

Family	Genus	Species	Common Name	Size
Cupressaceae	Juniperus	chinensis 'Sea Green'	Sea Green Juniper	24" Wide
Taxaceae	Taxus	x media 'Densiformis'	Dense Yew	24" Wide



Landscape Plan Unit 4, Lot 402

BUTTERFIELD CENTER FOR BUSINESS & INDUSTRY

Aurora, Illinois

December 1, 2015

CONSULTANTS:



LANDSCAPE ARCHITECT:

GARY R. WEBER ASSOCIATES, INC 212 SOUTH MAIN STREET WHEATON, ILLINOIS 60187



CIVIL ENGINEER

MANHARD CONSULTING, LTD. 700 SPRINGER DRIVE LOMBARD, IL 60148




LOCATION MAP SCALE: 1"=1000'




INDEX OF SHEETS

SHEET NO.	DESCRIPTION
0	COVER SHEET
1	OVERALL LANDSCAPE PLAN
2	LANDSCAPE PLAN
3	LANDSCAPE PLAN
4	LANDSCAPE SPECIFICATIONS



SYMBOL LEGEND



8' SIMTEK FENCE

NATIVE SEED LEGEND

Key	Description
	EMERGENT SEED # PLUGS
	WET MEADOW SEED MIX
	LOW PROFILE PRAIRIE SEED MIX

PLANTING MATERIALS TABLE LANDSCAPE PLAN



Landscape Data Table: CTEs Provided										
	CTE Value	Count Provided	Total CTEs Provided							
Canopy Trees	1	211	211							
Evergreen Trees	3	165	55							
Understory Trees	3	30	10							
Deciduous Shrubs	20	176	9							
Evergreen Shrubs	20	90	5							
Existing Canopy Trees	1	3	3							
Upsized Material	1	18	18							
	Total:	693	310							

GENERAL NOTES

- 1. Contractor shall verify underground utility lines and is responsible for any damage.
- 2. Contractor shall verify all existing conditions in the field prior to construction and shall notify landscape architect of any
- 3. Material quantities shown are for contractors convenience only. The Contractor must verify all material and supply sufficient materials to complete the job per plan.
- 4. The landscape architect reserves the right to inspect trees and shrubs either at place of growth or at site before planting, for compliance with requirements of variety, size and quality.
- 5. Work shall conform to American Standard for Nursery Stock, State of Illinois Horticultural Standards, and Local Municipal requirements.
- 6. Contractor shall secure and pay for all permits, fees, and inspections necessary for the proper execution of this work and comply with all codes applicable to this work.
- 7. See General Conditions and Specifications for landscape work for additional requirements.



GARY R. WEBER ASSOCIATES, INC. ECOLOGICAL CONSULTING LANDSCAPE ARCHITECTURE 212 SOUTH MAIN STREET WHEATON, ILLINOIS 60187

> **OLD DOMINION** FREIGHT LINE, INC 500 OLD DOMINION WAY

PHONE: 630-668-7197

THOMASVILLE, NC 27360 MANHARD CONSULTING

700 SPRINGER DRIVE



6.03.16

REVISIONS


CHECKED

DATE 12.01.15 PROJECT NO. OD1501 **DRAWN** MGM/TRC/GFB

5.23.16

SHEET NO.





PLAN	T LIST	MATCH	LINE - SEE SHEET	T 3					MATCH LINE - SEE SHEET	3						
Key Qty	Botanical/Common Name	Size	Remarks	Key Qty	Botanical/Common Name	Size	Remarks	Key Qty	Botanical/Common Name	Size	Remarks	Key	Qty	Botanical/Common Name	Size	Remarks
	SHADE TREES				SHADE TREES CONT.				ORNAMENTAL TREES (CONT.)					DECIDUOUS SHRUBS		
AF 3	Acer x freemanii 'Autumn Fantasy' AUTUMN FANTASY MAPLE	2 1/2" Cal.		QC 10	Quercus muehlenbergii CHINKAPIN OAK	2 1/2 ¹¹ Cal.		MS 5	Malus 'Snowdrift' SNOWDRIFT CRABAPPLE	8' Ht.	Clump form	SP	48	Syringa patula 'Miss Kim' MISS KIM LILAC	24" Tall	4' O.C.
AF4 12	Acer x freemanii 'Autumn Fantasy' AUTUMN FANTASY MAPLE	4" Cal.		QM 9	Quercus macrocarpa BUR OAK	2 1/2" Cal.		TA10 10	Tilia americana 'McKSentry' SENTRY AMERICAN LINDEN	10' Ht.	Clump form	VD	39	Viburnum dentatum 'Morton' NORTHERN BURGUNDY ARROWWOOD VIBU	36" Tall	5' O.C.
AM 3	Acer miyabei 'Morton' STATE STREET MIYABE MAPLE	2 1/2" Cal.		QM4 2	Quercus macrocarpa BUR OAK	4" Cal.			EVERGREEN TREES			VL	25	Viburnum lantana 'Mohican' MOHICAN VIBURNUM	36" Tall	5' O.C.
AM4 12	Acer miyabei 'Morton' STATE STREET MIYABE MAPLE	4" Cal.		SR 6	Syringa reticulata 'Ivory Silk' IVORY SILK JAPANESE TREE LILAC	12' Ht.	Tree form	AC 11	Abies concolor WHITE FIR	6' Ht.		VT	64	Viburnum trilobum 'Hah's' HAH'S CRANBERRYBUSH VIBURNUM	36" Tall	5' O.C.
AS 10	Acer saccharum SUGAR MAPLE	2 1/2" Cal.		TD 16	Taxodium distichum BALD CYPRESS	2 1/2" Cal.		AC12 17	Abies concolor WHITE FIR	12' Ht.				EVERGREEN SHRUBS		
AS4 4	Acer saccharum SUGAR MAPLE	4" Cal.		TA 11	Tilia americana 'McKSentry' SENTRY LINDEN	2 1/2" Cal.		PA 14	Picea abies NORWAY SPRUCE	6' Ht.		JS	68	Juniperus chinensis 'Sea Green' SEA GREEN JUNIPER	24" Wide	5' O.C.
AG 6	Amelanchier x grandiflora APPLE SERVICEBERRY	2 1/2" Cal.	Tree form	TA4 3	Tilia americana 'McKSentry' SENTRY LINDEN	2 1/2" Cal.		PA12 15	Picea abies	12' Ht.		TM	22	Taxus x media 'Densiformis' DENSE YEW	24" Wide	4' O.C.
AG12 4	Amelanchier x grandiflora APPLE SERVICEBERRY	12' Ht.	Tree form	TT 9	Tilia tomentosa 'Sterling' STERLING SILVER LINDEN	2 1/2" Cal.		PG 38	NORWAY SPRUCE Picea glauca 'Densata'	6' Ht.					10050	
CO 9	Celtis occidentalis COMMON HACKBERRY	2 1/2" Cal.		TT4 6	Tilia tomentosa 'Sterling' STERLING SILVER LINDEN	4" Cal.			BLACK HILLS SPRUCE					PERENNIALS AND ORNAMENTAL GR		
CO4 3	Celtis occidentalis COMMON HACKBERRY	4" Cal.		UM 8	Ulmus 'Morton Glossy' TRIUMPH ELM	2 1/2 ¹¹ Cal.		PG12 15	Picea glauca 'Densata' BLACK HILLS SPRUCE	12' Ht.		CK	105	Calamagrostis x acutiflora 'Karl Foerster' FEATHER REED GRASS	#2	36" O.C.
GD 8	Gymnocladus dioicus KENTUCKY COFFEE TREE	2 1/2" Cal.		UM4 5	Ulmus 'Morton Glossy' TRIUMPH ELM	4" Cal.		PP 23	Picea pungens GREEN COLORADO SPRUCE	6' Ht.		HP	172	Hemerocallis 'Pardon Me' PARDON ME DAYLILY	#2	24" O.C.
GE 10	Gymnocladus dioicus 'Espresso' ESPRESSO KENTUCKY COFFEETREE	2 1/2" Cal.		UR 9	Ulmus carpinifolia 'Regal' REGAL SMOOTHLEAF ELM	2 1/2 ¹¹ Cal.		PP12 7	Picea pungens GREEN COLORADO SPRUCE	12' Ht.		SH	10	Sporobolus heterolepis PRAIRIE DROPSEED	#2	24" O.C.
GE4 2	Gymnocladus dioicus 'Espresso' ESPRESSO KENTUCKY COFFEETREE	4" Cal.		UR4 5	Ulmus carpinifolia 'Regal'	4" Cal.		PI 14	Picea pungens 'Glauca' COLORADO BLUE SPRUCE	6' Ht.				MISCELLANEOUS MATERIALS		
LS 5	Liquidambar styraciflua 'Moraine' MORAINE SWEETGUM	2 1/2" Cal.			ORNAMENTAL TREES			PII2 10	Picea pungens 'Glauca' COLORADO BLUE SPRUCE	12' Ht.			3. <i>00</i>	Turf Seed \$ Erosion Control Blanket Emergent Seed Mix \$ Plugs	AC. AC.	
LS4 2	Liquidambar styraciflua 'Moraine'	4'' Cal.		CM 3		0 1 1	Clumpus Course	PN 8	Pinus nigra	6' Ht.				Wet Meadow Seed Mix & Erosion Control Blank		
	MORAINE SWEETGUM	0.1/0 6-1		CM 3	Cornus mas CORNELIANCHERRY DOGWOOD	8' Ht.	Clump form		AUSTRIÁN PINE				1.75	Low Profile Prairie Seed Mix & Erosion Control Blanket	AC.	
QB 9	Quercus bicolor SWAMP WHITE OAK	2 1/2" Cal.		CV 5	Crataegus viridis 'Winter King' WINTER KING HAWTHORNE	8' Ht.	Clump form						0.86	Low Mow Fescue Erosion Control Blanket Berm	AC.	ណ្តា
QB4 11	Quercus bicolor SWAMP WHITE OAK	4" Cal.		MC 7									175		C.Y.	811
	SMALIF MHILE DAN			MC 7	Malus 'Purple Prince' PURPLE PRINCE CRABAPPLE	8' Ht.	Clump form							8' SIMTEK Fence	L.F.	Know what's belo Call before y



GARY R. WEBER
ASSOCIATES, INC.
LAND PLANNING
ECOLOGICAL CONSULTING
LANDSCAPE ARCHITECTURE
212 SOUTH MAIN STREET
WHEATON, ILLINOIS 60187
PHONE: 630-668-7197

OWNER/APPLICANT:
OLD DOMINION
FREIGHT LINE, INC
500 OLD DOMINION WAY
THOMASVILLE, NC 27360

CIVIL ENGINEER:

MANHARD CONSULTING

700 SPRINGER DRIVE



& INDUSTRY

LANDSCAPE PLAN

BUTTERFIELD CENTER FOR BUSINES


UNIT 4 - LOT 402
AURORA, ILLINOIS

JEFFREY C. TORRENS
157-001432
EXP
4NDSCAPE

	6.03.16
	5.23.16
EVISIONS	

DATE 12.01.15
PROJECT NO. OD1501
DRAWN MGM/TRC/GFB
CHECKED JCT
SHEET NO.

2 **OF** 4





GARY R. WEBER ASSOCIATES, INC LAND PLANNING ECOLOGICAL CONSULTING LANDSCAPE ARCHITECTURE 212 SOUTH MAIN STREET WHEATON, ILLINOIS 60187

OWNER/APPLICANT: **OLD DOMINION** FREIGHT LINE, INC 500 OLD DOMINION WAY THOMASVILLE, NC 27360

CIVIL ENGINEER: MANHARD CONSULTING 700 SPRINGER DRIVE LOMBARD, ILLINOIS 60148



N

6.03.16

12.01.15

5.23.16

PROJECT NO. **DRAWN** MGM/TRC/GFB CHECKED SHEET NO.

The work shall consist of furnishing, transporting and installing all seeds, plants and other materials required

- The establishment of trees, shrubs, perennial, annual and lawn areas as shown on Landscape Plan; . The provision of post-planting management as specified herein;
 - Any remedial operations necessary in conformance with the plans as specified in this document; The design, furnishing and installation of a complete underground sprinkler system; and . Permits which may be required.
- 1.2 QUALITY ASSURANCE
- A. Work shall conform to State of Illinois Horticultural Standards and local municipal requirements.

Comply with governing regulations applicable to landscape materials.

- 1. Ship landscape materials with certificates of inspection as required by governmental authorities.
- 2. Do not make substitutions. If specified landscape material is not obtainable, submit to Landscape Architect proof of non-availability and proposal for use of eapivalent material.
- 3. Analysis and Standards: Package standard products with manufacturer's certified analysis
- 1.3 SUBMITTALS
- A. Planting Schedule
- Submit three (3) copies of the proposed planting schedule showing dates for each type of planting
- B. Maintenance Instruction Landscape Work
- Submit two (2) copies of typewritten instructions recommending procedures to be established by the Owner for the maintenance of landscape work for one full year. Submit prior to expiration of required maintenance periods
- Instructions shall include: watering, fertilizing, spraying, mulching and pruning for plant material and trimming groundcover. Instructions for watering, fertilizing and mowing grass areas shall be provided ten (10) days prior to request for inspection for final acceptance. Landscape Architect shall receive copies of all instructions when issued.
- C. Submit two (2) copies of soil test of existing topsoil with recommendations for soil additive requirement to Landscape Architect for review and written approval.
- D. Submit two (2) samples of shredded hardwood bark mulch, erosion control blankets, and all other products and materials as specified on plans to Landscape Architect for review and written approval
- E. Nursery packing lists indicating the species and quantities of material installed must be provided to the Owner and/or City upon request.

1.4 JOB CONDITIONS

- A. Examine and evaluate grades, soils and water levels. Observe the conditions under which work is to be performed and notify Landscape Architect of unsatisfactory conditions. Do not proceed with the work until unsatisfactory conditions have been corrected in an acceptable manner.
- B. Utilities: Review underground utility location maps and plans; notify local utility location service; demonstrate an awareness of utility locations; and certify acceptance of liability for the protection of utilities during course of work. Contractor shall be responsible for any damage to utilities or
- C. Excavation: When conditions detrimental to plant growth are encountered such as rubble fill, adverse drainage conditions or obstructions, notify Landscape Architect before planting.

1.5 GUARANTEES

- A. Guarantee seeded and sodded areas through the specified maintenance period and until final acceptance. B. Guarantee trees, shrubs, groundcover and perennials for a period of one year after date of acceptance against defects including death and unsatisfactory growth, except for defects resulting from neglect by Owner, abuse or damage by others or unusual phenomena or incidents which are beyond Landscape
- C. Native Planting Area Performance Criteria

Installer's control.

- 1st Full Growing Season: 90% of cover crop shall be established. There shall be no bare areas greater than two (2) square feet in seeded areas. At least 25% of vegetation coverage shall be native, non-invasive species. At least 50% of the emergent species, if planted as plugs shall be alive and
- 2nd Full Growing Season: All areas with the exception of emergent zones shall exhibit full vegetative cover. At least 50% of the vegetation coverage shall be native, non-invasive species
- 3rd Full Growing Season: At least 75% of vegetation coverage shall be native, non-invasive species, Non-native species shall constitute no more than 25% relative aerial coverage of the planted area. Tyoha species (Cattail) can make up to 50% of the emergent area.

LANDSCAPE WORK PART 2 - PLANT MATERIALS

2.1 LAWN SOD

Provide strongly rooted sod, not less than two (2) years old and free of weeds and undesirable native grasses. Provide only sod capable of growth and development when planted (viable, not dormant) and in strips not more than 18" wide x 4' long. Provide sod composed of a 5-way blend of Kentucky Bluegrass such as: Midnight, Allure, Viva, Washington, Liberty

2.2 LAWN SEED MIXTURE

Grass Seed: Provide fresh, clean, new crop seed complying with the tolerance for purity and germination established by the Official Seed Analysts of North America. Provide seed of the grass species, proportions and maximum percentage of weed seed, as specified.

- A. Lawn Seed Mixture 5 1bs./1,000 sq. ft 50 % Kentucky Bluegrass 98/85 Cutter Perennial Ryegrass Spartan Hard Fescue
- Edge Perennial Ryegrass Express Perennial Ryegrass 5%Pennlawn Creeping Red Fescue
- B. Temporary Lawn Seed Mixture 5 lbs./1,000 sq.ft. 40% Kentucky Bluegrass 98/85
- 40% Perennial Ryegrass 20% Annual Ryegrass
- C. Low Mow Fescue Seed Mix Berm <u>Common Name</u> Discovery Hard Fescue 75,000 Tiffany Chewings Fescue 75.000 Florentine Creeping Red Fescue 75.000 Bighorn Sheeps Fescue 75.000

Total: 2.3 NATIVE PLANTING MIXTURES

Provide fresh, clean, new crop of the species and proportions as specified. Native seed and live plant material shall be obtained from a reputable supplier (approved by Landscape Architect) that has collected from sources east of the Mississippi River within the same EPA Level III Ecoregion as the project site (Central Corn Belt Plains). Any material sourced from outside this ecoregion must be approved by the Landscape Architect prior to installation.

300,000

For each species, the amount of seed indicated on the specifications shall mean the total amount of pure live seed (PLS) per acre. Seed tags and PLS testing information shall be provided to the Landscape Architect prior to seeding.

It is the sole responsibility of the Native Landscape Contractor to provide approved seed that meets industry-standard PLS requirements.

A. <u>Temporary Cover Crop</u>:

Total:

Cover crops shall be installed in all planting areas containing dry mesic, mesic, and wet mesic soils to, stabilize soils, and combat weed pressure during the germination and establishment of the native seeding

5434

8.125

For spring plantings use Seed Oats at the specified rate below:

Avena sativa	Seed Oats	40.0 lbs.	
For fall or dormant planting	s, use Regreen at the specif	ied rates below	:
Botanical Name	Common Name	ibs /AC	
Triticum aestivum	Regreen	50.0 lbs	
B. Emergent Plantings - Sh	noreline edge and Planting she	elf 4" deep - 1	2" deep
Botanical Name	Common Name	ibs /AC	Plugs/AC
Acorus calomus	Sweet Flag	0.500	494
Alisma subcordatum	Water Plantain	1.250	
Eleocharis obtusa	Blunt Spike Rush	0.375	
Eleocharis palustris	Marsh Spike Rush	0.375	
Glyceria grandis	Reed Manna Grass	0.375	
Hibiscus laevis	Rose Mallow	0.250	
Iris virginica shrevei	Blue Flag	0.500	494
Juncus effusus	Common Rush	0.500	
Juncus ettusus		1.250	494
Leersia Oryzoides	Rice Cut Grass	1,200	
	Rice Cut Grass Pickerelweed	0.250	494
Leersia Oryzoides	, ,		494 494
Leersia Oryzoides Pontederia Cordata	Pickerelweed	0.250	
Leersia Oryzoides Pontederia Cordata Sagittaria latifolia	Pickerelweed Common Arrowhead	0.250 1.250	494
Leersia Oryzoides Pontederia Cordata Sagittaria latifolia Scirpus acutus	Pickerelweed Common Arrowhead Hardstem Bulrush	0.250 1.250 0.250	494

Note: If emergent zone is permanently flooded seeding will be impossible and live plugs shall be installed at the specified rate. Plugs are specified at a standard 38 cell flat and shall measure 2.25" x 5" with a volume of 11.30 inches. Substitution of plug size must be approved by the Landscape Architect prior to

C. Wet Meadow Seed Mixture - Lower slopes of basin

Botanical Name	Common Name	1bs /4
Grasses and Sedges		
Carex bebbii	Bebbs Oval Sedge	0.250
Carex bicknellii	Bicknells Sedge	0.250
Carex brevior	Plains Oval Sedge	0.250
Carex cristatella	Crested Oval Sedge	0.150
Carex molesta	Field Oval Sedge	0.250
Carex normalis	Spreading Oval Sedge	0.250
Carex scorparia	Pointed Broom Sedge	0.190
Carex stipata	Common Fox Sedge	0.250
Carex vulpinoidea	Brown Fox Sedge	0.250
Elymus virginicus	Virginia Wild Rye	3.000
Glyceria striata	Fowl manna grass	0.130
Juncus dudleyi	Dudleys Rush	0.003
Juncus torreyi	Torreys Rush	0.005
Panicum virgatum	Switch Grass	1.000
Scirpus atrovirens	Dark Green Rush	0.060
Scirpus cyperinus	Wool Grass	0.015
Total Grasses and Sec	dges:	6.303
Wildflowers/Broadleaves		
Alsclepias incarnata	Swamp Milkweed	0.500
Bidens cernua	Nodding Bur Marigold	0.190
Boltonia asteroids	False Aster	0.031
	Partridge pea	1.000
Chamaecrista fasciculate	i all things pas	
Chamaecrista fasciculate Euthamia gramnifolia	Grassleaved Goldenrod	0.025
	= :	0.025
Euthamia gramnifolia	Grassleaved Goldenrod	0.015
Euthamia gramnifolia Eupatorium perfoliatum	Grassleaved Goldenrod Common Boneset	0.015
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale	Grassleaved Goldenrod Common Boneset Sneezeweed	0.015 0.063
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale Iris virginica shrevei	Grassleaved Goldenrod Common Boneset Sneezeweed Blue Flag	0.015 0.063 1.500 0.031
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale Iris virginica shrevei Loebelia siphilitica	Grassleaved Goldenrod Common Boneset Sneezeweed Blue Flag Great Blue Lobelia	0.015 0.063 1.500 0.031 0.003
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale Iris virginica shrevei Loebelia siphilitica Mimulus ringens	Grassleaved Goldenrod Common Boneset Sneezeweed Blue Flag Great Blue Lobelia Monkey Flower	0.015 0.063 1.500 0.031 0.003 0.250
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale Iris virginica shrevei Loebelia siphilitica Mimulus ringens Symphyotrichum novae-angliae	Grassleaved Goldenrod Common Boneset Sneezeweed Blue Flag Great Blue Lobelia Monkey Flower New England Aster	0.015 0.063 1.500 0.031 0.003 0.250 0.063
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale Iris virginica shrevei Loebelia siphilitica Mimulus ringens Symphyotrichum novae-angliae Pycnanthemum virginianum	Grassleaved Goldenrod Common Boneset Sneezeweed Blue Flag Great Blue Lobelia Monkey Flower New England Aster Common Mountain Mint	0.015 0.063 1.500 0.031 0.003 0.250 0.063
Euthamia gramnifolia Eupatorium perfoliatum Helenium autumnale Iris virginica shrevei Loebelia siphilitica Mimulus ringens Symphyotrichum novae-angliae Pycnanthemum virginianum Rudebeckia fulgida var.sullvantii	Grassleaved Goldenrod Common Boneset Sneezeweed Blue Flag Great Blue Lobelia Monkey Flower New England Aster Common Mountain Mint Showy Black-Eyed Susan Golden Alexanders	0.063 1.500

D. Low Profile Prairie With Flowers Seed Mixture - Upper Basin Slopes

Botanical Name	Common Name	lbs /AC
Grasses		
Bouteloua curtipendula	Side Oats Grama	8.000
Panicum virgatum	Prairie Switch Grass	0.125
Elymus canadensis	Prairie Wild Rye	1.000
Schizachyrium scoparium	Little Blue Stem	6.000
Total Grasses:		15.125
Wildflowers/Broadleaves		
Allium cernuum	Nodding Wild <i>O</i> nion	0.190
Amorpha canescens	Lead Plant	0.125
Asclepias tuberosa	Butterflyweed	0.500
Asclepias verticillata	Whorled Milkweed	0.063
Astragalus canadensis	Canada Milk Vetch	0.063
Coreopsis palmata	Prairie Coreopsis	0.025
Echinacea pallida	Pale Purple Coneflower	1.000
Echinacea purpurea	Purple Coneflower	0.500
Eryngium yuccifalium	Rattlesnake Master	0.125
Lespedeza capitata	Round-Headed Bush Clover	0.125
Liatris aspera	Rough Blazing Star	0.250
Liatris pycnostachya	Prairie Blazing Star	0.188
Monarda fistulosa	Prairie Bergamont	0.063
Parthenium integrifolium	Wild Quinine	0.016
Penstemon digitalis	Foxglove Beardtongue	0.125
Petalostemum candidum	White Prairie Clover	0.125
Petalostemum purpureum	Purple Prairie Clover	0.156
Potentilla arguta	Prairie Cinquefoil	0.031
Pycanthemum tenuifalium	Slender Mt Mint	0.031
Ratibida pinnata	Yellow Coneflower	0.125
Rudebeckia fulgida var.sullvantii	Showy Black-Eyed Susan	0.500
Rudbeckia hirta	Black-Eyed Susan	0.500
Rudbeckia subtomentosa	Sweet Black-Eyed Susan	0.063
Symphyotrichum laeve	Smooth Blue Aster	0.063
Tradescantia ohiensis	Spiderwort	0.063
Verbena stricta	Hoary Vervain	0.125
Zizia aurea	Golden Alexanders	0.050

2.4 GROUNDCOVERS, PERENNIALS AND ANNUALS

and burlapped (B&B) deciduous shrubs.

per manufacturer's recommendations.

Total Wildflowers/Broadleaves:

Total Lo Pro Prairie Seed Mixture:

Provide plants established and well-rooted in removable containers or integral peat pots and with not less than the minimum number and length of runners required by ANSI Z60.1 for the pot size shown or listed.

5.190

20.315

2.5 TREES AND SHRUBS

- A. Name and Variety: Provide nursery grown plant material true to name and variety.
- B Quality: Provide trees, shrubs and other plants complying with the recommendations and
- requirements of ANSI Z60.1 "Standard for Nursery Stock" and as further specified. C. Deciduous Trees: Provide trees of height and caliper listed or shown and with branching configuration
- special forms are shown or listed. Provide balled and burlapped (B\$B) deciduous trees. D. Deciduous Shrubs: Provide shrubs of the height shown or listed and with not less than the minimum number of canes required by ANSI Z60.1 for the type and height of shrub required. Provide balled

recommended by ANSI Z60.1 for type and species required. Provide single stem trees except where

- E. Coniferous Evergreen: Provide evergreens of the sizes shown or listed. Dimensions indicate minimum spread for spreading and semi-spreading type evergreens and height for other types. Provide quality evergreens with well-balanced form complying with requirements for other size relationships to the primary dimension shown. Provide balled and burlapped (B\$B) evergreen trees and containerized
- F. Inspection: All plants shall be subject to inspection and review at the place of growth or upon delivery and conformity to specification requirements as to availity, right of inspection and rejection upon delivery at the site or during the progress of the work for size and condition of balls or roots, diseases, insects and latent defects or injuries. Rejected plants shall be removed immediately from the site.

2.6 PLANTING SOIL MIXTURE

Provide planting soil mixture consisting of clean uncompacted topsoil (stockpiled at site) for all planting pits, perennial, annual and groundcover areas. Topsoil shall be conditioned based on any recommendations resulting from the soil test in 1.3.C.

2.7 EROSION CONTROL

- A. Erosion Control Blanket-Detention Basins: North American Green \$150, or equivalent approved equal.
- B. Shoreline Erosion Control Blanket: North American Green SCI50, or approved equal. To be installed
- C. Lawn and Low-Mow Fescue Areas: Futerra EnviroNet color: Green, or approved equal. To be installed per manufacturer's recommendations.

2.8 MULCH

Provide mulch consisting of shredded hardwood. Provide sample to Landscape Architect for approval prior to ordering materials. LANDSCAPE WORK PART 3 - EXECUTION

3.1 PLANTING SCHEDULE

At least thirty (30) days prior to the beginning of work in each area, submit a planting schedule for approval by the Landscape Architect.

3.2 PLANTINGS

A. Seeding New Lawns

- 1. Remove existing grass, vegetation and turf. Dispose of such material legally off-site. Do not turn over into soil being prepared for lawns.
- 2. Till to a depth of not less than 6"; apply soil amendments; remove high areas and fill in depressions; till soil to a homogenous mixture of fine texture, remove lumps, clods, stones over 1"

diameter, roots and other extraneous matter. Dispose of such material legally off-site.

- 3. Seeded lawn areas shall receive an application of commercial fertilizer at the rate of 5 lbs. per 1,000 sq. ft. and shall be 6-24-24. Fertilizer shall be uniformly spread and mixed into the soil to a depth of 1" inches.
- 4. Do not use wet seed or seed which is moldy or otherwise damaged in transit or storage.
- 5. Sow seed using a spreader or seeding machine. Do not seed when wind velocity exceeds five (5) miles per hour. Distribute seed evenly over entire area by sowing equal quantity in two directions at right angles to each other.
- 6. Sow not less than specified rate.

disposed of legally off-site.

7. Rake lawn seed lightly into top 1" of soil, roll lightly and water with a fine spray.

B. Seeding Native Areas

- . The period for planting prairie seed shall be from April 1 to June 15 or September 15 to just before the first frost. Seeding outside of these timeframes must be approved by the landscape
- 2. The General Contractor and Native Landscape Contractor shall be responsible for performing all work necessary to achieve and maintain an acceptable seedbed prior to seeding. All areas must be properly prepared before seeding begins. Equipment having low unit pressure ground contact shall be utilized within the planting areas.
- 3. If present, compacted soils shall be disked or raked prior to seeding. Remedial measures for the access area may, at the direction of the Wetland Consultant, involve ripping from 12 to 18 inches
- 4. Prior to seeding, planting areas shall have at least twelve inches of clean un-compacted topsoil. Clumps, clods, stones over 2" diameter, roots and other extraneous matter shall be removed and
- 5. Granular mycorrhizal innoculants shall be installed with the seed mix at a rate of 40lbs/ acre. Inoculant can be banded under seed, worked into seed or added into spray tanks. Native areas shall not receive fertilizer.
- 6. Contractor shall be solely responsible for the proper handling and storage of the seed according to the best seed handling and storage practices, including fungicide treatments and stratification considerations. Owner shall make no compensation for damage to the seed because of improper storage, cleaning, threshing, or screening operations.
- 7. Except where site conditions preclude their use, seeding shall be performed using a Truax drill, ax Trillion seeder, or comparable equipment designed specifically for installation of native seed. For areas where site conditions preclude the use of specialized equipment, seed may be installed through hand broadcasting and followed by light raking. Hand broadcast seed shall be spread at twice the specified rate. Other methods of seed installation may be used with prior approval from the Landscape Architect.
- 8. Prior to starting work, all seeding equipment shall be calibrated and adjusted to sow seeds at the proper seeding rate. In general, the optimum seeding depth is 0.25 inch below the soil surface. Areas where the seed has not been incorporated into the soil to the proper depths will not be accepted, and no compensation for materials or labor for the rejected work will be made by the
- 9. Seeding and soil tracking/firming shall not be done during periods of rain, severe drought, high winds, excessive moisture, frozen ground, or other conditions that preclude satisfactory results.
- 10. Wet mesic and emergent areas shall be planted, and seed allowed to germinate (if possible), prior to flooding with significant amounts of water. Any areas of significant permanent water located within the planting area will receive live plugs in lieu of seed
- 11. After the seeding operation is completed, install erosion control blanket per manufacturer's
- 12. Emergent plugs shall be planted in natural groupings within designed areas containing saturated soils or shallow inundation. Plants within groupings shall be planted at 2 foot centers.
- 13. Emergent plugs shall not be planted less than the specified rate and shall be protected with goose exclosures surrounding all natural groupings of plugs.

E. Groundcover and Perennial Beds

Groundcover, perennials, and annuals shall be planted in continuous beds of planting soil mixture a minimum of 8" deep. Install per spacing indicated on plan.

F. Trees and Shrubs

- 1. Set balled and burlapped (B&B) stock plumb and in center of pit or trench with top of ball at an elevation that will keep the root flare exposed upon backfill and mulching. Remove burlap from top and sides of balls; retain on bottoms. When set, place additional topsoil backfill around base and sides of ball and work each layer to settle backfill and eliminate voids and air pockets. When excavation is approximately 2/3 full, water thoroughly before placing remainder of backfill Repeat watering until no more is absorbed. Water again after placing final layer of backfill
- 2. Dish top of backfill to allow for mulching. Provide additional backfill berm around edge of excavations to form shallow saucer to collect water.
- 3 Mulch pits, trenches and planted greas. Provide not less than 2" thickness of mulch and work into top of backfill and finish level with adjacent finish grades. Maintain exposed root flare at all
- 4. Prune only injured or dead branches from flowering trees, if any. Protect central leader of tree during shipping and pruning operations. Prune shrubs to retain natural character in accordance with standard horticultural practices.
- 5. Remove and replace excessively pruned or ill-formed stock resulting from improper pruning.
- 6. The Contractor shall be wholly responsible for assuring that all trees are planted in a vertical and plumb position and remain so throughout the life of this contract and guarantee period. Trees may or may not be staked and guyed depending upon the individual preference of the Contractor; however, any bracing procedure(s) must be approved by the Owner prior to its installation.

- A. Begin maintenance immediately after planting, continuing until final acceptance. A minimum of thirty
- B. Maintain planted and seeded areas by watering, rolling/regrading, replanting and implementing erosion control as required to establish vegetation free of eroded or bare areas. C. Low Mow Fescue and Native Planting areas are to be mowed only once per spring during the initial
- three year establishment period.

3.4 NATIVE LANDSCAPED AREAS CONTINUED MONITORING \$ MAINTENANCE

A. Monitoring

The Owner's Environmental Specialist shall inspect the plantings at least twice per year during the three-year term of the Establishment and Maintenance, to determine compliance with the minimum annual performance criteria (See 1.5C Guarantees). A monitoring report will be provided to the Owner by January 31st following each inspection.

B. Maintenance:

With the exception of the emergent area, native seeding areas should be mowed to a height of 6" to control annual nonnative and invasive species early in the growing season. Mowing, including weed whipping, should be conducted prior to weed seed production. Mowing height and timing may need to be adjusted per taraet species. Small quantities of undesirable plant species, shall be controlled by hand pulling prior to the development and maturity of the plant. Hand removal shall include the removal of all above-ground and below-ground stems, roots and flower masses prior to development of seeds. Herbicide should be applied as necessary by a trained and licensed operator that is competent in the identification of native and nonnative herbaceous plants. Debris and litter shall be removed from the native areas and storm structures shall be inspected and maintained as necessary. Supplemental reseeding shall occur in areas that are bare or sparsely vegetated. Native seed mixes shall be hand broadcasted over the soil surface and raked in.

Second Season

Control of undesirable plant species during the second growing season shall consist primarily of precise herbicide application. Mowing and weed whipping shall be conducted as needed during the early growing season and as needed to a height of 6 to 8 inches to prevent annual weeds from producing seed. Debris and litter shall be removed from the native areas and storm structures shall be inspected and maintained

Third, Fourth, and Fifth Years:

Seasonal mowing and herbicide will continue as above but should be reduced over time. Debris and litter shall be removed from the native areas and storm structures shall be inspected and maintained as necessary. At the completion of the third growing season (dependent on fuel availability; dominance of graminoid species; and favorable weather conditions), fire may be introduced to the planted areas as a

State and local permits shall be required prior to controlled burning. Burning shall be conducted by trained professionals experienced in managing smoke in urban environments. Prior to a controlled burn, surrounding property owners as well as local fire and police departments shall be notified. A burn plan detailing preferred wind direction and speed, location of fire breaks, and necessary personnel and equipment shall be prepared and utilized in planning and burn implementation.

The initial burn shall be dependant on fuel availability which is directly related to the quantity and quality of grasses contained within the plant matrix. Timing of the burn shall be determined based on results of the annual monitoring indicating species composition of the management area and other analysis of management goals. Generally, burns shall be scheduled from spring to fall on a rotational basis. Burn frequency shall also be dependant on the species composition within the management area. Generally, a new prairie restoration area shall be burned annually for two years after the second or third growing season after planting and then every 2-3 years thereafter, burning 50-75% of the area.

C. Long Term Wetland and Prairie Management/Maintenance


A final compliance report and Long-Term Operation and Maintenance Plan shall be submitted by the Developer/Owner's Environmental Specialist no less than 60 days prior to the expiration of any landscape Cash Bond or Letter of Credit posted for the native areas. Final acceptance and release shall be determined by the County/City/USACE upon inspection of the site to

The Long -Term Operation and Maintenance Plan shall be written to include auidelines and schedules for burning, mowing, application of herbicide, debris/litter removal and inspection schedule for strom


3.5 CLEAN UP AND PROTECTION

structures and sediment removal.

- A. During landscape work, store materials and equipment where directed. Keep pavements clean and work areas and adjoining areas in an orderly condition.
- B. Protect landscape work and materials from damage due to landscape operations, operations by other trades and trespassers. Maintain protection during installation and maintenance periods. Treat, repair or replace damaged landscape work as directed by Landscape Architect.
- 3.6 INSPECTION AND ACCEPTANCE
- A. The Landscape Architect reserves the right to inspect seeds, plants, trees and shrubs either at place of growth or at site before planting for compliance with requirements for name, variety, size, quantity, quality and mix proportion.
- B. Supply written affidavit certifying composition of seed mixtures and integrity of plant materials with respect to species, variety and source
- C. Notify the Landscape Architect within five (5) days after completing initial and/or supplemental
- D. When the landscape work is completed, including maintenance, the Landscape Architect will, upon request, make a final inspection to determine acceptability. After final acceptance, the Owner will be responsible for maintenance.



SIMTEK FENCE LAYOUT DETAIL





GARY R. WEBER ASSOCIATES, INC LAND PLANNING ECOLOGICAL CONSULTING LANDSCAPE ARCHITECTURE 212 SOUTH MAIN STREET

WHEATON, ILLINOIS 60187

PHONE: 630-668-7197

OWNER/APPLICANT: **OLD DOMINION** FREIGHT LINE, INC 500 OLD DOMINION WAY THOMASVILLE, NC 27360

CIVIL ENGINEER: MANHARD CONSULTING 700 SPRINGER DRIVE



Z 0

4 S

Ш

6.03.16 5.23.16 REVISIONS