



Fire Apparatus Quotation for: AURORA FIRE DEPARTMENT

Quotation Number: 124395 Rev: 6

Unit Description: PTAL-CYCN

Quote Description: Pumper, Aluminum, Cyclone

Salesperson: GREGHANSEN

Salescode	Extended Description	Qty
TESTING COMPLIANCE STANDARD		
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1
3090-0002	OAH. Unit has no overall height restrictions.	1
3090-0004	OAL. Unit has no overall length restrictions.	1
3090-0006	The hose bed is to have the capacity for the following hose. Hose load shall be listed from driver to officer.	1
3340-1137-12B	Equipment allowance on the apparatus shall be 2000 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1
INSPECTIONS AND PENAL TIES		
1002-0001	Final inspection trip.	1
BUMPERS		
1160-0000	Bumper 10" stainless steel.	1
1160-0008	3/16" Front Bumper Gravel Shield.	1
1160-0015	24" Front Bumper Gravel Shield Extension.	1
BUMPER TRAYS		
1150-0120	Bumper tray center of bumper with slats 12 inches deep (approx 11 inches to slats).	1
1150-0126	Divider center bumper tray running side to side with adjustable track (Provides two storage areas, one ahead and one behind divider).	1
1150-0139-589	Nylon black strap with a stainless steel quick release buckle for front bumper hose tray. Strap to attach to front and rear walls of tray down low as applicable. Location: center.	1

Salescode	Extended Description	Qty	
FRAME ASSEMBLY			
1250-0076	Rear underbody support frame. Zinc plated (galvanized).	1	
1250-0080	Frame assembly with 10.25 x 3.5 x .375 powder coated galvanized rails.	1	
1250-0083	Frame liner 9.375 x 3.125 x .375, galvanized and powder coated.	1	
1250-0085	Front chassis frame extensions, crossmembers and battery brackets shall be zinc plated (galvanized) IPOS. Includes rear subframe if applicable (urban interface, straight frame 4x4, etc).	1	
1250-0092	GEOMET coated frame assembly fasteners.	1	
AXLE OPTIONS			
1025-0017	Meritor RS-25-160 single rear axle 27,000 lb. capacity.	1	
1025-0028	Koni shock absorbers for front axle - adjustable.	1	
1025-0030	Stemco sight glass for front axle hubs. Inboard wheel seals will be Chicago Rawhide (or equivalent).	1	
1025-0232	Meritor MFS-20 front axle rated at 20,000 lb. For use on 100" wide cabs with L9 engine only. Includes maintenance free bushings.	1	
SUSPENSIONS			
1070-0027	Rear suspension FIREMAAX EX model FMX-272 27,000 lb. single axle air ride.	1	
WHEEL OPTIONS			
1050-0001	Alcoa aluminum wheels for front axle (2).	1	
1050-0003	Alcoa aluminum wheels for rear axle (4).	1	
1050-0007	Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals.	1	
1050-0008	Rear axle (single) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers.	1	
1050-0017	Each inside wheel of the single rear axle shall have valve stem extensions.	1	
TIRE OPTIONS			
1060-0016	Four Michelin 12R rear tires with XDN2 all weather tread.	1	
1060-0043	Two Michelin 425 tires model XZY3 for front axle.	1	
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1	
BRAKE SYSTEMS			

Salescode	Extended Description	Qty	
BRAKE SYSTEMS			
1100-0001	Meritor EX225H 17" disc brakes for front axle.	1	
1100-0003	Meritor EX225H 17" disc brakes for rear axle, maximum capacity 27,000 lbs.	1	
1100-0005	Brake system air 4X2/4X4.	1	
1100-0006	Parking brake release mounted on the driver's side lower dash.	1	
1100-0020	Compression fittings for all air brake system lines. Includes cab interior air lines as applicable and accessories (if equipped).	1	
1100-0024	G4 Electronic Stability Control (4x2), Includes RSC and ATC. Not available on 4x4, commercial chassis or tiller.	1	
AIR SYSTEM OPTIONS			
1110-0000-001	Inlet for air system. Location: driver door jamb.	1	
1110-0002	Air dryer Bendix AD-9.	1	
1110-0006	Air lines nylon.	1	
1110-0026	Air horns Hadley e-tone recessed in bumper (PR).	1	
1110-0027	Isolated air tank. Includes pressure protection valve.	1	
1110-0034	Auxiliary air tank to be plumbed to the chassis air horns only.	1	
1110-0044-179-02	Air inlet Auto-Eject, Kussmaul. Includes Red weatherproof gasketed cover. Location: outside driver's door next to handrail.	1	
1110-0050	Air brake lines to have 4 to 6" slack for future service work.	1	
1110-0096	Stainless steel mounting straps for air tank.	4	
ENGINES & TRANSMISSIONS			
1200-0017	Push-button transmission shift selector.	1	
1200-0020	TranSynd, Shell Spirax S6ATF A295, or equivalent synthetic transmission fluid for EVS3000 series.	1	
1200-0097	Electronic limiting of speed to 68 MPH maximum. Note: Axle gear ratio will be as low as possible while allowing for 68 MPH top speed to improve acceleration. Note: Max speed may be set at 65 MPH due to tire rating.	1	
1200-0413	Eng/Trans Cummins L9 400HP/EVS3000 2021 EPA compliant engine.	1	
SECONDARY BRAKING			
1125-0003	Allison transmission retarder. Pre-select feature will be switched off with this option.	1	
1125-0010	Allison transmission retarder to be programmed at 1/3 off throttle, 1/3 at 4 psi brake pressure, 1/3 at full (10 psi) brake pressure.	1	

Salescode	Extended Description	Qty	
EXHAUST OPTIONS			
1225-0060	Exhaust end with fresh air vent for Plymovent exhaust extraction system.	1	
COOLING PACKAGE			
1800-0013	Cooling system for use with Typhoon, Cyclone and Quest chassis. For use with 2010 - 2021 EPA engines. Includes coolant recovery system.	1	
1800-0029	Engine cooler. E-ONE chassis only. Requires control option for pump panel.	1	
FUEL SYSTEMS			
1350-0011	Fuel pump electric w/re-prime.	1	
1350-0012-670	Fuel shut-off valve. Location: one (1) inlet side of OEM fuel filter.	1	
1350-0022	Fuel line hose rubber.	1	
1350-0043	Fuel system w/50 gallon stainless steel tank.	1	
ALTERNATOR			
1700-0027	Alternator Leece Neville 420 amp. 420 amp SAE/369 amp NFPA.	1	
BATTERIES			
1400-0019-3XJ	Special battery jumper stud location. Jumper studs to be located behind driver side top mount walkway access door. All wiring connections to be inside compartment, not exposed to elements..	1	
1400-0031	Stainless steel battery trays with stainless steel covers.	1	
1400-0032	Battery five group 31 1000 CCA (two left / three right). For use with below cab DEF tank only.	1	
CHASSIS OPTIONS			
1680-0005	Thermatic fan clutch.	1	
1680-0006	Drivelines 1710.	1	
1680-0008	Tow eyes front painted below bumper/cab (PR).	1	
1680-0075	(3) way rear underbody receiver assembly. Includes rearward 9000 lb. winch receiver or Class III trailer receiver and (2) side facing 9000 lb. winch receivers- (1) each below rearward body compartments. Includes rearward tow eyes and electrical winch connections for each receiver. NOTE: When facing the receiver, mount electrical connection to the left side.	1	
1680-0250-M58	Diesel Exhaust Fluid (DEF) 5 gallon tank. Location: left side below rear of cab.	1	
1680-0284	Radiator mounted power steering cooler.	1	
CAB MODEL			

Salescode	Extended Description	Qty	
CAB MODEL			
1520-0244	Cyclone long cab - 100" wide (67.5" CA).	1	
CAB ROOF TYPE			
1615-0005	Delete front vista roof windows.	1	
1615-0007	Delete rear vista roof windows.	1	
1615-0009	Delete upper rear door vista roof windows	1	
1615-0042	Vista cab roof 4F/16R. Includes 4" front raise and 16" rear raise (12" step up). Does not include front side Vista windows. For use with 100" wide Cyclone only.	1	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
CAB DOOR OPTIONS			
1550-0003	Rear crew cab doors in the medium position.	1	
1550-0084	All cab exterior entry doors to have 1250 keyed locks.	1	
1550-0159	Interior cab door locks - manual. Will be individually actuated from each respective door. Includes key lock on each exterior cab door handle.	1	
1550-0179-000-17	Red/Fluorescent Yellow Green Reflexite V98 chevron "A" stripe on lower cab door panel approx 18" high. Stainless steel/painted door panels only. E-ONE cabs only.	1	
1550-0185	Cab door panels aluminum painted multi-tone to match cab interior paint. Includes upper and lower panels with seam below handrail.	1	
1550-0247-657	Door mounted Weldon 8401 series 16" x .75" amber LED flashing arrow strip lights (4) w/clear lenses. Locate lights on each cab door in the outboard position. Lights to be switched with door ajar.	1	
1550-0283	Driver and officer cab door windows with manual regulators. For use with new Typhoon and Cyclone cabs.	1	
1550-0284	Rear crew cab door window(s) with manual regulator(s). For use with new Typhoon and 100" wide Cyclone cabs.	1	
1550-0288	Cab doors to extend down to cover lower step well. For use with new Typhoon cab and 100" wide Cyclone only.	1	
1550-0377	All cab doors shall have exterior pull style handles with integral key lock (glass reinforced nylon).	1	
CAB STEP OPTIONS			
1640-0045-158	Step below cab door. Open back style with angled corners. Located driver's front door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0045-159	Step below cab door. Open back style with angled corners. Located officer's front door. Steps under front cab doors shall not interfere with approach angle.	1	

Salescode	Extended Description	Qty	
CAB STEP OPTIONS			
1640-0045-160	Step below cab door. Open back style with angled corners. Located driver side rear door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0045-161	Step below cab door. Open back style with angled corners. Located officer side rear door. Steps under front cab doors shall not interfere with approach angle.	1	
1640-0047	Lower steps to extend 3.5" past cab. For use with legacy Typhoon / Cyclone with barrier style doors and new Typhoon / Cyclone with barrier style or extended doors.	1	
MIRRORS			
1670-0001-274	Ramco 6001FFR mirrors. Remote controlled with top CAS750 manual convex. Location: mounted on front corners of cab.	1	
1670-0031	2" extension for Ramco mirrors.	1	
1670-0088	Driver and officer Ramco cab mirrors to be heated. Includes all surfaces (flat and convex, as applicable).	1	
MISC EXTERIOR CAB OPTIONS			
1550-0035	No window on the driver side of the cab	1	
1550-0036	No window on the officer side of the cab.	1	
1675-0030	Mud flaps, front, black with E-ONE logo.	1	
1675-0049	Rear cab wall to be smooth 3/16" aluminum plate with a diamond plate overlay.	1	
1675-0201	Large radius cab wheel well. Includes bolt-on adjustable wheel well trim.	1	
1675-0202	Mounting plate for battery charger receptacle, indicator, air inlet, etc (if applicable). Plate to be removable brushed stainless steel.	1	
1675-0229	Pair of one piece knurled stainless steel 18" handrails located just behind driver and officer front door one each side.	1	
1675-0254	Rear cab and vista glass (if so equipped) to have dark tint IPOS. Glass to be smoked glass with 20% light transmittance (+/- 10%). Includes all glass rearward of front cab doors.	1	
1675-0269	Pair of one piece knurled stainless steel 18" handrails located just behind driver and officer rear door one each side.	1	
1685-0705	Coat hook(s), stainless steel Brey-Krause VS-1030-BS, shall be provided on the cab. Location: mounted with the upper mount of the cab handrail. (EA) For one piece hand rails only.	4	
HVAC			
1515-0053	Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and Cyclone with severe duty dash)	1	
1515-0078	Locate rear cab heaters one each side on lower rear wall inboard of step wells.	1	

Salescode	Extended Description	Qty	
HVAC			
1515-0085	Additional fan control for rear facing air conditioner. Locate adjacent to rear AC vents/filter on officer side.	1	
1515-0099	Air conditioning with radiator mounted condenser for use with Cummins L9 and X12 engine. Includes reduced profile evaporator w/powder coated cover and electronic controls.	1	
1685-0056	Heater rear cab w/o cover (PR) and front cab heater with heat to the feet for the driver and officer.	1	
SEATS			
1510-0116-132	Fold-down seat located officer's side outboard.	1	
1510-0203-147	Bracket SCBA IMMI SmartDock Gen2 restraint system. Location: officer's seat.	1	
1510-0203-151	Bracket SCBA IMMI SmartDock Gen2 restraint system. Location: inboard driver's side rear wall.	1	
1510-0203-152	Bracket SCBA IMMI SmartDock Gen2 restraint system. Location: inboard officer's side rear wall.	1	
1510-0279-146	Ready/Reach seat belt extender. Location: driver's seat.	1	
1510-0279-147	Ready/Reach seat belt extender. Location: officer's seat.	1	
1510-0279-151	Ready/Reach seat belt extender. Location: inboard driver's side rear wall.	1	
1510-0279-152	Ready/Reach seat belt extender. Location: inboard officer's side rear wall.	1	
1510-0301	Seats, Valor brand.	1	
1510-0302	Seat cover material Valor Tech XD (previously identified as Cordura).	1	
1510-0303	Seat color black with red stitching.	1	
1510-0328	Driver seat USSC Valor P1A air ride.	1	
1510-0332	Two man bench centered on rear wall with Valor SCBA backs. Includes angled corners.	1	
1510-0345	Officer seat USSC Valor P1A air ride SCBA.	1	
1685-0032	Seating capacity tag of five occupants.	1	
MEDICAL CABINETS			
1535-0129	Reverse hinge driver and officer side ALS compartment door. Includes vertically mounted drip rail along forward area of compartment opening (as applicable)(in addition to the horizontal drip rail above the door opening; Cyclone and Typhoon cabs only). Doors to open approx. 110 degrees.	1	
1535-0177	Compartment rear side of cab "under riser" type. Approx 9W x 30H opening. Includes double pan hinged door. Long cab with medium door location only. Note: striker pin extends into opening - may block extinguisher placement.	1	

Salescode	Extended Description	Qty	
MEDICAL CABINETS			
1535-0202	Location: driver and officer side. Cab medical/storage cabinet(s) finish to be multi-tone gray. Includes interior/exterior of cabinet and shelves/trays if equipped.	1	
1535-0256	Officer side cab wheel well medical cabinet with external locking pan door painted job color and interior cargo net. Cabinet includes (2) adjustable shelves. Cabinet is approximately 42H x 22W x 28D on Typhoon and Cyclone and 42H x 25W x 28D on 100" wide Cyclone and Quest (viewed from interior).	1	
1535-0257	Driver side cab wheel well medical cabinet with external locking pan door painted job color and interior cargo net. Cabinet includes (2) adjustable shelves. Cabinet is approximately 42H x 22W x 28D on Typhoon and Cyclone and 42H x 25W x 28D on 100" wide Cyclone and Quest (viewed from interior).	1	
1535-0310	The compartments to the rear sides of the cab are to be designed with a pass through that extends fully from the driver side compartment to the officer side compartment. To be used when equipped with a bench seat riser, common riser used with individual seat(s) or center rear wall cabinet.	1	
1535-0583-160	The cab compartment located behind driver side rear door to have floor 7.75 inch outside dimension square recessed 4" for storage of one (1) standard size SCBA bottle, 20lbs ABC Extinguisher or 2.5 gal Water Extinguisher. Storage shall be rectangular with cutout for extinguisher hose towards the inside wall. Requires minimum 30" tall compartment and 67.5" CA or longer cab.	1	
1535-0583-161	The cab compartment located behind officer side rear door to have floor 7.75 inch outside dimension square recessed 4" for storage of one (1) standard size SCBA bottle, 20lbs ABC Extinguisher or 2.5 gal Water Extinguisher. Storage shall be rectangular with cutout for extinguisher hose towards the inside wall. Requires minimum 30" tall compartment and 67.5" CA or longer cab.	1	
1535-0680	Louvers for interior medical/ ALS cabinet wall(s) to help cabinet contents to maintain cab interior temperatures. The louvers specified by customer, using Baan notes.	1	
1535-0705	(2) broom handle tubes vertically stacked on forward wall of cab transverse compartment.	1	
1535-0835	Upper forward vista area cabinet. Cabinet to be full width and height of vista area forward of rear cab doors full depth flush with forward edge of rear cab door. Includes (3) horizontal hinged lift-up doors. Outboard compartments to be approx. 12" wide. with horizontally hinged lift-up doors and push button thumb latch(es).	1	
1535-0926	Special cargo net cover with twist lock fasteners on cab medical cabinets IPOS. (EA)	2	
1535-1091	Upper forward vista cabinet door(s) to use Southco latch in place of standard.	1	

Salescode	Extended Description	Qty
MAP BOXES		
1540-0013	All map boxes in the cab to be painted multi-tone gray finish.	1
1540-0029	Offset suspended map box to rear of vertical 3x3 extrusions and as low as possible. Front of map box flush with front of 3x3 uprights.	1
1540-0103	Map box suspended with drop down doors. 34"W x 6"H x 12.5"D. Includes full width upper shelf and lower vertical divider.	1
MISC INTERIOR CAB OPTIONS		
1685-0005	Lexan sun visors, driver and officer's side overhead.	1
1685-0068	Rear engine cover diamond plate trim.	1
1685-0187	Severe duty engine cover, molded polyurethane.	1
1685-0275-966	Cup holder (PR). Polyurethane construction for use in Typhoon and CII with severe duty engine cover only. Location: to be mounted at final inspection.	2
1685-0438	Cover(s) below rear bench seat or in the transverse/ pass-thru area (if equipped) to protect back of heaters.	1
1685-0446	Severe duty overhead console. Includes driver, center and officer overhead ahead of air conditioning plenum. Center overhead includes siren mounting locations. Overhead to match cab interior.	1
1685-0464	Control lanyard Y type with "Heavy-Duty" (keyring) attachment for air horns.	1
1685-0531	Reduced profile rear engine cover for increased legroom.	1
1685-0670	Severe duty dash package with raised profile center section. Cast alum construction. Includes smooth plate alum lower kick panels; all painted to match cab interior.	1
1685-0692	Cab insulation package. Includes insulation for ceiling, front wall, rear wall, side walls, below seat risers and in doors.	1
1685-0775	Aluminum tray mounted to rear of engine cover. Approximately 49"W x 22"D with 2" lip on all sides. To be used between wheel well cabinets (as applicable). Located approx. 21" from floor to bottom of tray. Finish to match interior. Equipment stored on shelf must use brackets to meet NFPA.	1
1685-0891	Cab interior padding to be gray.	1
CAB ELECTRICAL OPTIONS		
1750-0015-175	Windshield fans 8" pair. Location: centered below overhead console.	1
1750-0015-G71	Windshield fans 8" pair. Location: rear facing mounted up high on vertical 3 x 3 posts.	1
1750-0024-179-02	Auto-Eject receptacle inlet 20 amp located outside driver's door next to handrail with a Red cover.	1
1750-0031	Switch horn button two position DOT/Q2B.	1

Salescode	Extended Description	Qty	
CAB ELECTRICAL OPTIONS			
1750-0046-194	Cab Headlights. Position: upper.	1	
1750-0070	Additional 4" red LED dome lights (PR) for rear of cab.	1	
1750-0071-585	Mount customer supplied antenna on cab roof. Location: driver side forward with coaxial cable terminating at the center of the dash board. Note: New antenna with original packaging only, used antenna not acceptable.	1	
1750-0071-586	Mount customer supplied antenna on cab roof. Location: driver side rearward with coaxial cable terminating at the center of the dash board. Note: New antenna with original packaging only, used antenna not acceptable.	1	
1750-0071-844	Mount customer supplied antenna on cab roof. Location: officer side forward with coaxial cable terminating at the center of the overhead console. Note: New antenna with original packaging only, used antenna not acceptable.	1	
1750-0072-456	12 VDC electrical outlet wired battery hot. Location: as specified. C/A to note in Baan specific locations per customer specification.	2	
1750-0072-592	12 VDC electrical outlet wired battery hot. Location: driver side dash.	1	
1750-0072-593	12 VDC electrical outlet wired battery hot. Location: officer side dash.	1	
1750-0072-748	12 VDC electrical outlet wired battery hot. Location: officer side rear cab wall in or below seat support structure as space allows.	1	
1750-0074	Interlock to position front intake for cab tilting.	1	
1750-0075	English dominant main cab gauge cluster.	1	
1750-0166	ATC override switch.	1	
1750-0198-01J	Battery charger to be located driver side of vista medical cabinet.	1	
1750-0265	Speedometer for officer side multiplex display.	1	
1750-0344	Battery charger E-ONE LPC 40. 120 volt inlet, 40 amp output. Includes status indicator panel.	1	
1750-0449	Momentary DPF regeneration override switch.	1	
1750-0482	Control push-button switch officer switch panel for Q2B siren.	1	
1750-0483	Control push-button switch on officer's switch panel for Q2B siren brake.	1	
1750-0580	Light EON LED (EA) mounted in riser height compartment.	2	
1750-0659-173	Turn signal Federal Signal FireRay model FR6-ARROW LED amber pair located lower headlight bezel.	1	
1750-0663	JW Speaker LED cab headlights. Model 8800 Evolution 2, heated.	1	
1750-0764	Daytime Running Light TecNiq LED strip (PR) with polished alum housing located between quad headlight bezels (New Typhoon and Cyclone only).	1	
1750-0768	TecNiq D07 LED cab door step area lighting. Includes (2) lights at each door area. Lights to be switched with door ajar.	1	

Salescode	Extended Description	Qty	
CAB ELECTRICAL OPTIONS			
1750-0902-456	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: as specified. C/A to note in Baan specific locations per customer specification.	2	
1750-0902-592	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: driver side dash.	1	
1750-0902-593	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: officer side dash.	1	
1750-0902-748	Kussmaul dual port USB product code 091-264-N. Includes USB-C and USB-A NGR outlet charger sockets in the cab wired battery hot. Location: officer side rear cab wall in or below seat support structure as space allows.	1	
1750-0912	Radio speakers pair. Locate speakers in cab as specified by sales, with wiring terminating in location as specified by sales.	1	
5400-0057	Dome lts red/white 4" LED (4). Lights to be located two front and two rear. White light wired through door and light assembly mounted rocker switch. Red light through light assembly mounted rocker switch.	1	
BODY COMPT LEFT SIDE			
3100-0351	Driver side body with full height 48" wide forward and 62" wide rearward compartmentation. Includes (1) 56" wide compartment over the wheel well.	1	
BODY COMPT RIGHT SIDE			
3120-0520	Officer side body with full height 48" wide forward and 62" wide rearward compartmentation. Includes (1) 56" wide compartment over the wheel well.	1	
BODY COMPT REAR			
3110-0042	Single low rear compartment. For use with low hosebed. Includes smooth plate panels. This compartment shall be transverse through to the side rear compartments.	1	
3110-0284	Bolt-on diamond plate 18" tailboard (full width of body). Includes (2) slanted beavertails (no stanchions) with removable outer panels and handrails- (2) vertically on trailing edge of body.	1	
3110-0728	(1) bolt-on compartment 14.5" W x 31" H x 14" D. Locate on the driver side of rear step and to have 13" wide opening. The compartment includes smooth plate door with D-ring, removable Duradek flooring and embossed non-skid treadplate compartment top. Lower hose bed access steps to be mounted to inboard side of compartment.	1	
DOORS			

Salescode	Extended Description	Qty	
DOORS			
3300-0021-004	Door roll up short (up to 45") with painted finish ROM. Location(s): L2.	1	
3300-0021-016	Door roll up short (up to 45") with painted finish ROM. Location(s): R2.	1	
3300-0022-003	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L1.	1	
3300-0022-005	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L3.	1	
3300-0022-015	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R1.	1	
3300-0022-017	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R3.	1	
3300-0066-003	Drip pan for a ROM roll-up door (EA). Location(s): L1.	1	
3300-0066-004	Drip pan for a ROM roll-up door (EA). Location(s): L2.	1	
3300-0066-005	Drip pan for a ROM roll-up door (EA). Location(s): L3.	1	
3300-0066-015	Drip pan for a ROM roll-up door (EA). Location(s): R1.	1	
3300-0066-016	Drip pan for a ROM roll-up door (EA). Location(s): R2.	1	
3300-0066-017	Drip pan for a ROM roll-up door (EA). Location(s): R3.	1	
3300-0276	All rear panel body storage compartments and tunnels with hinged doors greater than 1 sq. ft. shall have D-Ring latches in place of thumb latches .	1	
3300-0290-027	Door double vertical hinged w/rotary latches - smooth plate sanded. Location(s): B1. Includes latch handle extension installed on secondary door's interior latch with "PULL" tags using .125 plate.	1	
3300-0368	Pull-down bungee type straps for full height and high side roll-up door(s) on body / pump module. For use with ROM and AMDOR doors only.	1	
SHELVES			
3370-0245	Permanent fixed shelf. Aluminum or stainless steel body applications. Location:	2	L1 bottom of transition; L3 top of transition
3370-0246	Adjustable shelf for non-transverse compartments. Location:	7	L1 lower; L2; L3 lower; R1 lower rear of part; R2; R3 upper fwd of part; R3 lower fwd of part
3370-0247	Tracks for adjustable shelf and/or adjustable tray in a compartment. Location:	6	L1; L2; L3; R1; R2; R3
COMPARTMENT DIVIDERS			
3390-0557	Partition, bolt-in vertical partition wall. Location:	2	R1 lower 12in from fwd wall; R3 18in from fwd wall
TRAYS / TOOLBOARDS			
3380-0049-135	Running board suction tray (floating style). Includes tapered 3" front corner and removable slats in bottom of tray. Location(s): driver side running board.	1	
3380-0049-136	Running board suction tray (floating style). Includes tapered 3" front corner and removable slats in bottom of tray. Location(s): officer side running board.	1	
3380-0508	Adjustable heavy duty tool board with 500 lbs. capacity. Includes return style	2	R3

Salescode	Extended Description	Qty	
TRAYS / TOOLBOARDS			
	reinforcing bends on vertical front and rear edges of tool board, upper and lower adjustable track and gas shock actuated. Tool board sized to compartment height and depth as applicable. Location:		
3380-0513	Fixed wall mounted toolboard. Toolboard to be spaced off wall a half inch. Location:	1	L1 upper back wall
3380-0515	PAC TRAC panels vertical stacked with tool mounting grooves orientated horizontal on wall of a compartment. Location:	1	R1 upper backwall
COVERS			
3305-0022-000-02	Vinyl rear cover for diamond plate hose bed cover. Color: Red.	1	
3305-0027	Nylon black cargo net on sides of speedlay. One pair per opening.	1	
3305-0064-135	Nylon black strap with stainless steel quick-release buckle for hose tray. Strap to attach to side walls of tray down low as applicable. Location: driver side running board.	1	
3305-0064-136	Nylon black strap with stainless steel quick-release buckle for hose tray. Strap to attach to side walls of tray down low as applicable. Location: officer side running board.	1	
3305-0069	Diamond plate speedlay cover. Includes fixed rear portion on rear of module (over backboard storage area, if applicable) and hold-open with grab handles on rearward area.	1	
3305-0318	Two (2) piece aluminum hose bed cover. The rear section shall slide over the forward section on tracks and rollers. When rolled open, the two sections shall lift upward on a forward mounted stainless steel piano hinge to assist in loading hose. Includes appropriate handrails per NFPA guidelines. Maximum allowable hosebed length of 155".	1	
PUMP MODULE			
3130-0167	Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and transverse module(s) if applicable.	1	
3130-0524	Top mount pump module with 20" walkway (excluding cab gap). Extruded aluminum with runningboards and formed side access steps.	1	
3130-0532	Pump panel opening is 39" wide. Pumper / tanker only.	1	
3130-0540	Pump module height is 80". Pumper / tanker only.	1	
3130-0634	One (1) Folding step each side of TM walkway in place of the standard diamond plate gator grip step.	1	
3130-1134	Speedlay module (stacked). Includes area for (2) speedlays, lower storage compartments with push button latches and running boards.	1	

Salescode	Extended Description	Qty
PUMP PANELS		
3134-0014	Driver and Officer side upper pump access panels to be horizontal hinged with diamond plate doors. Includes (2) push-button latches and (2) hold opens for each.	1
3134-0015	Stainless steel TM control panel, driver and officer side pump panels.	1
MISC PUMP PANEL OPTIONS		
4460-0003	Pump panel tags color coded per NFPA compliance.	1
4460-0004	All tags installed on the exterior of the apparatus shall be mechanically fastened with stainless steel screws. These include but not limited to tags installed on the pump module, body, cab and bumper. Pump panel tags shall be mechanically fastened regardless whether the panel is enclosed behind a door.	1
4460-0010	Pump panel tags - Special label. (Must specify.)	1
4460-0087	Hose reel blow-out, with Innovative Controls 1/4" valve w/1/4 turn handle.	1
PUMP MODULE OPTIONS		
3136-0000-372	Air horn switch at pump panel. Switch to be labeled "Evacuation Alert". Location: top mount control panel.	1
3136-0010	Stainless steel roller assemblies for crosslays and/or speedlays.	1
3136-0011	P-Rubber in flex joint(s) between pump module and/or body modules.	1
3136-0015	(2) vertical mounted booster reel spool guide roller assemblies. Locate (1) each side on trailing edge of beavertails/body (as applicable). For use with rear compartment mounted booster reel or similar.	1
3136-0031	Removable Speedlay Tray(s). The floor of the tray(s) to be slotted to prevent the accumulation of water and allow for ventilation of wet hose.	2
3136-0050	Heat pan extensions. Includes bolt-on plates added to the front and rear of the heat pan extending up as close as possible to the chassis frame rails and other components to fill all open gaps, further enclosing the pump module for increased heat retention.	1
3136-0058	E-ONE logo mounted one each side on pump module/preconnect panels. Logos to be sized as applicable to available space on panels.	1
3136-0064	Heat pan. The lower area of the pump compartment to have a four (4) sided heat pan with two (2) removable (side to side) bottoms. Bottoms to be secured in the closed position with butterfly latches.	1
3136-0138	Pump module storage pan.	1
3136-0146	Compartments for area below TM walkway (PR). Includes hinged door each side with push button latch and LED compartment light. Requires TM pump module	1

Salescode	Extended Description	Qty	
PUMP MODULE OPTIONS			
	with walkway.		
WATER TANK			
4010-0064	780 Gallon" L" shape Water Tank. Includes lowered rear section for lower hosebed height. Note: Any foam cell(s) optioned will reduce the overall water capacity. Tank capacity is 780 US gallon / 649 Imperial gallons / 2952 Liters.	1	
4010-0223	Fill tower(s) to be located offset to driver side of water tank.	1	
TANK PLUMBING			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0119	3" tank to pump Akron manual valve w/4" tank connection.	1	
FOAM TANK			
4100-0013-590	50 gallon integral foam tank for Class A foam. Foam tank capacity will reduce the water tank capacity. Tank capacity is 50 US gallon / 41 Imperial gallons / 189 Liters.	1	
LADDER STORAGE / RACKS			
3365-0049	Brand of ladders capable of being carried on unit to be Alco-Lite.	1	
3365-0075-0XE	Officer side vertical storage tunnel. For use with low hose bed. Tunnel to hold: 2-section 24', 14' roof, 10' attic, (1) standard backboard and (3) pike poles. Includes vertical hinged rear smooth plate door(s) with push-button latch.	1	
3365-0086-B02	Pike pole(s) capable of being stored are to be the following length: (3) 10' pike poles.	1	
3365-0087-C57	The length of ladders capable of being stored shall be the following: 24' 2-section and 14' roof ladder.	1	
HANDRAILS / STEPS			
3330-0165-E56	Handrail 24". Location Officer side pump module up high.	1	
3330-0165-H16	Handrail 24". Location Driver side pump module up high.	1	
3330-0206	Step rear 10" intermediate embossed treadplate. Locate below hosebed, includes three (3) hand hold cut-outs on top of the step in place of the hand rail.	1	
3330-0277	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable).	1	
3330-0278	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on officer side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on officer side	1	

Salescode	Extended Description	Qty	
HANDRAILS / STEPS			
	upper hosebed side (as applicable).		
3330-0279-060	Innovative Controls dual lighted LED folding step. Location: officer side front compartment face. Each location requires a minimum of (1) handrail per NFPA.	4	
3330-0279-062	Innovative Controls dual lighted LED folding step. Location: driver side front compartment face. Each location requires a minimum of (1) handrail per NFPA.	4	
3330-0340	Handrail upgrade for pump enclosure (as applicable) and rear body handrails (excludes chrome grab handles if equipped) replaced with Brey-Krause Mfg. Co. one piece knurled SS IPOS.	1	
MISC BODY OPTIONS			
3340-0004	Hosebed above the booster tank. Includes forward hosebed and tower(s) cover plate work (as applicable). Hosebed adjustable divider extrusion in the forward area and rearward area of the hose bed to run full width of the hosebed (as is practical with other hosebed mounted equipment).	1	
3340-0035	Divider Long. To run full length of hose bed (front to rear).	3	
3340-0049	Hosebed storage pan. Locate in forward area of hosebed.	1	
3340-0058	Recessed fuel fill driver side wheel well.	1	
3340-0074	Body mainframe and hosebed side assemblies for a 85" high body.	1	
3340-0079	Locate Tank Fill Tower(s) in the hose bed storage pan as applicable.	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0102	(Boston style) Angled tailboard corners.	1	
3340-0110	The rear of each hose bed divider to have a hand hold cut-out(s).	1	
3340-0145	Rub rail for the body and pump area module(s).	1	
3340-0190	Diamond Plate Hosebed Storage Pan Cover. Includes (1) D-ring latch and gas shock(s). Hinge to the rear of the hosebed storage pan. Cover to open to 90 degrees.	1	
3340-0191	Divider Support to run full width of hosebed (side to side) at the front of the hosebed and towards the rear of the hosebed at top of the divider(s). Attach to each hosebed divider to provide additional support.	1	
3340-0520	Smooth plate single axle wheel well painted job color. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes.	1	
3340-0681	Body mainframe layout line to be 24". Includes body and all applicable modules.	1	
3340-0961	Divider long fixed at the edge of the step-down in hosebed (officer side). Divider to run full length of hose bed (front to rear).	1	
3340-1373	Hosebed divider(s) to be notched as specified by the customer. See drawings for details.	1	

Salescode	Extended Description	Qty	
SCBA BOTTLE STORAGE			
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
3320-0187-495	Cast Products brand (1) SCBA bottle storage with gasketed door and push button latch. Door shall NOT cover the recessed fuel fill if located adjacent to the SCBA storage. Location: driver side rear wheel well offset forward	1	
3320-0187-497	Cast Products brand (1) SCBA bottle storage with gasketed door and push button latch. Door shall NOT cover the recessed fuel fill if located adjacent to the SCBA storage. Location: driver side rear wheel well offset rearward	1	
3320-0187-498	Cast Products brand (1) SCBA bottle storage with gasketed door and push button latch. Door shall NOT cover the recessed fuel fill if located adjacent to the SCBA storage. Location: officer side rear wheel well offset forward	1	
3320-0187-500	Cast Products brand (1) SCBA bottle storage with gasketed door and push button latch. Door shall NOT cover the recessed fuel fill if located adjacent to the SCBA storage. Location: officer side rear wheel well offset rearward	1	
PUMPS			
4005-0031	Rating 1500 GPM.	1	
4005-0196	Hale QMAX 1000-2250 GPM single stage pump. Requires primer option.	1	
PUMP CERTIFICATION			
4475-0000	Pump certification 750-2250 GPM	1	
PUMP OPTIONS			
4015-0008	Zinc anodes for Hale pump (PR), (1) discharge side and (1) intake side.	2	
4015-0012	Pump shift override, side panel mounted.	1	
4015-0018-202	Valve Inlet MIV-E - Hale. Location: driver side pump panel.	1	
4015-0018-203	Valve Inlet MIV-E - Hale. Location: officer side pump panel.	1	
4015-0018-340	Valve Inlet MIV-E - Hale. Location: 5 in. front intake.	1	
4015-0022	Mechanical pump seal - Hale.	1	
4015-0029	Hale pressure relief valve. Hale Qmax, or Qflo only.	1	
4015-0037	Engine throttle, vernier.	1	
4015-0045	Throttle Selection Switch on Pump Operator's Panel for Back-Up of Relief and Throttle System.	1	
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1	
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1	
4015-0056	Air operated master pump drain (upgrade).	1	

Salescode	Extended Description	Qty	
PUMP OPTIONS			
4015-0234	Control for engine cooler. Includes Innovative Controls 1/4 turn valve with "T" handle and label. Requires engine cooler option.	1	
4015-0238	Hale electric primer (oil-less).	1	
INTAKES			
4440-0004-202	2.5" side suction top mount control handle Akron manual valve. Location: driver side pump panel.	1	
4440-0014	5" front intake without valve. Includes fixed 90 degree elbow above bumper when swivel option not selected. (Requires NST adapter if no swivel).	1	
INTAKE OPTIONS			
4445-0005	Front intake swivel 6" polished chrome.	1	
4445-0023	Recessed front suction intake swivel in bumper, 3" in tray.	1	
DISCHARGES AND PRECONNECTS			
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1	
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1	
4415-0016-584	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2.	1	
4415-0041	3" Deck Gun Discharge, Akron manual valve. (outlet shall terminate with MNPT threads unless extend gun is install)	1	
4415-0065	1.5" Double Speedlay with Akron Manual Valves.	1	
4415-1219-583	4" Panel discharge w/ Akron electric valve and cap. Requires valve controller option. Location: right side discharge 1.	1	
4415-1280-229	4" Rear discharge w/ Akron electric valve and cap. Requires valve controller option. Location: driver rear.	1	
4417-0106-L65	Deck gun piping to be positioned centered in deck gun channel.	1	
DISCHARGE OPTIONS			
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	8	
4417-0186	Innovative Controls discharge and intake bezels with color code and verbiage for top mount pump panel.	1	
4417-0188	TM Valve controls to be Innovative Controls Twist-Lock handles.	11	
4417-0246	Dealer/Customer installed monitor, nozzle and/or tips, make and model as specified.	1	

Salescode	Extended Description	Qty	
DISCHARGE OPTIONS			
4417-0313-229	Akron 9333 Navigator Pro 2 electric valve controller with full color LCD display. Locate on pump operator panel to control driver rear.	1	
4417-0313-583	Akron 9333 Navigator Pro 2 electric valve controller with full color LCD display. Locate on pump operator panel to control right side discharge 1.	1	
4417-0400	12"- 18" service loop added to all pump and discharge drains at the pump panel to aid with servicing the pump when removing the pump panel	1	
BOOSTER REEL			
4405-0020	Booster Reel. Reel to have capacity of 200' of 1" (not included). Requires rewind switch selection. Locate rear body compartment.	1	
4405-0047	Drop down booster reel mounted roller assembly. For use with compartment mounted booster reel.	1	
PRESSURE GOVERNORS			
4465-0011	Class 1 TPG pressure governor. Includes, water, oil, volt and tachometer.	1	
GAUGES			
4435-0026-350	Flowminder System. Discharge: left rear discharge.	1	
4435-0026-583	Flowminder System. Discharge: right side discharge 1.	1	
4435-0069	Class 1 ENFO IV system on pump operator's panel.	1	
4435-0083	Innovative Controls 10 LED SL series water tank level gauge. On pump panel.	1	
4435-0084	Innovative Controls 10 LED series foam tank level gauge. On pump panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	8	
4435-0247	4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400.	1	
4435-0273	Class 1 flow meter totalizer button. Location Pump operator panel.	1	
FOAM SYSTEMS			
4430-0045-562	95 GPM Akron Foam Eductor. Location: 1.5 first speedlay.	1	
4430-0079	The foam system performance shall be tested and certified in compliance with the applicable NFPA 1901 requirements.	1	
ELECTRICAL SYSTEMS			
5010-0036	V-MUX Electrical system for pumper / tanker / rescue.	1	
5010-0049	Vehicle data recorder - 2009 / 2016 NFPA compliant. Includes occupant detection shown in multiplex display. E-ONE chassis only.	1	
5010-0055-168	Vista IV display for V-MUX electrical system. Location: officer's side engine cover.	1	

Salescode	Extended Description	Qty	
ELECTRICAL SYSTEMS			
5010-0055-649	Vista IV display for V-MUX electrical system. Location: driver's side engine cover.	1	
5010-0074	Special programming for multiplex color or text display (per hour). Requires engineering review and approval to determine feasibility and time.	1	
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
LIGHT BARS			
5300-0391-034	Light bar Federal Signal Split Vision VSLR8. Two (2) 26.5" 4-pod light bars. Driver w/ (2) red and (2) multi-color pods with clear lenses; officer w/ (3) red and (1) multi-color pods with clear lenses. Location: front cab corners.	1	
5300-0392-08X	Front Federal Signal VSLR multi-color pod programming: driver side pods to be blue, officer to be clear and change to red with park brake. (If applicable, includes side facing when colors are the same.)	1	
WARNING LIGHTS			
5550-0067	Flash rate for Federal QuadraFlare and/or FireRay LED lower level warning lights to be set at QuadFlash 75 - Simultaneous.	1	
5600-0306-F21	Opticom Emitter GTT 794H. LED emitter and control only. Location and activation: front of cab behind grille.	1	
5600-0377-479	Federal Signal Vision LED rotating beacons with clear lenses model VSLR1-R2A02 with rear facing IPX6 amber LED warning light. Location: rear upper body on aerial style brackets.	1	
5600-0680-0BT-5D	Warning light Federal Signal FireRay model FR6 LED (PR) BLUE with BLUE lenses. Surface mounted with bezel. Location: (1) each side rear of body midway between tail lights and upper warning lights.	1	
5600-0680-3RE-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone front facing.	1	
5600-0680-3RF-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone forward side facing.	1	
5600-0680-3RG-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone midship side facing.	1	
5600-0680-3RI-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side NFPA/ULC required lower zone rear facing.	1	
5600-0680-457-9Y	Warning light Federal Signal FireRay model FR6 LED (PR) AMBER with AMBER lenses. Surface mounted with bezel. Location: (1) each side of body rear facing	1	

Salescode	Extended Description	Qty	
WARNING LIGHTS			
	up high.		
5600-0680-464-4U	Warning light Federal Signal FireRay model FR6 LED (PR) RED with RED lenses. Surface mounted with bezel. Location: (1) each side of cab down low just ahead of rear doors.	1	
5600-0773-3RH-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone rear side facing. Note: MicroPulse Series lights are only available with clear lenses.	1	
5600-0773-469-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side centered below forward compartments in rubrail if equipped. Note: MicroPulse Series lights are only available with clear lenses.	1	
5600-0773-470-4T	Warning light Federal Signal Micro Pulse Ultra model MPS3 LED w/ bezel (PR) RED with CLEAR lenses. Location: (1) each side rear facing (angled portions of Boston style tailboard as applicable) corners of tailboard in rubrail if equipped. Note: MicroPulse Series lights are only available with clear lenses.	1	
5600-0850-170	Hazard (door ajar) light TecNiq S38 LED red. Location: center overhead.	1	
DIRECTIONAL LIGHT BARS			
5310-0020-846	Directional light bar control is to be located center overhead console offset to driver side.	1	
5310-0025	Directional light circuit wiring through upper level warning.	1	
5310-0156	Light bar Federal Signal MicroPulse Signal Master LED 32" with 6 lights.	1	
SIRENS			
5500-0011-209	Federal Q2B siren - Pedestal mounted on bumper. Location: driver side front bumper. Requires activation switch.	1	
DOT LIGHTING			
5150-0025	Marker light Truck-Lite LED body/cab package. E-One custom cab and pumper or tanker body only.	1	
5150-0080-460	Weldon auxiliary turn signal model 9186-8580 LED (PR). Location: (1) each side of cab centered over wheel well.	1	
5150-0149	License plate light incandescent with chrome housing located at the rear of the body below tailboard/body.	1	
5150-0205	Federal Signal FireRay LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical 4 housing and weatherproof connectors.	1	

Salescode	Extended Description	Qty	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0162	Light recessed step Truck-Lite LED. Locate one each side of top mount walkway.	1	
5380-0182	Ground light package EON LED - large.	1	
5380-0311	Compartment light package Hansen LED for medium bodies. Includes two lights per compartment (four if transverse).	1	
5380-0315	Compartment light Hansen white LED for medical cabinet (EA).	5	
5380-0323	The auxiliary steps below the cab doors and/or below pump module/body (if applicable) to have EON LED lights to illuminate the stepping surface and ground below (IPO lights indicated in the main ground light package).	1	
LIGHTS - DECK AND SCENE			
5390-0007	Deck/scene light circuit wiring through chassis reverse. Requires rear deck or scene light.	1	
5390-0058-395	Deck Lights - Truck-Lite LED model 81380 (PR). Location: rear body/beavertail area on the trailing edge up high.	1	
5390-0251	Hose bed light Federal Signal 64LEDCENE. Locate at the front area of hose bed. Switched with work light switch in cab.	2	
5390-0264-457	FireTech FT-GESM scene lights (PR) with chrome flange (when required) and weatherproof connectors. Switch in cab (driver and officer side lights switched separately). Locate: (1) each side of body rear facing up high.	1	
LIGHTS - NON-WARNING			
5400-0185	LED pump compartment light (EA).	1	
5400-0224	Engine compartment light Optronics LED Series ILL22 (EA).	1	
5400-0260	TecNiq model E10 pump panel LED light package - top mount. Includes (2) lights per side pump panel and (3) lights for top mount panel. Side pump panels over 45" wide may require additional lights. Top mount only.	1	
CONTROLS / SWITCHES			
1750-0034-A24	Switch, additional 12 volt/15 amp. Location and function: driver rear of body for rear work lights.	1	
5100-0001-2BH	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: pump operator panel for driver side 12v scene/flood lights.	1	
5100-0001-2BI	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: pump operator panel for officer side 12v scene/flood lights.	1	
5100-0001-2BJ	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: pump operator panel for rear 12v	1	

Salescode	Extended Description	Qty	
CONTROLS / SWITCHES			
	scene/flood lights.		
5100-0001-2BK	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: pump operator panel for front 12v scene/flood lights.	1	
5100-0022-2LL	Push-button hose reel switch. Location: B1 bracket mounted on driver side wall.	1	
5100-0036-3CR	Additional programming instructions: front facing cab Firetech light to activate with single switch.	1	
5100-0036-Z04	Additional programming instructions: provide node programming for dealer supplied Vogel Lubrication System in pump module (or near aerial crade on aerals with no pump module).	1	
5100-0046	Cut-off switch for Q2B main power. Switch to be accessible from driver's seat.	1	
5100-0165	Audible door ajar alarm wired through door ajar light. For use with multiplex display(s) only.	1	
CAMERAS / INTERCOM			
5350-0070	Voyager back-up camera. Video displays automatically when transmission is in reverse. Camera only - does not include monitor.	1	
5350-0071	Voyager side mtd rear facing camera positioned up high on officer side of the cab centrally located (above canopy window if applicable) interlocked with right turn signal. Camera only - does not include monitor.	1	
MISC ELECTRICAL			
5110-0004	Alternating flasher for headlights. Not available on Ford chassis.	1	
5110-0005	Pre-wire for trailer hitch. Includes stop, left turn, right turn, marker and ground wires. Does not include connector.	1	
5110-0008	Audible indicator in cab with rear buttons. The rear buttons will be located one each side at the rear, behind the hand rail (if equipped).	1	
5110-0017	Back-up alarm 97 dB.	1	
5110-0041	7 pin trailer wiring connector. Requires trailer wiring pre-wire option.	1	
5110-0044	ABS cover for multiplex PDM's located in the pump module.	1	
5110-0219-170	Blue Sea 12V power distribution module model 5032. Location: center overhead.	1	
5110-0219-4S6	Blue Sea 12V power distribution module model 5032. Location: as specified. C/A to note in Baan specific locations per customer specification.	1	
5110-0219-762	Blue Sea 12V power distribution module model 5032. Location: behind officer's seat.	1	
5110-0355	Additional ground strap from the mechanical siren to chassis frame.	1	

Salescode	Extended Description	Qty	
LIGHTS - AREA			
5450-0321	FireTech 75" 12V brow light with integrated marker lights and black housing. Includes switch accessible to driver. Replaces front brow marker lights. Requires special bracket 5450-0340 on aerials with waterway trough. Not available on aerials with deep trough.	1	
5450-0395-493	FireTech 35" 12V mini brow light with black housing and flood optics. Includes switch in cab (driver and officer side facing lights switched separately). Location: driver and officer side over rear cab door	2	
5450-0797-2RK	FireTech BG2 72" 12V scene light with black housing. Includes switch accessible to driver. Side facing lights switched separately. Location: (1) each side of body centered (as close as possible) on compartment top(s).	2	
5450-0903	Firetech BG2 light shall be configured as "smart" version with built in alternating red/blue warning lights. Quantity is per side of apparatus with lights configured. Warning lights to flash when upper warning is activated. Scene lighting control to override warning lights when activated.	2	
RECEPTACLES			
5470-0004-01J	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: driver side of vista medical cabinet.	1	
5470-0004-4S6	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: as specified. C/A to note in Baan specific locations per customer specification.	2	
HOSE / NOZZLES			
7700-0006	Booster hose 100' long, 1" 800 PSI.	2	
7700-0007	Akron 1" 60gpm Pistol Grip Assault Nozzle	1	
GROUND LADDERS			
7800-0016	Alco-Lite PEL-24' 2-section extension ladder.	1	
7800-0032	Alco-Lite FL-10, 10' folding ladder w/safety shoes.	1	
7800-0101	Alco-Lite DRL-14' roof ladder.	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
EXTERIOR PAINT			
8100-0084	All applicable pump/pre-connect application modules are to have a job color finish. Includes upper and lower pump modules, crosswalk module and/or	1	

Salescode	Extended Description	Qty	
EXTERIOR PAINT			
	speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.		
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0176-000-26	Paint E-ONE chassis cab - Sikkens paint (non-metallic color). Color: FLNA 3047 E-ONE RED.	1	
8100-0182-000-26	Paint Body - Small - For Pumpers, Rear Mounts, S/A Tankers/Wetsides and Rescues. Sikkens paint (non-metallic color). Color: FLNA 3047 E-ONE RED.	1	
8100-0222	Paint roll up door header plate(s) job color for all painted roll-up doors.	1	
8100-0396	Undercoating E-ONE. To be applied after customer final inspection.	1	
8100-0501	Paint each body compartment lower door opening edge with Scorpion polyurethane coating. Color: Job Color.	1	
8100-0589	Paint each cab door opening at the rear vertical edges that is rolled back and over 1" on both sides with Scorpion polyurethane coating. Including behind each exterior handrail the same size as a scuff plate between the cab and handrail. Color: Job Color.	1	
8100-0614	Paint each exterior cab compartment lower door opening edge with Scorpion polyurethane coating. Color: Job Color.	1	
8100-0798	Paint rear cab extrusions. Same height as rear cab diamond plate overlay panels.	1	
INTERIOR PAINT			
8150-0011	The interior of the cab to be painted multi-tone gray finish.	1	
8150-0024	The lower area of the painted cab interior door panels to be masked off and left un-painted for reflective material.	1	
PROTECTIVE COATINGS			
1160-0149	LINE-X bumper package: Includes all visible diamond plate/smooth aluminum surfaces including gravel shield, exterior surface of trays and lids(flat or raised). If equipped, exterior of the fabricated booster reel housing, fabricated box for booster reel rollers and winch access door shall be included in this package.	1	
1640-0036	LINE-X package for custom cab steps: Includes cab step wells (everything below the cab floor) and all welded and bolt on steps including stirrup and swing out steps as applicable. Steps hanging below the cab shall have LINE-X coating inside and outside. DEF tank door or any other access doors are also included in this package if located in the step well area below the cab floor.	1	
3130-0646	LINE-X package for top mount pump module: Includes exterior surfaces of all running boards (including speedlay running boards if applicable), exterior surface of runningboard trays and lids, intermediate steps, stirrup steps and all fabricated	1	

Salescode	Extended Description	Qty	
PROTECTIVE COATINGS			
	mounting plates installed under the module or body for plumbing options like drains, bleeders, stirrup style switch etc. as applicable. Also includes walkway and walkway steps.		
3340-0994	LINE-X package for Pumper or Tanker body (excluding eMAX), see specification for more details. Does not include LINE-X finish on hosebed cover(added separately).	1	
8100-0495	LINE-X: One or more components installed on this unit shall have LINE-X coating. Color shall be Black unless otherwise specified.	1	
8175-0088	LINE-X pump module exterior: Includes exterior surfaces of all diamond plate visible from the side of the truck. Also includes slide-out platform, backboard storage doors, recessed platework or any other platework/doors on the pump module visible from the side of the truck.	1	
STRIPING			
8300-0001	NFPA required reflective striping to be dealer/customer applied.	1	
8300-0101	Black rubrail scotchlite insert.	1	
8300-0274-000-J7	Chevron "A" style 6" Reflexite V98 striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0381	Yellow perimeter marking to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901 consisting of individual Reflexite diamonds approximately 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0101	Meritor 5 year / unlimited miles parts and labor warranty for front non-drive axle. Exceptions: MFS rated at 22,800 includes a 2 year / 200K miles parts and labor warranty and a front drive axle includes a 2 year / unlimited miles parts and labor warranty.	1	
9100-0102	Meritor 5 year unlimited miles, parts and labor rear drive single or rear drive tandem axle warranty.	1	
9100-0117	General One (1) year or 24,000 Miles Limited Warranty (RFW00001)	1	
9100-0126	Custom chassis One (1) Year or 18,000 Miles Limited Warranty (RFW0101).	1	
9100-0131	Regulated Emissions Systems Five (5) Years or 100,000 Miles Limited Warranty (RFW0140). N/A for California. For units going to California use 9100-0162 with L9 and 9100-0163 with X12/15.	1	
9100-0132	Electrical One (1) Year or 18,000 Miles Limited Warranty (RFW0201).	1	

Salescode	Extended Description	Qty	
WARRANTY / STANDARD & EXTENDED			
9100-0136	Body Structure Aluminum Ten (10) years or 100,000 Miles Limited Warranty (RFW0502).	1	
9100-0138	Cab Structural Ten (10) Years or 100,000 Miles Limited Warranty (RFW0602).	1	
9100-0139	Plumbing and piping (Stainless Steel) Ten (10) years or 100,000 Miles Limited Warranty (RFW0800).	1	
9100-0140	Paint and Finish (Exterior Clear coated) Ten (10) Years Limited Warranty (RFW0710).	1	
9100-0151	Frame Rail Corrosion (Zinc Plate and Powder Coat) Twenty Five (25) Years or 150,000 Miles Limited Warranty (RFW0316).	1	
9100-0152	Frame Components Corrosion (Zinc Plate) Twenty (20) Years or 132,000 Miles Limited Warranty (RFW0314).	1	
9100-0165	Frame Rail Lifetime (50) Years or 250,000 Miles Limited Warranty (RFW0305).	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0012	Pump panel approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0016	Approval Drawings-Standard.	1	
9300-0031	Dash/Console panel layout approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
Dealer Supplied Equipment			