

ROOM FINISH SCHEDULE															
ROOM NUM.	ROOM	WALLS								FLR.	CEILING				
		EAST	BASE	WEST	BASE	NO.	BASE	SO.	BASE	MTL.	MTL.	HEIGHT	NOTE		
100 SERIES NOT ON SCHEDULE = NO WORK															
107	BAR	FRP/PT1	CB2	FRP/PT1	CB2	FRP/PT1	CB2	FRP/PT1	CB2	CT2	SCT	10'-0	1		
110	DISH WASH	FRP/PT1	CB2	FRP/PT1	CB2	FRP/PT1	CB2	FRP/PT1	CB2	CT2	SCT	10'-0	1		
200	TENANT														
201	DINING	PT2	VB1	PT2	VB1	PT2	VB1	PT2	VB1	CT2	ACT	10'-0	1		
202	OFFICE	PT2	VB1	PT2	VB1	PT2	VB1	PT2	VB1	CT2	GYP.	10'-0	1		
203	DRY STO.	PT2	VB1	PT2	VB1	PT2	VB1	PT2	VB1	CT2	GYP.	10'-0	1		
204	WOMAN												2		
205	MEN												2		
206	STAIR												2		
	2x4 VINYL FACED SANITARY GYP. BD. CEILING TILE W/ 15/16 GRID VERIFY HEIGHT IN FIELD			EXISTING VINYL COMP TILE AND VB			FIBERGLASS REINF. WALL PANEL LIGHT COLOR TO 8'-0"		NOTES: 1. PATCH FINISHES TO MATCH FROM MINOR WORK 2. NO WORK TO MATCH FROM MINOR WORK						
	2x4 FINE TEXTURE ACOUSTIC CEILING TILE REVEAL EDGE W/ 15/16 GRID VERIFY HEIGHT IN FIELD			SEMIGLOSS LATEX 2 COATS COLOR TO BE SELECTED OVER 1 COAT PRIMER ABOVE FRP			1" COVED VINYL BASE								
	PORCELAIN CERAMIC 4x12 MATCHING BASE			EGGSHELL LATEX 2 COATS COLOR TO BE SELECTED OVER 1 COAT PRIMER		SMOKE AND FLAME SPREAD FINISH RATINGS: STAIRS: CLASS A OTHER: CLASS C (OCCUPANCY <300)									
DOOR SCHEDULE															
DOOR	ROOM	MATL.	FRAME	HDWR.	CLSR.	TYPE	REMARKS								
EXIST. = EXISTING VERIFY 36" WIDE W/ LEVER OR PANIC HARDWARE WITH SINGLE ACTION NO SPECIAL KNOWLEDGE															
101	STAIR	SCWD	H.M.	PANIC	Y	A	90 MIN. FIRE RATED MAGNETIC HOLD OPEN ON ALARM								
102	COOLER	ALUM	ALUM	LEVER	N	COOLER	INTERIOR SAFETY RELEASE								
103	VACANT	SCWD	H.M.	STORAGE	Y	A									
DOOR HARDWARE PERFORMANCE:															
- ALL LATCH SETS TO BE ADA SCHLAGE STANDARD DUTY COMMERCIAL BRUSHED STN. STL. LEVER TYPE NEPTUNE				- HARDWARE FUNCTION AS DEFINED BY SCHLAGE				- WALK IN COOLER AND FREEZER DOORS TO BE EQUIPPED WITH INTERIOR EXITING LATCH RELEASE							
- ALL DOORS TO HAVE 1 1/2 PAIR STN. STL. BALL BEARING HINGES				- ALL PUSH PULL, PANIC AND PADDLE TO BE BRUSHED STN. STL.											
- ALL DEAD BOLTS TO BE KEYLESS LEVER TYPE				- ALL CLOSERS TO BE 8 LB. PULL AT AT EXTERIOR 4# AT INTERIOR											
- ALL LOCK FUNCTIONS SHALL BE KEYLESS IN DIRECTION OF EGRESS SINGLE ACTION WITHOUT REQUIRING SPECIAL KNOWLEDGE				- PAINT ALL HOLLOW MTL. DOORS AND FRAMES 2 COAT SEMI-GLOSS COLOR TO MATCH STOREFRONT											
				- SUBMIT CUT SHEETS, SUBMITTALS AND SAMPLES TO OWNER FOR APPROVAL AS REQUESTED											
				ALL THRESHOLDS SHALL BE 1/2"											
				MAX.											